

AIR PERMIT

PERMITTEE: Southern Alabama Limestone, LLC

FACILITY NAME: St. Stephens Quarry

LOCATION: St. Stephens, Alabama

<u>PERMIT NUMBER</u>	<u>DESCRIPTION OF EQUIPMENT, ARTICLE OR DEVICE</u>
108-0025-X002	250 TPH Portable Crushing, Screening, Conveying, and Loadout Circuit with Wet Suppression (NSPS)

In accordance with and subject to the provisions of the Alabama Air Pollution Control Act of 1971, Ala. Code §§ 22-28-1 to 22-28-23, as amended, the Alabama Environmental Management Act, Ala. Code §§ 22-22A-1 to 22-22A-17, as amended, and rules and regulations adopted there under, and subject further to the conditions set forth in this permit, the Permittee is hereby authorized to construct, install and use the equipment, device or other article described above.

ISSUANCE DATE: Date

Provisos
Southern Alabama Limestone, LLC
Facility No. 108-0025
Unit No. X002

1. This permit is issued on the basis of Rules and Regulations existing on the date of issuance. In the event additional Rules and Regulations are adopted, it shall be the permit holder's responsibility to comply with such rules.
2. This permit is not transferable. Upon sale or legal transfer, the new owner or operator must apply for a permit within 30 days.
3. A new permit application must be made for new sources, replacements, alterations or design changes which may result in the issuance of, or an increase in the issuance of, air contaminants, or the use of which may eliminate or reduce or control the issuance of air contaminants.
4. The permittee shall keep this permit under file or on display at all times at the site where the facility for which the permit is issued is located and shall make the permit readily available for inspection by any or all persons who may request to see it.
5. Each point of emission, which requires testing, will be provided with sampling ports, ladders, platforms, and other safety equipment to facilitate testing performed in accordance with procedures established by Part 60 of Title 40 of the Code of Federal Regulations, as the same may be amended or revised.
6. All air pollution control equipment shall be operated at all times while this process is operational. In the event of scheduled maintenance, unscheduled maintenance, or a breakdown of the pollution control equipment, the process shall be shutdown as expeditiously as possible (unless this act and subsequent re-start would clearly cause greater emissions than continuing operations of the process for a short period). The Department shall be notified of all such events **that exceed 1 hour** within 24 hours. The notification shall include all pertinent facts, including the duration of the process operating without the control device and the level of excess emissions which have occurred. Records of all such events, regardless of reporting requirements, shall be made and maintained for a period of five years. These records shall be available for inspection.
7. This process, including all air pollution control devices and capture systems for which this permit is issued shall be maintained and operated at all times in a manner so as to minimize the emissions of air contaminants. Procedures for ensuring that the above equipment is properly operated and maintained so as to minimize the emission of air contaminants shall be established.

Permit Number 108-0025-X002

8. This permit expires and the application is cancelled if construction has not begun within 24 months of the date of issuance of the permit.
9. On completion of construction of the device(s) for which this permit is issued, written notification of the fact is to be submitted to the Chief of the Air Division. The notification shall indicate whether the device(s) was constructed as proposed in the application. The device(s) shall not be operated until authorization to operate is granted by the Chief of the Air Division. Failure to notify the Chief of the Air Division of completion of construction and/or operation without authorization could result in revocation of this permit.
10. Submittal of other reports regarding monitoring records, fuel analyses, operating rates, and equipment malfunctions may be required as authorized in the Department's air pollution control rules and regulations. The Department may require stack emission testing at any time.
11. Prior to a date to be specified by the Chief of the Air Division in the authorization to operate, emission tests are to be conducted by persons familiar with and using the EPA Sampling Train and Test Procedure as described in the Code of Federal Regulations, Title 40, Part 60, for the following pollutants. Written tests results are to be reported to the Air Division within 15 working days of completion of testing.

Particulates	()	Carbon Monoxide	()
Sulfur Dioxide	()	Nitrogen Oxides	()
Volatile Organic Compounds	()	Visible Emissions	(X)

12. Additions and revisions to the conditions of this Permit will be made, if necessary, to ensure that the Department's air pollution control rules and regulations are not violated.
13. Nothing in this permit or conditions thereto shall negate any authority granted to the Department pursuant to the Alabama Environmental Management Act or regulations issued thereunder.
14. This permit is issued with the condition that, should obnoxious odors arising from the plant operations be verified by Air Division inspectors, measures to abate the odorous emissions shall be taken upon a determination by the Alabama Department of Environmental Management that these measures are technically and economically feasible.

Permit Number 108-0025-X002

15. The Air Division must be notified in writing at least 10 working days in advance of all emission tests to be conducted and submitted as proof of compliance with the Department's air pollution control rules and regulations.

To avoid problems concerning testing methods and procedures, the following shall be included with the notification letter:

- (a) The date the test crew is expected to arrive, the date and time anticipated of the start of the first run, how many and which sources are to be tested, and the names of the persons and/or testing company that will conduct the tests.
- (b) A complete description of each sampling train to be used, including type of media used in determining gas stream components, type of probe lining, type of filter

media, and probe cleaning method and solvent to be used (if test procedure requires probe cleaning).
- (c) A description of the process(es) to be tested, including the feed rate, any operating parameter used to control or influence the operations, and the rated capacity.
- (d) A sketch or sketches showing sampling point locations and their relative positions to the nearest upstream and downstream gas flow disturbances.

A pretest meeting may be held at the request of the source owner or the Department. The necessity for such a meeting and the required attendees will be determined on a case-by-case basis.

All test reports must be submitted to the Air Division within 15 days of the actual completion of the test, unless an extension of time is specifically approved by the Air Division.

16. Precautions to prevent fugitive dust shall be taken so that provisions of the Department's rules and regulations shall not be violated.
17. Precautions shall be taken to prevent fugitive dust emanating from plant roads, grounds, stockpiles, screens, dryers, hoppers, ductwork, etc.

Plant or haul roads and grounds shall be maintained in the following manner so that dust will not become airborne. A minimum of one, or a combination, of the following methods shall be utilized to minimize airborne dust from plant or haul roads and grounds:

Permit Number 108-0025-X002

- (a) by the application of water any time the surface of the road is sufficiently dry to allow the creation of dust emissions by the act of wind or vehicular traffic;
- (b) by reducing the speed of vehicular traffic to a point below that at which dust emissions are created;
- (c) by paving;
- (d) by the application of binders to the road surface at any time the road surface is found to allow the creation of dust emissions;

Should one, or a combination, of the above methods fail to adequately reduce airborne dust from plant or haul roads and grounds, alternative methods shall be employed, either exclusively or in combination with one or all of the above control techniques, so that dust will not become airborne. Alternative methods shall be approved by the Department prior to utilization.

- 18. Any performance tests required shall be conducted and data reduced in accordance with the test methods and procedures contained in each specific permit condition unless the Director (1) specifies or approves, in specific cases, the use of a reference method with minor changes in methodology, (2) approves the use of an equivalent method, or (3) approves the use of an alternative method, the results of which he has determined to be adequate for indicating whether a specific source is in compliance.
- 19. If this plant relocates to another site, this plant's Air Permit remains valid for this site unless or until it is revoked for failure to comply with ADEM Air Division Rules and Regulations. The owner or operator of this plant must provide written notification of the intent to relocate the plant to this site at least two weeks in advance. The written notification should include the planned construction beginning date and the projected startup date. Failure to provide this written notification is a violation of this permit condition and is grounds for revocation of this permit.
- 20. All of the equipment associated with this circuit are subject to the New Source Performance Standards (40 CFR 60, Subpart OOO - Standards of Performance for Nonmetallic Mineral Processing Plants) where applicable. This NSPS limits fugitive emissions from uncontrolled crushers to 12% opacity, and fugitive emissions from grinding mills, screening operations, bucket elevators, transfer points on belt conveyors, bagging operations, storage bins, enclosed truck or railcar loading stations, or from any other affected facility to 7 % opacity. This NSPS allows no emissions from wet screening operations.

Permit Number 108-0025-X002

21. Compliance with the opacity standards for sources subject to NSPS-Subpart OOO will be determined by conducting visible emission observations in accordance with the most recent version of EPA Reference Method 9 of Appendix A-4 of the CFR, Title 40, Part 60. When determining compliance with the fugitive emissions standard for grinding mills, screening operations, crushers, transfer points on belt conveyors, bucket elevators, bagging operations, storage bins, or enclosed truck or railcar loading stations or from any other affected facility of this circuit, the duration of the Method 9 observations are required to be 30 minutes or five six minute averages. No more than 3 points may be tested concurrently by the same observer. The specified criteria of NSPS - Subpart OOO must be met.

The observations will be made by an observer currently certified to make EPA Method 9 visible emission observations. The opacity observations will be conducted within 60 days of the source achieving maximum production rate but no later than 180 days of initial start-up of the facility. The visible observation report will be submitted to the Department within 15 days of taking the observations

22. Periodic monitoring is required for all equipment controlled by wet suppression and/or water carryover. Each spray nozzle shall be examined monthly to assure water is appropriately supplied to the nozzle and that the water is sprayed from the nozzle correctly. Any corrective action indicated shall be taken within 24 hours of the inspection.
23. Recordkeeping is required for all monthly periodic monitoring inspections for the quarry equipment. Records shall be kept on the facility site, either in a handwritten log book or in electronic version suitable for inspection upon request by Air Division inspectors and will be retained for at least two years following the date of generation. Records of the inspection date, results, and any corrective action taken shall be recorded. In addition, if wet suppression is not utilized during the inspection, any other control method used should be recorded or circumstances shall be noted.
24. Should this facility, at any time, exceed the limits of this Air Permit, this Department must be notified within 24 hours of the exceedance.
25. The permittee shall not use as a defense in an enforcement action that maintaining compliance with conditions of this permit would have required halting or reducing the permitted activity.
26. The issuance of this permit does not convey any property rights of any sort, or any exclusive privilege.

Permit Number 108-0025-X002

27. Precautions shall be taken by the permittee and its personnel to ensure that no person shall ignite, cause to be ignited, permit to be ignited, or maintain any open fire in such a manner as to cause the Department's rules and regulations applicable to open burning to be violated.

Date