LANCE R. LEFLEUR
DIRECTOR

ROBERT J. BENTLEY
GOVERNOR

Alabama Department of Environmental Management
adem.alabama.gov

1400 Coliseum Blvd. 36110-2400 ▪ Post Office Box 301463
Montgomery, Alabama 36130-1463
(334) 271-7700 ▪ FAX (334) 271-7950

OCT 0 4 2016

Johnny L. Smith, Mayor
Jacksonville Water Works, Gas and Sewer Board
330 Church Avenue SE
Jacksonville, AL 36265

RE: Draft Permit
NPDES Permit No. AL0022586
Jacksonville WWTP
Calhoun County, Alabama

Dear Mr. Smith:

Transmitted herein is a draft of the referenced permit.

We would appreciate your comments on the permit within **30 days** of the date of this letter. Please direct any comments of a technical or administrative nature to the undersigned. Please notice the Mercury limitations have been corrected from mg/L to µg/L.

By copy of this letter and the draft permit, we are also requesting comments within the same time frame from EPA.

Our records indicate that you are currently utilizing the Department's web-based electronic environmental (E2) reporting system for submittal of discharge monitoring reports (DMRs). Your E2 DMRs will automatically update on the effective date of this permit, if issued.

The Alabama Department of Environmental Management encourages you to voluntarily consider pollution prevention practices and alternatives at your facility. Pollution Prevention may assist you in complying with effluent limitations, and possibly reduce or eliminate monitoring requirements.

If you have questions regarding this permit or monitoring requirements, please contact me at (334) 271-7808.

Sincerely,

Dustin Stokes
Municipal Section
Water Division

Enclosure: Draft Permit

cc: Environmental Protection Agency Email
Ms. Elaine Snyder/U.S. Fish and Wildlife Services
Ms. Elizabeth Brown/Alabama Historical Commission
Advisory Council on Historic Preservation
Department of Conservation and Natural Resources

Birmingham Branch
110 Vulcan Road
Birmingham, AL 35209-4702
(205) 942-6168
(205) 941-1603 (FAX)

Decatur Branch
2715 Sandlin Road, S.W.
Decatur, AL 35603-1333
(256) 353-1713
(256) 340-9359 (FAX)

Mobile Branch
2204 Perimeter Road
Mobile, AL 36615-1131
(251) 450-3400
(251) 479-2593 (FAX)

Mobile-Coastal
3664 Dauphin Street, Suite B
Mobile, AL 36608
(251) 304-1176
(251) 304-1189 (FAX)

ADEM
Alabama Department of Environmental Management

NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM PERMIT

PERMITTEE:	JACKSONVILLE WATER WORKS, GAS AND SEWER BOARD 330 CHURCH AVENUE SE JACKSONVILLE, ALABAMA 36265
FACILITY LOCATION:	JACKSONVILLE WWTP (3.5 MGD) 655 NISBET STREET JACKSONVILLE, ALABAMA CALHOUN COUNTY
PERMIT NUMBER:	AL0022586
RECEIVING WATERS:	UNNAMED TRIBUTARY TO TALLASSEEHATCHEE CREEK

In accordance with and subject to the provisions of the Federal Water Pollution Control Act, as amended, 33 U.S.C. §§1251-1388 (the "FWPCA"), the Alabama Water Pollution Control Act, as amended, Code of Alabama 1975, §§ 22-22-1 to 22-22-14 (the "AWPCA"), the Alabama Environmental Management Act, as amended, Code of Alabama 1975, §§22-22A-1 to 22-22A-17, and rules and regulations adopted thereunder, and subject further to the terms and conditions set forth in this permit, the Permittee is hereby authorized to discharge into the above-named receiving waters.

ISSUANCE DATE:

EFFECTIVE DATE:

EXPIRATION DATE:

Draft

Alabama Department of Environmental Management

MUNICIPAL SECTION
NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM (NPDES) PERMIT

TABLE OF CONTENTS

PART I DISCHARGE LIMITATIONS, CONDITIONS, AND REQUIREMENTS 4

A. DISCHARGE LIMITATIONS AND MONITORING REQUIREMENTS 4

1. Outfall 001I Discharge Limits - Monthly 4
2. Outfall 001Q Discharge Limits - Quarterly 5
3. Outfall 001S Discharge Limits – Stormwater 6
4. Outfall 001T Discharge Limits - Toxicity 7

B. DISCHARGE MONITORING AND RECORD KEEPING REQUIREMENTS 8

1. Representative Sampling 8
2. Measurement Frequency 8
3. Test Procedures 8
4. Recording of Results 8
5. Records Retention and Production 9
6. Reduction, Suspension or Termination of Monitoring and/or Reporting 9
7. Monitoring Equipment and Instrumentation 9

C. DISCHARGE REPORTING REQUIREMENTS 9

1. Reporting of Monitoring Requirements 9
2. Noncompliance Notification 11

D. OTHER REPORTING AND NOTIFICATION REQUIREMENTS 12

1. Anticipated Noncompliance 12
2. Termination of Discharge 12
3. Updating Information 12
4. Duty to Provide Information 13

E. SCHEDULE OF COMPLIANCE 13

1. Compliance with discharge limits 13
2. Schedule 13

PART II OTHER REQUIREMENTS, RESPONSIBILITIES, AND DUTIES 14

A. OPERATIONAL AND MANAGEMENT REQUIREMENTS 14

1. Facilities Operation and Maintenance 14
2. Best Management Practices (BMP) 14
3. Certified Operator 14

B. OTHER RESPONSIBILITIES 14

1. Duty to Mitigate Adverse Impacts 14
2. Right of Entry and Inspection 14

C. BYPASS AND UPSET 14

1. Bypass 14
2. Upset 15

D. DUTY TO COMPLY WITH PERMIT, RULES, AND STATUTES 15

1. Duty to Comply 15
2. Removed Substances 15
3. Loss or Failure of Treatment Facilities 15
4. Compliance With Statutes and Rules 16

E. PERMIT TRANSFER, MODIFICATION, SUSPENSION, REVOCATION, AND REISSUANCE 16

1. Duty to Reapply or Notify of Intent to Cease Discharge 16
2. *Change in Discharge* 16
3. Transfer of Permit 16
4. Permit Modification and Revocation 16
5. Termination 17

6. Suspension 17
7. Stay 17
F. COMPLIANCE WITH TOXIC POLLUTANT STANDARD OR PROHIBITION 18
G. NOTICE TO DIRECTOR OF INDUSTRIAL USERS 18
H. PROHIBITIONS 18
PART III ADDITIONAL REQUIREMENTS, CONDITIONS, AND LIMITATIONS 19
A. CIVIL AND CRIMINAL LIABILITY 19
1. Tampering 19
2. False Statements 19
3. Permit Enforcement 19
4. Relief from Liability 19
B. OIL AND HAZARDOUS SUBSTANCE LIABILITY 19
C. PROPERTY AND OTHER RIGHTS 19
D. AVAILABILITY OF REPORTS 19
E. EXPIRATION OF PERMITS FOR NEW OR INCREASED DISCHARGES 20
F. COMPLIANCE WITH WATER QUALITY STANDARDS 20
G. GROUNDWATER 20
H. DEFINITIONS 20
I. SEVERABILITY 23
PART IV SPECIFIC REQUIREMENTS, CONDITIONS, AND LIMITATIONS 24
A. SLUDGE MANAGEMENT PRACTICES 24
1. Applicability 24
2. Submitting Information 24
3. Reopener or Modification 24
B. EFFLUENT TOXICITY LIMITATIONS AND BIOMONITORING REQUIREMENTS FOR CHRONIC TOXICITY 24
1. Chronic Toxicity Test 24
2. General Test Requirements 24
3. Reporting Requirements 25
4. Additional Testing Requirements 25
5. Test Methods 25
6. Effluent Toxicity Testing Reports 25
C. TOTAL RESIDUAL CHLORINE (TRC) REQUIREMENTS 27
D. PLANT CLASSIFICATION 27
E. POLLUTANT SCANS 27
F. STORM WATER REQUIREMENTS 27

ATTACHMENT:
FORM 421 NON-COMPLIANCE NOTIFICATION FORM

PART I DISCHARGE LIMITATIONS, CONDITIONS, AND REQUIREMENTS

A. DISCHARGE LIMITATIONS AND MONITORING REQUIREMENTS

1. Outfall 0011 Discharge Limits - During the period beginning on the effective date of this permit and lasting through the expiration date of this permit, the Permittee is authorized to discharge from Outfall 0011, which is described more fully in the Permittee's application. Such discharge shall be limited and monitored by the Permittee as specified below:

	Discharge Limitations*							Monitoring Requirements**			
Parameter	Monthly Average	Weekly Average	Monthly Average	Weekly Average	Daily Minimum	Daily Maximum	Percent Removal	(1) Sample Location	(2) Sample Type	(3) Measurement Frequency	(4) Seasonal
Oxygen, Dissolved (DO) 00300 1 0 0	*****	*****	*****	*****	6.0 mg/l	*****	*****	E	GRAB	C	*****
pH 00400 1 0 0	*****	*****	*****	*****	6.0 S.U.	8.5 S.U.	*****	E	GRAB	C	*****
Solids, Total Suspended 00530 G 0 0	REPORT lbs/day	REPORT lbs/day	REPORT mg/l	REPORT mg/l	*****	*****	*****	I	COMP24	C	*****
Solids, Total Suspended 00530 1 0 0	875 lbs/day	1313 lbs/day	30.0 mg/l	45.0 mg/l	*****	*****	*****	E	COMP24	C	*****
Nitrogen, Ammonia Total (As N) 00610 1 0 0	58.3 lbs/day	87.5 lbs/day	2.0 mg/l	3.0 mg/l	*****	*****	*****	E	COMP24	C	S
Nitrogen, Ammonia Total (As N) 00610 1 0 0	87.5 lbs/day	131 lbs/day	3.0 mg/l	4.5 mg/l	*****	*****	*****	E	COMP24	C	W
Nitrogen, Kjeldahl Total (As N) 00625 1 0 0	REPORT lbs/day	REPORT lbs/day	REPORT mg/l	REPORT mg/l	*****	*****	*****	E	COMP24	G	*****
Nitrite Plus Nitrate Total 1 Det. (As N) 00630 1 0 0	REPORT lbs/day	REPORT lbs/day	REPORT mg/l	REPORT mg/l	*****	*****	*****	E	COMP24	G	*****
Phosphorus, Total (As P) 00665 1 0 0	REPORT lbs/day	REPORT lbs/day	REPORT mg/l	REPORT mg/l	*****	*****	*****	E	COMP24	G	*****
Zinc Total Recoverable (7) 01094 1 0 0	*****	*****	582 µg/L	*****	*****	582 µg/L	*****	E	GRAB	G	*****
Flow, In Conduit or Thru Treatment Plant 50050 1 0 0	REPORT MGD	*****	*****	*****	*****	REPORT MGD	*****	E	CONTIN	A	*****
Chlorine, Total Residual See note (5) (6) 50060 1 0 0	*****	*****	0.02 mg/l	*****	*****	0.03 mg/l	*****	E	GRAB	C	*****
E. Coli 51040 1 0 0	*****	*****	126 col/100mL	*****	*****	487 col/100mL	*****	E	GRAB	C	ECS
E. Coli 51040 1 0 0	*****	*****	548 col/100mL	*****	*****	2507 col/100mL	*****	E	GRAB	C	ECW
BOD, Carbonaceous 05 Day, 20C 80082 G 0 0	REPORT lbs/day	REPORT lbs/day	REPORT mg/l	REPORT mg/l	*****	*****	*****	I	COMP24	C	*****
BOD, Carbonaceous 05 Day, 20C 80082 1 0 0	729 lbs/day	1094 lbs/day	25.0 mg/l	37.5 mg/l	*****	*****	*****	E	COMP24	C	*****
BOD, Carb-5 Day, 20 Deg C, Percent Remvl 80091 K 0 0	*****	*****	*****	*****	*****	*****	85.0%	K	CALCTD	G	*****
Solids, Suspended Percent Removal 81011 K 0 0	*****	*****	*****	*****	*****	*****	85.0%	K	CALCTD	G	*****

* See Part II.C.1. (Bypass); Part II.C.2. (Upset)

** Monitoring Requirements

(1) Sample Location
I – Influent
E – Effluent
X – End Chlorine Contact Chamber
K - Percent Removal of the Monthly Avg. Influent Concentration from the Monthly Avg. Effluent Concentration.
RS - Receiving Stream

(2) Sample Type:
CONTIN - Continuous
INSTAN - Instantaneous
COMP-8 - 8-Hour Composite
COMP24 - 24-Hour Composite
GRAB – Grab
CALCTD - Calculated

(3) Measurement Frequency: See also Part I.B.2.
A - 7 days per week
B - 5 days per week
C - 3 days per week
D - 2 days per week
E - 1 day per week
F - 2 days per month
G - 1 day per month
H - 1 day per quarter
J - Annual
Q - For Effluent Toxicity Testing, see Provision IV.B.

(4) Seasonal Limits:
S = Summer (May – November)
W = Winter (December - April)
ECS = E. coli Summer (June – September)
ECW = E. coli Winter (October – May)

(5) See Part IV.C. for Total Residual Chlorine (TRC). Monitoring for TRC is applicable if chlorine is utilized for disinfection purposes. If monitoring is not applicable during the monitoring period, enter "NODI=9" on the monthly DMR.

(6) A measurement of Total Residual Chlorine below 0.05 mg/L shall be considered in compliance with the permit limitations above and should be reported as NODI=B or *B on the discharge monitoring reports.

(7) If only one sampling event occurs during a monitoring period, the sample result shall be reported on the DMRs as both the monthly average and daily maximum.

2. Outfall 001Q Discharge Limits - Quarterly

This is an administrative outfall designation. Outfall 001Q is the same physical outfall as Outfall 0011. Discharge from this outfall shall be limited and monitored by the Permittee as specified below:

Parameter	Discharge Limitations*							Monitoring Requirements**			
	Monthly Average	Weekly Average	Monthly Average	Weekly Average	Daily Minimum	Daily Maximum	Percent Removal	(1) Sample Location	(2) Sample Type	(3) Measurement Frequency	(4) Seasonal
Mercury Total Recoverable (5) (6) 71901 1 0 0	*****	*****	0.022 µg/l	*****	*****	3.93 µg/l	*****	E	GRAB	H	*****

* See Part II.C.1. (Bypass); Part II.C.2. (Upset)
** Monitoring Requirements

(1) Sample Location
I – Influent
E – Effluent
X – End Chlorine Contact Chamber
K - Percent Removal of the Monthly Avg. Influent Concentration from the Monthly Avg. Effluent Concentration.
RS - Receiving Stream

(2) Sample Type:
CONTIN - Continuous
INSTAN - Instantaneous
COMP-8 - 8-Hour Composite
COMP24 - 24-Hour Composite
GRAB – Grab
CALCTD - Calculated

(3) Measurement Frequency: See also Part I.B.2.
A - 7 days per week
B - 5 days per week
C - 3 days per week
D - 2 days per week
E - 1 day per week
F - 2 days per month
G - 1 day per month
H - 1 day per quarter
J - Annual
Q - For Effluent Toxicity Testing, see Provision IV.B.

(4) Seasonal Limits:
S = Summer (May – November)
W = Winter (December - April)
ECS = E. coli Summer (June – September)
ECW = E. coli Winter (October – May)

(5) EPA Methods 1631 E/1669, or alternative methods specifically approved by the Department, shall be used for the analysis of this parameter.

(6) If only one sampling event occurs during a monitoring period, the sample result shall be reported on the DMRs as both the monthly average and daily maximum.

3. Outfall 001S Discharge Limits – Stormwater

During the period beginning on the effective date of this permit and lasting through the expiration date of this permit, the Permittee is authorized to discharge from Outfall 001S, which is described more fully in the Permittee's application. Such discharge shall be limited and monitored by the Permittee as specified below:

Parameter	Discharge Limitations*							Monitoring Requirements**			
	Monthly Average	Weekly Average	Monthly Average	Weekly Average	Daily Minimum	Daily Maximum	Percent Removal	(1) Sample Location	(2) Sample Type	(3) Measurement Frequency	(4) Seasonal
pH 00400 1 0 0	*****	*****	*****	*****	REPORT S.U.	REPORT S.U.	*****	E	GRAB	J	*****
Solids, Total Suspended 00530 1 0 0	*****	*****	*****	*****	*****	REPORT mg/l	*****	E	GRAB	J	*****
Oil & Grease 00556 1 0 0	*****	*****	*****	*****	*****	15 mg/l	*****	E	GRAB	J	*****
Nitrogen, Ammonia Total (As N) 00610 1 0 0	*****	*****	*****	*****	*****	REPORT mg/l	*****	E	GRAB	J	*****
Nitrogen, Kjeldahl Total (As N) 00625 1 0 0	*****	*****	*****	*****	*****	REPORT mg/l	*****	E	GRAB	J	*****
Nitrite Plus Nitrate Total 1 Det. (As N) 00630 1 0 0	*****	*****	*****	*****	*****	REPORT mg/l	*****	E	GRAB	J	*****
Phosphorus, Total (As P) 00665 1 0 0	*****	*****	*****	*****	*****	REPORT mg/l	*****	E	GRAB	J	*****
Flow, In Conduit or Thru Treatment Plant 50050 1 0 0	*****	*****	*****	*****	*****	REPORT MGD	*****	E	CALCTD	J	*****
Chlorine, Total Residual See note (5) 50060 1 0 0	*****	*****	*****	*****	*****	REPORT mg/l	*****	E	GRAB	J	*****
E. Coli 51040 1 0 0	*****	*****	*****	*****	*****	REPORT col/100mL	*****	E	GRAB	J	*****
BOD, Carbonaceous 05 Day, 20C 80082 1 0 0	*****	*****	*****	*****	*****	REPORT mg/l	*****	E	GRAB	J	*****

* See Part II.C.1. (Bypass); Part II.C.2. (Upset)
** Monitoring Requirements

(1) Sample Location
I – Influent
E – Effluent
X – End Chlorine Contact Chamber
K - Percent Removal of the Monthly Avg. Influent Concentration from the Monthly Avg. Effluent Concentration.
RS - Receiving Stream

(2) Sample Type:
CONTIN - Continuous
INSTAN - Instantaneous
COMP-8 - 8-Hour Composite
COMP24 - 24-Hour Composite
GRAB – Grab
CALCTD - Calculated

(3) Measurement Frequency: See also Part I.B.2.
A - 7 days per week
B - 5 days per week
C - 3 days per week
D - 2 days per week
E - 1 day per week
F - 2 days per month
G - 1 day per month
H - 1 day per quarter
J - Annual
Q - For Effluent Toxicity Testing, see Provision IV.B.

(4) Seasonal Limits:
S = Summer (May – November)
W = Winter (December - April)
ECS = E. coli Summer (June – September)
ECW = E. coli Winter (October – May)

4. Outfall 001T Discharge Limits - Toxicity

This is an administrative outfall designation. Outfall 001T is the same physical outfall as Outfall 0011. Discharge from this outfall shall be limited and monitored by the Permittee as specified below:

Parameter	Discharge Limitations*							Monitoring Requirements**			
	Monthly Average	Weekly Average	Monthly Average	Weekly Average	Daily Minimum	Daily Maximum	Percent Removal	(1) Sample Location	(2) Sample Type	(3) Measurement Frequency	(4) Seasonal
Toxicity, Ceriodaphnia Chronic 61426 1 0 0	*****	Pass = 0 Fail = 1	*****	*****	*****	*****	*****	E	COMP24	Q	*****
Toxicity, Pimephales Chronic 61428 1 0 0	*****	Pass = 0 Fail = 1	*****	*****	*****	*****	*****	E	COMP24	Q	*****

* See Part II.C.1. (Bypass); Part II.C.2. (Upset)
** Monitoring Requirements

(1) Sample Location
I – Influent
E – Effluent
X – End Chlorine Contact Chamber
K - Percent Removal of the Monthly Avg. Influent Concentration from the Monthly Avg. Effluent Concentration.
RS - Receiving Stream

(2) Sample Type:
CONTIN - Continuous
INSTAN - Instantaneous
COMP-8 - 8-Hour Composite
COMP24 - 24-Hour Composite
GRAB – Grab
CALCTD - Calculated

(3) Measurement Frequency: See also Part I.B.2.
A - 7 days per week
B - 5 days per week
C - 3 days per week
D - 2 days per week
E - 1 day per week
F - 2 days per month
G - 1 day per month
H - 1 day per quarter
J - Annual
Q - For Effluent Toxicity Testing, see Provision IV.B.

(4) Seasonal Limits:
S = Summer (May – November)
W = Winter (December - April)
ECS = E. coli Summer (June – September)
ECW = E. coli Winter (October – May)

B. DISCHARGE MONITORING AND RECORD KEEPING REQUIREMENTS

1. Representative Sampling

   Sample collection and measurement actions shall be representative of the volume and nature of the monitored discharge and shall be in accordance with the provisions of this permit. The effluent sampling point shall be at the nearest accessible location just prior to discharge and after final treatment, unless otherwise specified in the permit.

2. Measurement Frequency

   Measurement frequency requirements found in Provision I.A. shall mean:

   a. Seven days per week shall mean daily.

   b. Five days per week shall mean any five days of discharge during a calendar weekly period of Sunday through Saturday.

   c. Three days per week shall mean any three days of discharge during a calendar week.

   d. Two days per week shall mean any two days of discharge during a calendar week.

   e. One day per week shall mean any day of discharge during a calendar week.

   f. Two days per month shall mean any two days of discharge during the month that are no less than seven days apart. However, if discharges occur only during one seven-day period in a month, then two days per month shall mean any two days of discharge during that seven day period.

   g. One day per month shall mean any day of discharge during the calendar month.

   h. Quarterly shall mean any day of discharge during each calendar quarter.

   i. The Permittee may increase the frequency of sampling, listed in Provisions I.B.2.a through I.B.2.h; however, all sampling results are to be reported to the Department.

3. Test Procedures

   For the purpose of reporting and compliance, Permittees shall use one of the following procedures:

   a. For parameters with an EPA established Minimum Level (ML), report the measured value if the analytical result is at or above the ML and report "0" for values below the ML. Test procedures for the analysis of pollutants shall conform to 40 CFR Part 136 and guidelines published pursuant to Section 304(h) of the FWPCA, 33 U.S.C. Section 1314(h). If more than one method for analysis of a substance is approved for use, a method having a minimum level lower than the permit limit shall be used. If the minimum level of all methods is higher than the permit limit, the method having the lowest minimum level shall be used and a report of less than the minimum level shall be reported as zero and will constitute compliance, however should EPA approve a method with a lower minimum level during the term of this permit the Permittee shall use the newly approved method.

   b. For pollutants parameters without an established ML, an interim ML may be utilized. The interim ML shall be calculated as 3.18 times the Method Detection Level (MDL) calculated pursuant to 40 CFR Part 136, Appendix B.

      Permittees may develop an effluent matrix-specific ML, where an effluent matrix prevents attainment of the established ML. However, a matrix specific ML shall be based upon proper laboratory method and technique. Matrix-specific MLs must be approved by the Department, and may be developed by the Permittee during permit issuance, reissuance, modification, or during compliance schedule.

      In either case the measured value should be reported if the analytical result is at or above the ML and "0" reported for values below the ML.

   c. For parameters without an EPA established ML, interim ML, or matrix-specific ML, a report of less than the detection limit shall constitute compliance if the detection limit of all analytical methods is higher than the permit limit. For the purpose of calculating a monthly average, "0" shall be used for values reported less than the detection limit.

      The Minimum Level utilized for procedures a and b above shall be reported on the Permittee's DMR. When an EPA approved test procedure for analysis of a pollutant does not exist, the Director shall approve the procedure to be used.

4. Recording of Results

   For each measurement or sample taken pursuant to the requirements of this permit, the Permittee shall record the following information:

   a. The facility name and location, point source number, date, time and exact place of sampling;

b. The name(s) of person(s) who obtained the samples or measurements;

c. The dates and times the analyses were performed;

d. The name(s) of the person(s) who performed the analyses;

e. The analytical techniques or methods used, including source of method and method number; and

f. The results of all required analyses.

5. Records Retention and Production

a. The Permittee shall retain records of all monitoring information, including all calibration and maintenance records and all original strip chart recordings for continuous monitoring instrumentation, copies of all reports required by the permit, and records of all data used to complete the above reports or the application for this permit, for a period of at least three years from the date of the sample measurement, report or application. This period may be extended by request of the Director at any time. If litigation or other enforcement action, under the AWPCA and/or the FWPCA, is ongoing which involves any of the above records, the records shall be kept until the litigation is resolved. Upon the written request of the Director or his designee, the Permittee shall provide the Director with a copy of any record required to be retained by this paragraph. Copies of these records should not be submitted unless requested.

b. All records required to be kept for a period of three years shall be kept at the permitted facility or an alternate location approved by the Department in writing and shall be available for inspection.

6. Reduction, Suspension or Termination of Monitoring and/or Reporting

a. The Director may, with respect to any point source identified in Provision I.A. of this permit, authorize the Permittee to reduce, suspend or terminate the monitoring and/or reporting required by this permit upon the submission of a written request for such reduction, suspension or termination by the Permittee, supported by sufficient data which demonstrates to the satisfaction of the Director that the discharge from such point source will continuously meet the discharge limitations specified in Provision I.A. of this permit.

b. It remains the responsibility of the Permittee to comply with the monitoring and reporting requirements of this permit until written authorization to reduce, suspend or terminate such monitoring and/or reporting is received by the Permittee from the Director.

7. Monitoring Equipment and Instrumentation

All equipment and instrumentation used to determine compliance with the requirements of this permit shall be installed, maintained, and calibrated in accordance with the manufacturer's instructions or, in the absence of manufacturer's instructions, in accordance with accepted practices. At a minimum, flow measurement devices shall be calibrated at least once every 12 months.

C. DISCHARGE REPORTING REQUIREMENTS

1. Reporting of Monitoring Requirements

a. The Permittee shall conduct the required monitoring in accordance with the following schedule:

(1) **MONITORING REQUIRED MORE FREQUENTLY THAN MONTHLY AND MONTHLY** shall be conducted during the first full month following the effective date of coverage under this permit and every month thereafter.

(2) **QUARTERLY MONITORING** shall be conducted at least once during each calendar quarter. Calendar quarters are the periods of January through March, April through June, July through September, and October through December. The Permittee shall conduct the quarterly monitoring during the first complete calendar quarter following the effective date of this permit and is then required to monitor once during each quarter thereafter. Quarterly monitoring should be reported on the last DMR due for the quarter (i.e., March, June, September and December DMRs).

(3) **SEMIANNUAL MONITORING** shall be conducted at least once during the period of January through June and at least once during the period of July through December. The Permittee shall conduct the semiannual monitoring during the first complete calendar semiannual period following the effective date of this permit and is then required to monitor once during each semiannual period thereafter. Semiannual monitoring may be done anytime during the semiannual period, unless restricted elsewhere in this permit, but it should be reported on the last DMR due for the month of the semiannual period (i.e., June and December DMRs).

(4) **ANNUAL MONITORING** shall be conducted at least once during the period of January through December. The Permittee shall conduct the annual monitoring during the first complete calendar annual period following the effective date of this permit and is then required to monitor once during each annual period thereafter.

Annual monitoring may be done anytime during the year, unless restricted elsewhere in this permit, but it should be reported on the December DMR.

b. The Permittee shall submit discharge monitoring reports (DMRs) on the forms approved by the Department and in accordance with the following schedule:

(1) **REPORTS OF MORE FREQUENTLY THAN MONTHLY AND MONTHLY TESTING** shall be submitted on a monthly basis. The first report is due on the 28th day of the month following the month the permit becomes effective. The reports shall be submitted so that they are received by the Department no later than the 28th day of the month following the reporting period.

(2) **REPORTS OF QUARTERLY TESTING** shall be submitted on a quarterly basis. The first report is due on the 28th day of the month following the month the permit becomes effective. The reports shall be submitted so that they are received by the Department no later than the 28th day of the month following the reporting period.

(3) **REPORTS OF SEMIANNUAL TESTING** shall be submitted on a semiannual basis. The reports are due on the 28th day of JANUARY and the 28th day of JULY. The reports shall be submitted so that they are received by the Department no later than the 28th day of the month following the reporting period.

(4) **REPORTS OF ANNUAL TESTING** shall be submitted on an annual basis. Unless specified elsewhere in the permit, the first report is due on the 28th day of JANUARY. The reports shall be submitted so that they are received by the Department no later than the 28th day of the month following the reporting period.

c. Except as allowed by Provision I.C.1.c.(1) or (2), the permittee shall submit all Discharge Monitoring Reports (DMRs) required by Provision I.C.1.b. by utilizing the Department's web-based Electronic Environmental (E2) Reporting System.

(1) If the permittee is unable to complete the electronic submittal of DMR data due to technical problems originating with the Department's E2 Reporting System (this could include entry/submittal issues with an entire set of DMRs or individual parameters), the permittee is not relieved of their obligation to submit DMR data to the Department by the date specified in Provision I.C.1.b., unless otherwise directed by the Department.

If the E2 Reporting System is down on the 28th day of the month in which the DMR is due or is down for an extended period of time, as determined by the Department, when a DMR is required to be submitted, the permittee may submit the data in an alternate manner and format acceptable to the Department. Preapproved alternate acceptable methods include faxing, e-mailing, mailing, or hand-delivery of data such that they are received by the required reporting date. Within five calendar days of the E2 Reporting System resuming operation, the permittee shall enter the data into the E2 Reporting System, unless an alternate timeframe is approved by the Department. An attachment should be included with the E2 DMR submittal verifying the original submittal date (date of the fax, copy of dated e-mail, or hand-delivery stamped date), if applicable.

(2) The permittee may submit a request to the Department for a temporary electronic reporting waiver for DMR submittals. The waiver request should include the permit number; permittee name; facility/site name; facility address; name, address, and contact information for the responsible official or duly authorized representative; a detailed statement regarding the basis for requesting such a waiver; and the duration for which the waiver is requested. Approved electronic reporting waivers are not transferrable.

A permittee with an approved electronic reporting waiver for DMRs may submit hard copy DMRs for the period that the approved electronic reporting waiver request is effective. The permittee shall submit the Department-approved DMR forms to the address listed in Provision I.C.1.e.

(3) If a permittee is allowed to submit a hard copy DMR, the DMR must be legible and bear an original signature. Photo and electronic copies of the signature are not acceptable and shall not satisfy the reporting requirements of this permit.

(4) If the permittee, using approved analytical methods as specified in Provision I.B.2, monitors any discharge from a point source for a limited substance identified in Provision I.A. of this permit more frequently than required by this permit, the results of such monitoring shall be included in the calculation and reporting of values on the DMR and the increased frequency shall be indicated on the DMR.

(5) In the event no discharge from a point source identified in Provision I.A. of this permit and described more fully in the permittee's application occurs during a monitoring period, the permittee shall report "No Discharge" for such period on the appropriate DMR.

d. All reports and forms required to be submitted by this permit, the AWPCA and the Department's Rules and Regulations, shall be electronically signed (or, if allowed by the Department, traditionally signed) by a "responsible official" of the permittee as defined in ADEM Administrative Code Rule 335-6-6-.09 or a "duly authorized representative" of such official as defined in ADEM Administrative Code Rule 335-6-6-.09 and shall bear the following certification:

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."

e. Discharge Monitoring Reports required by this permit, the AWPCA, and the Department's Rules that are being submitted in hard copy shall be addressed to:

Alabama Department of Environmental Management
Environmental Data Section, Permits & Services Division
Post Office Box 301463
Montgomery, Alabama 36130-1463

Certified and Registered Mail containing Discharge Monitoring Reports shall be addressed to:

Alabama Department of Environmental Management
Environmental Data Section, Permits & Services Division
1400 Coliseum Boulevard
Montgomery, Alabama 36110-2400

f. All other correspondence and reports required to be submitted by this permit, the AWPCA, and the Department's Rules shall be addressed to:

Alabama Department of Environmental Management
Municipal Section, Water Division
Post Office Box 301463
Montgomery, Alabama 36130-1463

Certified and Registered Mail shall be addressed to:

Alabama Department of Environmental Management
Municipal Section, Water Division
1400 Coliseum Boulevard
Montgomery, Alabama 36110-2400

g. If this permit is a re-issuance, then the permittee shall continue to submit DMRs in accordance with the requirements of their previous permit until such time as DMRs are due as discussed in Part I.C.1.b above.

2. Noncompliance Notification

a. The Permittee must notify the Department if, for any reason, the Permittee's discharge:

(1) Does not comply with any daily minimum or maximum discharge limitation for an effluent characteristic specified in Provision I. A. of this permit which is denoted by an "(X)"

(2) Potentially threatens human health or welfare,

(3) Threatens fish or aquatic life

(4) Causes an in-stream water quality criterion to be exceeded;

(5) Does not comply with an applicable toxic pollutant effluent standard or prohibition established under Section 307(a) of the FWPCA, 33 U.S.C. Section 1317(a);

(6) Contains a quantity of a hazardous substance that may be harmful to public health or welfare under Section 311(b)(4) of the FWPCA, 33 U.S.C. Section 1321(b)(4);

(7) Exceeds any discharge limitation for an effluent parameter listed in Part I.A as a result of an unanticipated bypass or upset; or

(8) Is an unpermitted direct or indirect discharge of a pollutant to a water of the state (Note that unpermitted discharges properly reported to the Department under any other requirement are not required to be reported under this provision)

The Permittee shall orally or electronically report any of the above occurrences, describing the circumstances and potential effects, to the Department within 24-hours after the Permittee becomes aware of the occurrence of such discharge. In addition to the oral or electronic report, the Permittee shall submit a written report to the Director or Designee, as provided in Provision I.C.2.c,no later than five days after becoming aware of the occurrence of such discharge or occurrence.

b. If for any reason, the Permittee's discharge does not comply with any limitation of this permit, then the Permittee must submit a written report to the Director or Designee, as provided in Provision I.C.2.c below. This report must be submitted with the next Discharge Monitoring Report required to be submitted by Provision I.C.1 of this permit after becoming aware of the occurrence of such noncompliance.

c. Form 421 must be submitted to the Director or Designee in accordance with Provisions I.C.2a. or b. The completed form must document the following information:

(1) A description of the discharge and cause of noncompliance;

(2) The period of noncompliance, including exact dates, times, and duration of the noncompliance. If not corrected by the due date of the written report, then the Permittee is to state the anticipated timeframe that is expected to transpire before the noncompliance is resolved; and

(3) A description of the steps taken by the Permittee and the steps planned to be taken by the Permittee to reduce or eliminate the noncompliant discharge, including all steps taken to prevent recurrence.

d. Immediate notification

The permittee shall provide notification to the Director, the public, the county health department, and any other affected entity such as public water systems, as soon as possible upon becoming aware of any notifiable sanitary sewer overflow. The Permittee shall also report notification of the noncompliance event to any other affected entity such as the public.

e. The Permittee shall keep an updated record of all known wastewater discharge points that are not authorized as permitted outfalls, including but not limited to SSOs. The Permittee shall submit annual Municipal Water Pollution Prevention Plan (MWPP) reports to the Department each year by May 31st for the prior calendar year period beginning January 1st and ending December 31st. The Annual MWPP Reports shall contain a list of all known wastewater discharge points that are not authorized as permitted outfalls and any discharges that occur prior to the headworks of the wastewater treatment plant covered by this permit. The MWPP shall also provide a list of any discharges reported in accordance with Provision I.C.2.a. The Permittee shall submit with its Annual MWPP Report the following information for each known unpermitted discharge that occurs:

(1) The cause of the discharge;

(2) Date, duration and volume of discharge (estimate if unknown);

(3) Description of the source (e.g., manhole, lift station);

(4) Location of the discharge, by street address or any other appropriate method;

(5) The ultimate destination of the flow (e.g., surface waterbody, municipal separate storm sewer to surface waterbody). Location should be shown on a USGS quad sheet or copy thereof; and

(6) Corrective actions or plans to eliminate future discharges.

f. The Permittee shall report SSO and other illicit or anomalous discharge events on Form 415 in accordance with Part I.C.2.a. This form is available on the ADEM web page or upon request from the Permittee.

D. OTHER REPORTING AND NOTIFICATION REQUIREMENTS

1. Anticipated Noncompliance

The Permittee shall give the Director written advance notice of any planned changes or other circumstances regarding a facility which may result in noncompliance with permit requirements.

2. Termination of Discharge

The Permittee shall notify the Director, in writing, when all discharges from any point source(s) identified in Provision I. A. of this permit have permanently ceased. This notification shall serve as sufficient cause for instituting procedures for modification or termination of the permit.

3. Updating Information

a. The Permittee shall inform the Director of any change in the Permittee's mailing address or telephone number or in the Permittee's designation of a facility contact or office having the authority and responsibility to prevent and abate violations of the AWPCA, the Department's Rules and the terms and conditions of this permit, in writing, no later than ten (10) days after such change. Upon request of the Director or his designee, the Permittee shall furnish the Director with an update of any information provided in the permit application.

b. If the Permittee becomes aware that it failed to submit any relevant facts in a permit application, or submitted incorrect information in a permit application or in any report to the Director, it shall promptly submit such facts or information with a written explanation for the mistake and/or omission.

4. Duty to Provide Information

   The Permittee shall furnish to the Director, within a reasonable time, any information which the Director or his designee may request to determine whether cause exists for modifying, revoking and re-issuing, suspending, or terminating this permit, in whole or in part, or to determine compliance with this permit.

E. SCHEDULE OF COMPLIANCE

1. Compliance with discharge limits

   The Permittee shall achieve compliance with the discharge limitations specified in Provision I. A. in accordance with the following schedule:

   COMPLIANCE SHALL BE ATTAINED ON THE EFFECTIVE DATE OF THIS PERMIT

2. Schedule

   No later than 14 calendar days following a date identified in the above schedule of compliance, the permittee shall submit either a report of progress or, in the case of specific actions being required by identified dates, a written notice of compliance or noncompliance. In the latter case, the notice shall include the cause of noncompliance, any remedial actions taken, and the probability of meeting the next scheduled requirement.

PART II OTHER REQUIREMENTS, RESPONSIBILITIES, AND DUTIES

A. OPERATIONAL AND MANAGEMENT REQUIREMENTS

1. Facilities Operation and Maintenance

   The Permittee shall at all times properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by the Permittee to achieve compliance with the conditions of the permit. Proper operation and maintenance includes effective performance, adequate funding, adequate operator staffing and training, and adequate laboratory and process controls, including appropriate quality assurance procedures. This provision requires the operation of backup or auxiliary facilities only when necessary to achieve compliance with the conditions of the permit.

2. Best Management Practices (BMP)

   a. Dilution water shall not be added to achieve compliance with discharge limitations except when the Director or his designee has granted prior written authorization for dilution to meet water quality requirements.

   b. The Permittee shall prepare, implement, and maintain a Spill Prevention, Control and Countermeasures (SPCC) Plan in accordance with 40 C.F.R. Section 112 if required thereby.

   c. The Permittee shall prepare, submit for approval and implement a BMP Plan for containment of any or all process liquids or solids, in a manner such that these materials do not present a significant potential for discharge, if so required by the Director or his designee. When submitted and approved, the BMP Plan shall become a part of this permit and all requirements of the BMP Plan shall become requirements of this permit.

3. Certified Operator

   The Permittee shall not operate any wastewater treatment plant unless the competency of the operator to operate such plant has been duly certified by the Director pursuant to AWPCA, and meets the requirements specified in ADEM Administrative Code, Rule 335-10-1.

B. OTHER RESPONSIBILITIES

1. Duty to Mitigate Adverse Impacts

   The Permittee shall promptly take all reasonable steps to mitigate and minimize or prevent any adverse impact on human health or the environment resulting from noncompliance with any discharge limitation specified in Provision I. A. of this permit, including such accelerated or additional monitoring of the discharge and/or the receiving waterbody as necessary to determine the nature and impact of the noncomplying discharge.

2. Right of Entry and Inspection

   The Permittee shall allow the Director, or an authorized representative, upon the presentation of proper credentials and other documents as may be required by law to:

   (1) Enter upon the Permittee's premises where a regulated facility or activity or point source is located or conducted, or where records must be kept under the conditions of the permit;

   (2) Have access to and copy, at reasonable times, any records that must be kept under the conditions of the permits;

   (3) Inspect any facilities, equipment (including monitoring and control equipment), practices, or operations regulated or required under the permit; and

   (4) Sample or monitor, for the purposes of assuring permit compliance or as otherwise authorized by the AWPCA, any substances or parameters at any location.

C. BYPASS AND UPSET

1. Bypass

   a. Any bypass is prohibited except as provided in b. and c. below:

   b. A bypass is not prohibited if:

      (1) It does not cause any discharge limitation specified in Provision I. A. of this permit to be exceeded;

      (2) It enters the same receiving stream as the permitted outfall; and

      (3) It is necessary for essential maintenance of a treatment or control facility or system to assure efficient operation of such facility or system.

   c. A bypass is not prohibited and need not meet the discharge limitations specified in Provision I. A. of this permit if:

      (1) It is unavoidable to prevent loss of life, personal injury, or severe property damage;

(2) There are no feasible alternatives to the bypass, such as the use of auxiliary treatment facilities, retention of untreated wastes, or maintenance during normal periods of equipment downtime (this condition is not satisfied if adequate back-up equipment should have been installed in the exercise of reasonable engineering judgment to prevent a bypass which occurred during normal periods of equipment downtime or preventive maintenance); and

(3) The Permittee submits a written request for authorization to bypass to the Director at least ten (10) days prior to the anticipated bypass (if possible), the Permittee is granted such authorization, and the Permittee complies with any conditions imposed by the Director to minimize any adverse impact on human health or the environment resulting from the bypass.

d. The Permittee has the burden of establishing that each of the conditions of Provision II. C. 1. b. or c. have been met to qualify for an exception to the general prohibition against bypassing contained in a. and an exemption, where applicable, from the discharge limitations specified in Provision I. A. of this permit.

2. Upset

a. A discharge which results from an upset need not meet the discharge limitations specified in Provision I. A. of this permit if:

(1) No later than 24-hours after becoming aware of the occurrence of the upset, the Permittee orally reports the occurrence and circumstances of the upset to the Director or his designee; and

(2) No later than five (5) days after becoming aware of the occurrence of the upset, the Permittee furnishes the Director with evidence, including properly signed, contemporaneous operating logs, or other relevant evidence, demonstrating that:

(i) An upset occurred;

(ii) The Permittee can identify the specific cause(s) of the upset;

(iii) The Permittee's facility was being properly operated at the time of the upset; and

(iv) The Permittee promptly took all reasonable steps to minimize any adverse impact on human health or the environment resulting from the upset.

b. The Permittee has the burden of establishing that each of the conditions of Provision II C. 2. a. of this permit have been met to qualify for an exemption from the discharge limitations specified in Provision I. A. of this permit.

D. DUTY TO COMPLY WITH PERMIT, RULES, AND STATUTES

1. Duty to Comply

a. The Permittee must comply with all conditions of this permit. Any permit noncompliance constitutes a violation of the AWPCA and the FWPCA and is grounds for enforcement action, for permit termination, revocation and reissuance, suspension, modification, or denial of a permit renewal application.

b. The necessity to halt or reduce production or other activities in order to maintain compliance with the conditions of the permit shall not be a defense for a Permittee in an enforcement action.

c. The discharge of a pollutant from a source not specifically identified in the permit application for this permit and not specifically included in the description of an outfall in this permit is not authorized and shall constitute noncompliance with this permit.

d. The Permittee shall take all reasonable steps, including cessation of production or other activities, to minimize or prevent any violation of this permit or to minimize or prevent any adverse impact of any permit violation.

e. Nothing in this permit shall be construed to preclude or negate the Permittee's responsibility to apply for, obtain, or comply with other Federal, State, or Local Government permits, certifications,or licenses or to preclude from obtaining other federal, state, or local approvals, including those applicable to other ADEM programs and regulations.

2. Removed Substances

Solids, sludges, filter backwash, or any other pollutant or other waste removed in the course of treatment or control of wastewaters shall be disposed of in a manner that complies with all applicable Department Rules.

3. Loss or Failure of Treatment Facilities

Upon the loss or failure of any treatment facilities, including but not limited to the loss or failure of the primary source of power of the treatment facility, the Permittee shall, where necessary to maintain compliance with the discharge limitations specified in Provision I. A. of this permit, or any other terms or conditions of this permit, cease, reduce, or otherwise control production and/or all discharges until treatment is restored. If control of discharge during loss or failure of the

primary source of power is to be accomplished by means of alternate power sources, standby generators, or retention of inadequately treated effluent, the Permittee must furnish to the Director within six months a certification that such control mechanisms have been installed.

4. Compliance With Statutes and Rules

   a. This permit has been issued under ADEM Administrative Code, Chapter 335-6-6. All provisions of this chapter, that are applicable to this permit, are hereby made a part of this permit. A copy of this chapter may be obtained for a small charge from the Office of General Counsel, Alabama Department of Environmental Management, 1400 Coliseum Boulevard Montgomery, Alabama 36110-2059.

   b. This permit does not authorize the noncompliance with or violation of any Laws of the State of Alabama or the United States of America or any regulations or rules implementing such laws. FWPCA, 33 U.S.C. Section 1319, and Code of Alabama 1975, Section 22-22-14.

E. PERMIT TRANSFER, MODIFICATION, SUSPENSION, REVOCATION, AND REISSUANCE

1. Duty to Reapply or Notify of Intent to Cease Discharge

   a. If the Permittee intends to continue to discharge beyond the expiration date of this permit, the Permittee shall file a complete permit application for reissuance of this permit at least 180 days prior to its expiration. If the Permittee does not intend to continue discharge beyond the expiration of this permit, the Permittee shall submit written notification of this intent which shall be signed by an individual meeting the signatory requirements for a permit application as set forth in ADEM Administrative Code Rule 335-6-6-.09.

   b. Failure of the Permittee to apply for reissuance at least 180 days prior to permit expiration will void the automatic continuation of the expiring permit provided by ADEM Administrative Code Rule 335-6-6-.06 and should the permit not be reissued for any reason any discharge after expiration of this permit will be an unpermitted discharge.

2. Change in Discharge

   Prior to any facility expansion, process modification or any significant change in the method of operation of the Permittee's treatment works, the Permittee shall provide the Director with information concerning the planned expansion, modification or change. The Permittee shall apply for a permit modification at least 180 days prior to any facility expansion, process modification, any significant change in the method of operation of the Permittee's treatment works or other actions that could result in the discharge of additional pollutants or increase the quantity of a discharged pollutant or could result in an additional discharge point. This condition applies to pollutants that are or that are not subject to discharge limitations in this permit. No new or increased discharge may begin until the Director has authorized it by issuance of a permit modification or a reissued permit.

3. Transfer of Permit

   This permit may not be transferred or the name of the Permittee changed without notice to the Director and subsequent modification or revocation and reissuance of the permit to identify the new Permittee and to incorporate any other changes as may be required under the FWPCA or AWPCA. In the case of a change in name, ownership or control of the Permittee's premises only, a request for permit modification in a format acceptable to the Director is required at least 30 days prior to the change. In the case of a change in name, ownership or control of the Permittee's premises accompanied by a change or proposed change in effluent characteristics, a complete permit application is required to be submitted to the Director at least 180 days prior to the change. Whenever the Director is notified of a change in name, ownership or control, he may decide not to modify the existing permit and require the submission of a new permit application.

4. Permit Modification and Revocation

   a. This permit may be modified or revoked and reissued, in whole or in part, during its term for cause, including but not limited to, the following:

      (1) If cause for termination under Provision II. E. 5. of this permit exists, the Director may choose to revoke and reissue this permit instead of terminating the permit;

      (2) If a request to transfer this permit has been received, the Director may decide to revoke and reissue or to modify the permit; or

      (3) If modification or revocation and reissuance is requested by the Permittee and cause exists, the Director may grant the request.

   b. This permit may be modified during its term for cause, including but not limited to, the following:

      (1) If cause for termination under Provision II. E. 5. of this permit exists, the Director may choose to modify this permit instead of terminating this permit;

(2) There are material and substantial alterations or additions to the facility or activity generating wastewater which occurred after permit issuance which justify the application of permit conditions that are different or absent in the existing permit;

(3) The Director has received new information that was not available at the time of permit issuance and that would have justified the application of different permit conditions at the time of issuance;

(4) A new or revised requirement(s) of any applicable standard or limitation is promulgated under Sections 301(b)(2)(C), (D), (E), and (F), and 307(a)(2) of the FWPCA;

(5) Errors in calculation of discharge limitations or typographical or clerical errors were made;

(6) To the extent allowed by ADEM Administrative Code, Rule 335-6-6-.17, when the standards or regulations on which the permit was based have been changed by promulgation of amended standards or regulations or by judicial decision after the permit was issued;

(7) To the extent allowed by ADEM Administrative Code, Rule 335-6-6-.17, permits may be modified to change compliance schedules;

(8) To agree with a granted variance under 301(c), 301(g), 301(h), 301(k), or 316(a) of the FWPCA or for fundamentally different factors;

(9) To incorporate an applicable 307(a) FWPCA toxic effluent standard or prohibition;

(10) When required by the reopener conditions in this permit;

(11) When required under 40 CFR 403.8(e) (compliance schedule for development of pretreatment program);

(12) Upon failure of the state to notify, as required by Section 402(b)(3) of the FWPCA, another state whose waters may be affected by a discharge permitted by this permit;

(13) When required to correct technical mistakes, such as errors in calculation, or mistaken interpretations of law made in determining permit conditions; or

(14) When requested by the Permittee and the Director determines that the modification has cause and will not result in a violation of federal or state law, regulations or rules.

5. Termination

This permit may be terminated during its term for cause, including but not limited to, the following:

a. Violation of any term or condition of this permit;

b. The Permittee's misrepresentation or failure to disclose fully all relevant facts in the permit application or during the permit issuance process or the Permittee's misrepresentation of any relevant facts at any time;

c. Materially false or inaccurate statements or information in the permit application or the permit;

d. A change in any condition that requires either a temporary or permanent reduction or elimination of the permitted discharge;

e. The Permittee's discharge threatens human life or welfare or the maintenance of water quality standards;

f. Permanent closure of the facility generating the wastewater permitted to be discharged by this permit or permanent cessation of wastewater discharge;

g. New or revised requirements of any applicable standard or limitation that is promulgated under Sections 301(b)(2)(C), (D), (E), and (F), and 307(a)(2) of the FWPCA that the Director determines cannot be complied with by the Permittee; or

h. Any other cause allowed by the ADEM Administrative Code, Chapter 335-6-6.

6. Suspension

This permit may be suspended during its term for noncompliance until the Permittee has taken action(s) necessary to achieve compliance.

7. Stay

The filing of a request by the Permittee for modification, suspension or revocation of this permit, in whole or in part, does not stay any permit term or condition.

F. COMPLIANCE WITH TOXIC POLLUTANT STANDARD OR PROHIBITION

If any applicable effluent standard or prohibition (including any schedule of compliance specified in such effluent standard or prohibition) is established under Section 307(a) of the FWPCA, 33 U.S.C. Section 1317(a), for a toxic pollutant discharged by the Permittee, and such standard or prohibition is more stringent than any discharge limitation on the pollutant specified in Provision I. A. of this permit or controls a pollutant not limited in Provision I. A. of this permit, this permit shall be modified to conform to the toxic pollutant effluent standard or prohibition, and the Permittee shall be notified of such modification. If this permit has not been modified to conform to the toxic pollutant effluent standard or prohibition before the effective date of such standard or prohibition, the Permittee shall attain compliance with the requirements of the standard or prohibition within the time period required by the standard or prohibition and shall continue to comply with the standard or prohibition until this permit is modified or reissued.

G. NOTICE TO DIRECTOR OF INDUSTRIAL USERS

1. The Permittee shall not allow the introduction of wastewater, other than domestic wastewater, from a new direct discharger prior to approval and permitting, if applicable, of the discharge by the Department.
2. The Permittee shall not allow an existing indirect discharger to increase the quantity or change the character of its wastewater, other than domestic wastewater, prior to approval and permitting, if applicable, of the increased discharge by the Department.
3. The Permittee shall report to the Department any adverse impact caused or believed to be caused by an indirect discharger on the treatment process, quality of discharged water, or quality of sludge. Such report shall be submitted within seven days of the Permittee becoming aware of the adverse impacts.

H. PROHIBITIONS

The Permittee shall not allow, and shall take effective enforcement action to prevent and terminate, the introduction of any of the following into its treatment works by industrial users:

1. Pollutants which create a fire or explosion hazard in the treatment works;
2. Pollutants which will cause corrosive structural damage to the treatment works, or dischargers with a pH lower than 5.0 s.u., unless the works are specifically designed to accommodate such discharges;
3. Solid or viscous pollutants in amounts which will cause obstruction of flow in sewers, or other interference with the treatment works;
4. Pollutants, including oxygen demanding pollutants, released in a discharge of such volume or strength as to cause interference in the treatment works;
5. Heat in amounts which will inhibit biological activity in the treatment plant resulting in interference or in such quantities that the temperature of the treatment plant influent exceeds 40°C (104° F) unless the treatment plant is designed to accommodate such heat; and
6. Pollutants in amounts which exceed any applicable pretreatment standard under Section 307 of FWPCA or any approved revisions thereof.

PART III ADDITIONAL REQUIREMENTS, CONDITIONS, AND LIMITATIONS

A. CIVIL AND CRIMINAL LIABILITY

1. Tampering

   Any person who falsifies, tampers with, or knowingly renders inaccurate any monitoring device or method required to be maintained or performed under the permit shall, upon conviction, be subject to penalties as provided by the AWPCA.

2. False Statements

   Any person who knowingly makes any false statement, representation, or certification in any record or other document submitted or required to be maintained under this permit, including monitoring reports or reports of compliance or noncompliance shall, upon conviction, be subject to penalties as provided by the AWPCA.

3. Permit Enforcement

   a. Any NPDES permit issued or reissued by the Department is a permit for the purpose of the AWPCA and the FWPCA, and as such, any terms, conditions, or limitations of the permit are enforceable under state and federal law.

   b. Any person required to have a NPDES permit pursuant to ADEM Administrative Code Chapter 335-6-6 and who discharges pollutants without said permit, who violates the conditions of said permit, who discharges pollutants in a manner not authorized by the permit, or who violates applicable orders of the Department or any applicable rule or standard of the Department, is subject to any one or combination of the following enforcement actions under applicable state statutes:

      (1) An administrative order requiring abatement, compliance, mitigation, cessation, clean-up, and/or penalties;

      (2) An action for damages;

      (3) An action for injunctive relief; or

      (4) An action for penalties.

   c. If the Permittee is not in compliance with the conditions of an expiring or expired permit the Director may choose to do any or all of the following provided the Permittee has made a timely and complete application for reissuance of the permit:

      (1) Initiate enforcement action based upon the permit which has been continued;

      (2) Issue a notice of intent to deny the permit reissuance. If the permit is denied, the owner or operator would then be required to cease the activities authorized by the continued permit or be subject to enforcement action for operating without a permit;

      (3) Reissue the new permit with appropriate conditions; or

      (4) Take other actions authorized by these rules and AWPCA.

4. Relief from Liability

   Except as provided in Provision II. C. 1. (Bypass) and Provision II. C. 2. (Upset), nothing in this permit shall be construed to relieve the Permittee of civil or criminal liability under the AWPCA or FWPCA for noncompliance with any term or condition of this permit.

B. OIL AND HAZARDOUS SUBSTANCE LIABILITY

Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the Permittee from any responsibilities, liabilities or penalties to which the Permittee is or may be subject under Section 311 of the FWPCA, 33 U.S.C. Section 1321.

C. PROPERTY AND OTHER RIGHTS

This permit does not convey any property rights in either real or personal property, or any exclusive privileges, nor does it authorize any injury to persons or property or invasion of other private rights, or any infringement of federal, state, or local laws or regulations, nor does it authorize or approve the construction of any physical structures or facilities or the undertaking of any work in any waters of the state or of the United States.

D. AVAILABILITY OF REPORTS

Except for data determined to be confidential under Code of Alabama 1975, Section 22-22-9(c), all reports prepared in accordance with the terms of this permit shall be available for public inspection at the offices of the Department. Effluent data shall not be considered confidential.

E. EXPIRATION OF PERMITS FOR NEW OR INCREASED DISCHARGES

1. If this permit was issued for a new discharger or new source, this permit shall expire eighteen months after the issuance date if construction of the facility has not begun during the eighteen-month period.

2. If this permit was issued or modified to allow the discharge of increased quantities of pollutants to accommodate the modification of an existing facility and if construction of this modification has not begun during the eighteen month period after issuance of this permit or permit modification, this permit shall be modified to reduce the quantities of pollutants allowed to be discharged to those levels that would have been allowed if the modification of the facility had not been planned.

3. Construction has begun when the owner or operator has:

   a. Begun, or caused to begin as part of a continuous on-site construction program:

      (1) Any placement, assembly, or installation of facilities or equipment; or

      (2) Significant site preparation work including clearing, excavation, or removal of existing buildings, structures, or facilities which are necessary for the placement, assembly, or installation of new source facilities or equipment; or

   b. Entered into a binding contractual obligation for the purpose of placement, assembly, or installation of facilities or equipment which are intended to be used in its operation within a reasonable time. Options to purchase or contracts which can be terminated or modified without substantial loss, and contracts for feasibility, engineering, and design studies do not constitute a contractual obligation under this paragraph.

4. Final plans and specifications for a waste treatment facility at a new source or new discharger, or a modification to an existing waste treatment facility must be submitted to and examined by the Department prior to initiating construction of such treatment facility by the Permittee.

5. Upon completion of construction of waste treatment facilities and prior to operation of such facilities, the Permittee shall submit to the Department a certification from a registered professional engineer, licensed to practice in the State of Alabama, that the treatment facilities have been built according to plans and specifications submitted to and examined by the Department.

F. COMPLIANCE WITH WATER QUALITY STANDARDS

1. On the basis of the Permittee's application, plans, or other available information, the Department has determined that compliance with the terms and conditions of this permit should assure compliance with the applicable water quality standards.

2. Compliance with permit terms and conditions notwithstanding, if the Permittee's discharge(s) from point sources identified in Provision I. A. of this permit cause or contribute to a condition in contravention of state water quality standards, the Department may require abatement action to be taken by the Permittee in emergency situations or modify the permit pursuant to the Department's Rules, or both.

3. If the Department determines, on the basis of a notice provided pursuant to this permit or any investigation, inspection or sampling, that a modification of this permit is necessary to assure maintenance of water quality standards or compliance with other provisions of the AWPCA or FWPCA, the Department may require such modification, and, in cases of emergency, the Director may prohibit the discharge until the permit has been modified.

G. GROUNDWATER

Unless specifically authorized under this permit, this permit does not authorize the discharge of pollutants to groundwater. Should a threat of groundwater contamination occur, the Director may require groundwater monitoring to properly assess the degree of the problem, and the Director may require that the Permittee undertake measures to abate any such discharge and/or contamination.

H. DEFINITIONS

1. Average monthly discharge limitation – means the highest allowable average of "daily discharges" over a calendar month, calculated as the sum of all "daily discharges" measured during a calendar month divided by the number of "daily discharges" measured during that month (zero discharge days shall not be included in the number of "daily discharges" measured and a less than detectable test result shall be treated as a concentration of zero if the most sensitive EPA approved method was used).

2. Average weekly discharge limitation - means the highest allowable average of "daily discharges" over a calendar week, calculated as the sum of all "daily discharges" measured during a calendar week divided by the number of "daily discharges" measured during that week (zero discharge days shall not be included in the number of "daily discharges" measured and a less than detectable test result shall be treated as a concentration of zero if the most sensitive EPA approved method was used).

3. Arithmetic Mean – means the summation of the individual values of any set of values divided by the number of individual values.
4. AWPCA – means the Alabama Water Pollution Control Act.
5. BOD – means the five-day measure of the pollutant parameter biochemical oxygen demand.
6. Bypass – means the intentional diversion of waste streams from any portion of a treatment facility.
7. CBOD – means the five-day measure of the pollutant parameter carbonaceous biochemical oxygen demand.
8. Daily discharge – means the discharge of a pollutant measured during any consecutive 24-hour period in accordance with the sample type and analytical methodology specified by the discharge permit.
9. Daily maximum – means the highest value of any individual sample result obtained during a day.
10. Daily minimum – means the lowest value of any individual sample result obtained during a day.
11. Day – means any consecutive 24-hour period.
12. Department – means the Alabama Department of Environmental Management.
13. Director – means the Director of the Department.
14. Discharge – means "[t]he addition, introduction, leaking, spilling or emitting of any sewage, industrial waste, pollutant or other waste into waters of the state". Code of Alabama 1975, Section 22-22-1(b)(9).
15. Discharge Monitoring Report (DMR) – means the form approved by the Director to accomplish reporting requirements of an NPDES permit.
16. DO – means dissolved oxygen.
17. 8HC – means 8-hour composite sample, including any of the following:
    a. The mixing of at least 8 equal volume samples collected at constant time intervals of not more than 1 hour over a period of not less than 8 hours between the hours of 6:00 a.m. and 6:00 p.m. If the sampling period exceeds 8 hours, sampling may be conducted beyond the 6:00 a.m. to 6:00 p.m. period.
    b. A sample continuously collected at a constant rate over period of not less than 8 hours between the hours of 6:00 a.m. and 6:00 p.m. If the sampling period exceeds 8 hours, sampling may be conducted beyond the 6:00 a.m. to 6:00 p.m. period.
18. EPA – means the United States Environmental Protection Agency.
19. FC – means the pollutant parameter fecal coliform.
20. Flow – means the total volume of discharge in a 24-hour period.
21. FWPCA – means the Federal Water Pollution Control Act.
22. Geometric Mean – means the Nth root of the product of the individual values of any set of values where N is equal to the number of individual values. The geometric mean is equivalent to the antilog of the arithmetic mean of the logarithms of the individual values. For purposes of calculating the geometric mean, values of zero (0) shall be considered one (1).
23. Grab Sample – means a single influent or effluent portion which is not a composite sample. The sample(s) shall be collected at the period(s) most representative of the discharge.
24. Indirect Discharger – means a nondomestic discharger who discharges pollutants to a publicly owned treatment works or a privately owned treatment facility operated by another person.
25. Industrial User – means those industries identified in the Standard Industrial Classification manual, Bureau of the Budget 1967, as amended and supplemented, under the category "Division D – Manufacturing" and such other classes of significant waste producers as, by regulation, the Director deems appropriate.
26. MGD – means million gallons per day.
27. Monthly Average – means the arithmetic mean of all the composite or grab samples taken for the daily discharges collected in one month period. The monthly average for flow is the arithmetic mean of all flow measurements taken in a one month period.
28. New Discharger – means a person, owning or operating any building, structure, facility or installation:
    a. From which there is or may be a discharge of pollutants;
    b. From which the discharge of pollutants did not commence prior to August 13, 1979, and which is not a new source; and

c. Which has never received a final effective NPDES permit for dischargers at that site.

29. NH3-N – means the pollutant parameter ammonia, measured as nitrogen.

30. Notifiable sanitary sewer overflow – means an overflow, spill, release or diversion of wastewater from a sanitary sewer system that:

    a. Reaches a surface water of the State; or

    b. May imminently and substantially endanger human health based on potential for public exposure including but not limited to close proximity to public or private water supply wells or in areas where human contact would be likely to occur.

31. Permit application – means forms and additional information that is required by ADEM Administrative Code Rule 335-6-6-.08 and applicable permit fees.

32. Point source – means "any discernible, confined and discrete conveyance, including but not limited to any pipe, channel, ditch, tunnel, conduit, well, discrete fissure, container, rolling stock, concentrated animal feeding operation, or vessel or other floating craft, . . . from which pollutants are or may be discharged." Section 502(14) of the FWPCA, 33 U.S.C. Section 1362(14).

33. Pollutant – includes for purposes of this permit, but is not limited to, those pollutants specified in Code of Alabama 1975, Section 22-22-1(b)(3) and those effluent characteristics specified in Provision I. A. of this permit.

34. Privately Owned Treatment Works – means any devices or system which is used to treat wastes from any facility whose operator is not the operator of the treatment works, and which is not a "POTW".

35. Publicly Owned Treatment Works – means a wastewater collection and treatment facility owned by the State, municipality, regional entity composed of two or more municipalities, or another entity created by the State or local authority for the purpose of collecting and treating municipal wastewater.

36. Receiving Stream – means the "waters" receiving a "discharge" from a "point source".

37. Severe property damage – means substantial physical damage to property, damage to the treatment facilities which causes them to become inoperable, or substantial and permanent loss of natural resources which can reasonably be expected to occur in the absence of a bypass. Severe property damage does not mean economic loss caused by delays in production.

38. Significant Source – means a source which discharges 0.025 MGD or more to a POTW or greater than five percent of the treatment work's capacity, or a source which is a primary industry as defined by the U.S. EPA or which discharges a priority or toxic pollutant.

39. TKN – means the pollutant parameter Total Kjeldahl Nitrogen.

40. TON – means the pollutant parameter Total Organic Nitrogen.

41. TRC – means Total Residual Chlorine.

42. TSS – means the pollutant parameter Total Suspended Solids.

43. 24HC – means 24-hour composite sample, including any of the following:

    a. The mixing of at least 8 equal volume samples collected at constant time intervals of not more than 2 hours over a period of 24 hours;

    b. A sample collected over a consecutive 24-hour period using an automatic sampler composite to one sample. As a minimum, samples shall be collected hourly and each shall be no more than one twenty-fourth (1/24) of the total sample volume collected; or

    c. A sample collected over a consecutive 24-hour period using an automatic composite sampler composited proportional to flow.

44. Upset – means an exceptional incident in which there is an unintentional and temporary noncompliance with technology-based permit discharge limitations because of factors beyond the reasonable control of the Permittee. An upset does not include noncompliance to the extent caused by operational error, improperly designed treatment facilities, inadequate treatment facilities, lack of preventive maintenance, or careless or improper operation.

45. Waters – means "[a]ll waters of any river, stream, watercourse, pond, lake, coastal, ground, or surface water, wholly or partially within the state, natural or artificial. This does not include waters which are entirely confined and retained completely upon the property of a single individual, partnership, or corporation unless such waters are used in interstate commerce." Code of Alabama 1975, Section 22-22-1(b)(2). Waters "include all navigable waters" as defined in Section 502(7) of the FWPCA, 22 U.S.C. Section 1362(7), which are within the State of Alabama.

46. Week – means the period beginning at twelve midnight Saturday and ending at twelve midnight the following Saturday.

47. Weekly (7-day and calendar week) Average – is the arithmetic mean of all samples collected during a consecutive 7-day period or calendar week, whichever is applicable. The calendar week is defined as beginning on Sunday and ending on Saturday. Weekly averages shall be calculated for all calendar weeks with Saturdays in the month. If a calendar week overlaps two months (i.e., the Sunday is in one month and the Saturday in the following month), the weekly average calculated for the calendar week shall be included in the data for the month that contains the Saturday.

I. SEVERABILITY

The provisions of this permit are severable, and if any provision of this permit or the application of any provision of this permit to any circumstance is held invalid, the application of such provision to other circumstances, and the remainder of this permit, shall not be affected thereby.

PART IV SPECIFIC REQUIREMENTS, CONDITIONS, AND LIMITATIONS

A. SLUDGE MANAGEMENT PRACTICES

1. Applicability

   a. Provisions of Provision IV.A. apply to a sewage sludge generated or treated in treatment works that is applied to agricultural and non-agricultural land, or that is otherwise distributed, marketed, incinerated, or disposed in landfills or surface disposal sites.

   b. Provisions of Provision IV.A. do not apply to:

      (1) Sewage sludge generated or treated in a privately owned treatment works operated in conjunction with industrial manufacturing and processing facilities and which receive no domestic wastewater.

      (2) Sewage sludge that is stored in surface impoundments located at the treatment works prior to ultimate disposal.

2. Submitting Information

   a. If applicable, the Permittee must submit annually with its Municipal Water Pollution Prevention (MWPP) report the following:

      (1) Type of sludge stabilization/digestion method;

      (2) Daily or annual sludge production (dry weight basis);

      (3) Ultimate sludge disposal practice(s).

   b. The Permittee shall provide sludge inventory data to the Director as requested. These data may include, but are not limited to, sludge quantity and quality reported in Provision IV.A.2.a as well as other specific analyses required to comply with State and Federal laws regarding solid and hazardous waste disposal.

   c. The Permittee shall give prior notice to the Director of at least 30 days of any change planned in the Permittee's sludge disposal practices.

3. Reopener or Modification

   a. Upon review of information provided by the Permittee as required by Provision IV.A.2. or, based on the results of an on-site inspection, the permit shall be subject to modification to incorporate appropriate requirements.

   b. If an applicable "acceptable management practice" or if a numerical limitation for a pollutant in sewage sludge promulgated under Section 405 of FWPCA is more stringent than the sludge pollutant limit or acceptable management practice in this permit. This permit shall be modified or revoked or reissued to conform to requirements promulgated under Section 405. The Permittee shall comply with the limitations no later than the compliance deadline specified in applicable regulations as required by Section 405 of FWPCA.

B. EFFLUENT TOXICITY LIMITATIONS AND BIOMONITORING REQUIREMENTS FOR CHRONIC TOXICITY

1. Chronic Toxicity Test

   a. The permittee shall perform short-term chronic toxicity tests on the wastewater at Outfall 001T.

   b. The samples shall be diluted using appropriate control water to the Instream Waste Concentration (IWC) which is **54 percent** effluent. The IWC is the actual concentration of effluent, after mixing, in the receiving stream during a 7-day, 10-year low flow period.

   c. Any test result that shows a statistically significant reduction in survival, growth, or reproduction between the control and test samples at the 95% confidence level indicates chronic toxicity and shall constitute noncompliance with this permit.

2. General Test Requirements

   a. A minimum of three (3) 24-hour composite samples shall be obtained for use in the above biomonitoring tests. Samples shall be collected every other day so that the laboratory receives water samples on the first, third, and fifth day of the seven-day test period. The holding time for each composite sample shall not exceed 36 hours. The control water shall be a water prepared in the laboratory in accordance with the EPA procedure described in EPA 821-R-02-013 (most current edition) or another control water selected by the Permittee and approved by the Department.

   b. Test results shall be deemed unacceptable and the Permittee shall rerun the tests as soon as practical within the monitoring period for the following:

      (1) For testing with P. promelas:, effluent toxicity tests with control survival of less than 80% or if dry weight per surviving control organism is less than 0.25 mg;

(2) For testing with C. dubia:, if the number of young per surviving control organism is less than 15 or if less than 60% of surviving control females produce three broods; or

(3) If the other requirements of the EPA Test Procedure are not met.

c. In the event of an invalid test, upon subsequent completion of a valid test, the results of all tests, valid and invalid, are to be reported to the Department along with an explanation of the tests performed and the test results.

d. Toxicity tests shall be conducted for the duration of this permit in the month of **November**. Should results from the Annual Toxicity test indicate that Outfall 001-1 exhibits chronic toxicity, then the Permittee must conduct the follow-up testing described in Part IV.B.4.a. In addition, the Permittee may then also be required to conduct toxicity testing in the months of FEBRUARY, MAY, AUGUST, and NOVEMBER.

3. Reporting Requirements

a. The Permittee shall notify the Department in writing within 48 hours after toxicity has been demonstrated by the scheduled test(s).

b. Biomonitoring test results obtained during each monitoring period shall be summarized and reported using the appropriate Discharge Monitoring Report (DMR) form approved by the Department. In accordance with Section 2 of this part, an effluent toxicity report containing the information in Sections 2 and 6 shall be included with the DMR. Two copies of the test results must be submitted to the Department no later than 28 days after the month that tests were performed.

4. Additional Testing Requirements

a. If chronic toxicity is indicated (i.e., noncompliance with permit limit), then the Permittee must perform two additional valid chronic toxicity tests in accordance with these procedures to determine the extent and duration of the toxic condition. The toxicity tests shall run consecutively beginning on the first calendar week following the date that the Permittee became aware of the permit noncompliance. The results of these follow-up tests shall be submitted to the Department no later than 28 days following the month the tests were performed.

b. After evaluation of the results of the follow-up tests, the Department will determine if additional action is appropriate and may require additional testing and/or toxicity reduction measures. The permittee may be required to perform a Toxicity Identification Evaluation (TIE) and/or a Toxicity Reduction Evaluation (TRE). The TIE/TRE shall be performed in accordance with the most recent protocols and guidance outlined by EPA (e.g., EPA/600/2-88/062, EPA/600/R-92/080, EPA/600/R-91-003, EPA/600/R-92/081, EPA/833/B-99/022, and/or EPA/600/6-91/005F)

5. Test Methods

The tests shall be performed in accordance with the latest edition of the "EPA Short-Term Methods for Estimating the Chronic Toxicity of Effluents and Receiving Waters to Freshwater Organisms." The Larval Survival and Growth Test, Method 1000.0, shall be used for the fathead minnow (Pimephales promelas) test and the Survival and Reproduction Test, Method 1002.0, shall be used for the cladoceran (Ceriodaphnia dubia) test.

6. Effluent Toxicity Testing Reports

The following information shall be submitted with each DMR unless otherwise directed by the Department. The Department may at any times suspend or reinstate this requirement or may decrease or increase the frequency of submittals.

a. Introduction

(1) Facility name, location and county
(2) Permit number
(3) Toxicity testing requirements of permit
(4) Name of receiving water body
(5) Contract laboratory information (if tests are performed under contract)
  (a) Name of firm
  (b) Telephone number
  (c) Address
(6) Objective of test

b. Plant Operations

(1) Discharge Operating schedule (if other than continuous)
(2) Volume of discharge during sample collection to include Mean daily discharge on sample collection dates (MGD, CFS, GPM)
(3) Design flow of treatment facility at time of sampling

c. Source of Effluent and Dilution Water

(1) Effluent samples

(a) Sampling point
(b) Sample collection dates and times (to include composite sample start and finish times)
(c) Sample collection method
(d) Physical and chemical data of undiluted effluent samples (water temperature, pH, alkalinity, hardness, specific conductance, total residual chlorine (if applicable), etc.)
(e) Lapsed time from sample collection to delivery
(f) Lapsed time from sample collection to test initiation
(g) Sample temperature when received at the laboratory

(2) Dilution Water

(a) Source
(b) Collection/preparation date(s) and time(s)
(c) Pretreatment (if applicable)
(d) Physical and chemical characteristics (water temperature, pH, alkalinity, hardness, specific conductance, etc.)

d. Test Conditions

(1) Toxicity test method utilized
(2) End point(s) of test
(3) Deviations from referenced method, if any, and reason(s)
(4) Date and time test started
(5) Date and time test terminated
(6) Type and volume of test chambers
(7) Volume of solution per chamber
(8) Number of organisms per test chamber
(9) Number of replicate test chambers per treatment
(10) Test temperature, pH, and dissolved oxygen as recommended by the method (to include ranges)
(11) Specify if aeration was needed
(12) Feeding frequency, amount, and type of food
(13) Specify if (and how) pH control measures were implemented
(14) Light intensity (mean)

e. Test Organisms

(1) Scientific name
(2) Life stage and age
(3) Source
(4) Disease(s) treatment (if applicable)

f. Quality Assurance

(1) Reference toxicant utilized and source
(2) Date and time of most recent chronic reference toxicant test(s), raw data, and current control chart(s). (The most recent chronic reference toxicant test shall be conducted within 30 days of the routine.)
(3) Dilution water utilized in reference toxicant test
(4) Results of reference toxicant test(s) (NOEC, IC25, etc.); report concentration-response relationship and evaluate test sensitivity
(5) Physical and chemical methods utilized

g. Results

(1) Provide raw toxicity data in tabular form, including daily records of affected organisms in each concentration (including controls) and replicate
(2) Provide table of endpoints: NOECs, IC25s, PASS/FAIL, etc. (as required in the applicable NPDES permit)
(3) Indicate statistical methods used to calculate endpoints
(4) Provide all physical and chemical data required by method
(5) Results of test(s) (NOEC, IC25, PASS/FAIL, etc.), report concentration-response relationship (definitive test only), report percent minimum significant difference (PMSD) calculated for sublethal endpoints determined by hypothesis testing.

h. Conclusions and Recommendations

(1) Relationship between test endpoints and permit limits

(2) Actions to be taken

1/ Adapted from "Short-Term Methods for Estimating the Chronic Toxicity of Effluents and Receiving Waters to Freshwater Organisms", Fourth Edition, October 2002 (EPA 821-R-02-013), Section 10, Report Preparation.

C. TOTAL RESIDUAL CHLORINE (TRC) REQUIREMENTS

1. If chlorine is not utilized for disinfection purposes, TRC monitoring under Part I of this Permit is not required. If TRC monitoring is not required, "NODI = 9" (conditional monitoring) should be reported on the DMR forms.

2. Testing for TRC shall be conducted according to either the amperometric titration method or the DPD colorimetric method as specified in Section 408(C) or (E), Standards Methods for the Examination of Water and Wastewater, 18th edition. If chlorine is not detected prior to actual discharge to the receiving stream using one of these methods (i.e., the analytical result is less than the detection level), the Permittee shall report on the DMR form "NODI = B" or "0". The Permittee shall then be considered to be in compliance with the daily maximum concentration limit for TRC.

3. This permit contains a maximum allowable TRC level in the effluent. The Permittee is responsible for determining the minimum TRC level needed in the chlorine contact chamber to comply with E.coli limits. The effluent shall be dechlorinated if necessary to meet the maximum allowable effluent TRC level.

4. The sample collection point for effluent TRC shall be at a point downstream of the chlorine contact chamber (downstream of dechlorination if applicable). The exact location is to be approved by the Director.

D. PLANT CLASSIFICATION

The Permittee shall report to the Director within 30 days of the effective date of this permit, the name, address and operator number of the certified wastewater operator in responsible charge of the facility. Unless specified elsewhere in this permit, this facility shall be classified in accordance with ADEM Admin. Code R. 335-10-1-.03.

E. POLLUTANT SCANS

The Permittee shall sample and analyze for the pollutants listed in 40 CFR 122 Appendix J Table 2. The Permittee shall provide data from a minimum of three samples collected within the four and one half years prior to submitting a permit application. Samples must be representative of the seasonal variation in the discharge from each outfall.

F. STORM WATER REQUIREMENTS

1. Prohibitions

   a. The Permittee shall not allow the discharge of non-storm water into permitted storm water outfall(s) unless said discharge is already subject to an NPDES permit.

   b. Pollutants removed in the course of treatment or control shall be disposed in a manner that complies with all applicable Department rules and regulations.

2. Operational and Management Practices

   The permittee shall prepare and implement a Storm Water Pollution Prevention (SWPP) Plan within one year of the effective date of this permit.

   a. In the SWPP Plan, the Permittee shall:

      (1) Assess the treatment plant site by developing and presenting site drainage maps, materials inventory, and best management operational practices. The plan shall also include a description of all spill or leak sources;

      (2) Describe mechanisms and procedures to prevent the contact of sewage sludge, screenings, raw or partially treated wastewater, or any other waste product or pollutant with storm water discharged from the facility;

      (3) Provide for daily inspection on workdays of any structures that function to prevent storm water pollution or that remove pollutants from storm water;

      (4) Provide for daily inspection of the facility in general to ensure that the SWPP Plan is continually implemented and effective;

      (5) Include a Best Management Practices (BMP) Plan that, as a minimum, addresses housekeeping, preventative maintenance, spill prevention and response, and non-storm water discharges;

      (6) Describe mechanisms and procedures to provide sediment control sufficient to prevent or control storm water pollution storm water by particles resulting from soil or sediment migration from the site due to significant clearing, grading, or excavation activities;

      (7) Designate by position or name the person or persons responsible for the day to day implementation of the SWPP Plan; and

(8) Bear the signature of an individual meeting signatory requirements as defined in ADEM Administrative Code, Rule 335-6-6-.09.

b. The Director or his designee may notify the permittee at any time that the SWPP Plan is deficient and will require correction of the deficiency. The permittee shall correct any SWPP Plan deficiency identified by the Director or his designee within 30 days of receipt of notification and shall certify to the Department that the correction has been made and implemented.

c. Administrative Procedures

(1) A copy of the SWPP Plan shall be maintained at the facility and shall be available for inspection by the Department.

(2) A log of daily inspections required by Provision IV.F.2.a.(3.) of the permit shall be maintained at the facility and shall be made available for inspection by the Department upon request. The log shall contain records of all inspections performed and each daily entry shall be signed by the person performing the inspection.

(3) The Permittee shall provide training for any personnel required to implement the SWPP Plan and shall retain documentation of such training at the facility. Training records for all personnel shall be available for inspection by the Department. Training shall be performed prior to the date implementation is required.

3. Monitoring Requirements

a. Storm water discharged through each storm water outfall shall be sampled once per calendar year, using first flush grab samples (FFGS) collected during the first 30 minutes of discharge.

b. The total volume of storm water discharged for the event must be monitored, including the date and duration (in hours) and rainfall (in inches) for the storm event(s) sampled. The duration between the storm event sampled and the end of the previous measurable (greater than 0.1 inch rainfall) storm event must be a minimum of 72 hours. This information must be recorded as part of the sampling procedure and records retained in accordance with Provision I.B.5. of this permit. The volume may be measured using flow measurement devices or may be estimated using any method approved in writing by the Department.

ALABAMA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
WATER DIVISION – INDUSTRIAL AND MUNICIPAL SECTIONS
NONCOMPLIANCE NOTIFICATION FORM

PERMITTEE NAME: _____ PERMIT NO: _____

FACILITY LOCATION: _____

DMR REPORTING PERIOD: _____

1. DESCRIPTION OF DISCHARGE: (Include outfall number (s))

2. DESCRIPTION OF NON-COMPLIANCE: (Attach additional pages if necessary):

LIST EFFLUENT VIOLATIONS (If applicable)			
Outfall Number (s)	NONCOMPLIANCE PARAMETER(S)	Result Reported (Include units)	Permit Limit (Include units)
LIST MONITORING / REPORTING VIOLATIONS (If applicable)			
Outfall Number (s)	NONCOMPLIANCE PARAMETER(S)	Monitoring / Reporting Violation (Provide description)	

3. CAUSE OF NON-COMPLIANCE (Attach additional pages if necessary):

4. PERIOD OF NONCOMPLIANCE: (Include exact date(s) and time(s) or, if not corrected, the anticipated time the noncompliance is expected to continue):

5. DESCRIPTION OF STEPS TAKEN AND/OR BEING TAKEN TO REDUCE OR ELIMINATE THE NONCOMPLYING DISCHARGE AND TO PREVENT ITS RECURRENCE (attach additional pages if necessary):

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."

_____
NAME AND TITLE OF RESPONSIBLE OFFICIAL (type or print)

_____/_____
SIGNATURE OF RESPONSIBLE OFFICIAL / DATE SIGNED

ADEM Form 421 09/05

FACT SHEET

APPLICATION FOR
NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM
PERMIT TO DISCHARGE TREATED WASTEWATERS
TO WATERS OF THE STATE OF ALABAMA

Date: March 11, 2016 Prepared By: Dustin Stokes

NPDES Permit No. AL0022586

1. SYNOPSIS OF APPLICATION

a. Name and Address of Applicant and Location if Different From Mailing Address

Applicant Name and Address:	Facility Location:
Jacksonville Water Works, Gas And Sewer Board	Jacksonville WWTP
330 Church Avenue SE	655 Nisbet Street NW
Jacksonville Al 36265	Jacksonville, Alabama 36265

b. Description of Applicant's Facility or Activity Generating the Discharge

Municipal Wastewater Treatment Plant

For the Outfall latitude and longitude see the permit application

c. Applicant's Receiving Waters

Receiving Waters	Classification
UT to Tallasseehatchee Creek	F&W

d. Quantitative Description of Proposed Discharges

See attached draft permit and permit application

2. PROPOSED DISCHARGE LIMITATIONS

See attached draft permit

3. STATEMENT OF BASIS FOR PERMIT LIMITATIONS

See attached permit rationale

4. PROCEDURES FOR THE FORMULATION OF FINAL DETERMINATIONS

a. Comment Period

The Alabama Department of Environmental Management proposes to issue an NPDES permit to this applicant subject to the effluent limitations and special conditions outlined above. These determinations are tentative.

Interested persons are invited to submit written comments on the permit application or on proposed determinations to the following address:

Russell A. Kelly, Chief
Permits and Services Division
Alabama Department of Environmental Management
1400 Coliseum Blvd
(Mailing Address: Post Office Box 301463; Zip 36130-1463)
Montgomery, Alabama 36110-2059
(334) 271-7714

All comments received prior to the closure of the public notice period (see attached public notice) will be considered in the formulation of final determinations with regard to this application.

b. Public Hearing

A written request for a public hearing may also be filed with the public notice period and must state the nature of the issues proposed to be raised in the hearing. The Director shall hold a public hearing whenever it is found, on the basis of hearing requests, that there exists a significant degree of public interest in the permit application or draft permit or group of permits. A request for a hearing should be filed with the Department at the following address:

Russell A. Kelly, Chief
Permits and Services Division
Alabama Department of Environmental Management
1400 Coliseum Blvd
(Mailing Address: Post Office Box 301463; Zip 36130-1463)
Montgomery, Alabama 36110-2059
(334) 271-7714

The Director may hold a public hearing if he determines that useful information and data may be obtained thereby. Public notice of such a hearing will be published at least 30 days prior to the hearing in a newspaper having general circulation in the geographical area of the discharge and will be sent to those on the ADEM mailing list at least thirty days prior to the hearing.

c. Issuance of the Permit

Upon the expiration of the comment period and, if applicable, completion of the public hearing process a response to all significant comments will be prepared. After consideration of all comments received during the notice period or as the result of a public hearing, the response to comments, and of the requirements of the Alabama Water Pollution Control Act and appropriate regulations, the Director will make a final decision regarding permit issuance. **The permit record, including the response to comments, will be available to the public and an appointment to review the record may be made by writing the Permits and Services Division at the above address.**

Unless a request for a stay of a permit or permit provision is granted, the proposed permit contained in the Director's determination shall be issued and effective; and will be the final action of the Alabama Department of Environmental Management.

d. Appeal Procedures

Any person adversely affected by the Director's final decision may submit an appeal or a request for a stay of the permit or one or more provisions of the permit. Such requests should be received by the

Environmental Management Commission within thirty days of issuance of the permit. Requests should be submitted to the Chairperson at the following address:

Alabama Environmental Management Commission
1400 Coliseum Blvd
(Mailing Address: Post Office Box 301463; Zip 36130-1463)
Montgomery, Alabama 36110-2059

All requests must:

(i) State the name, mailing address and telephone number of the person making such request;

(ii) Identify the interest of the appellant which is affected by the proposed issuance, denial or modification of the permit contained in the determination of the Director, and explain how and to what extent that interest would be directly and adversely affected by such determination;

(iii) Identify any persons whom the request represents;

(iv) State with particularity the issues proposed to be considered at the hearing;

(v) Include any terms and conditions with which the appellant proposes to revise or replace the determinations of the Director;

(vi) State the name, mailing address and telephone number of the attorney for the person making the request, if represented by an attorney; and

(vii) An original signature of the person making the request or such person's attorney.

The Commission may rule on the appeal or may hold an appeals hearing prior to making a ruling.

NPDES PERMIT RATIONALE

NPDES Permit No:	**AL0022586**	Date: August 2, 2016
Permit Applicant:	Jacksonville Water Works, Gas and Sewer Board 330 Church Avenue SE Jacksonville, Alabama 36265	
Location:	Jacksonville WWTP 655 Nisbet Street Jacksonville, Alabama 36265	
Draft Permit is:	Initial Issuance: Reissuance due to expiration: Modification of existing permit: Revocation and Reissuance:	 X
Basis for Limitations:	Water Quality Model: Reissuance with no modification: Instream calculation at 7Q10: Toxicity based: Secondary Treatment Levels: Other (described below):	DO, NH3-N, CBOD DO, pH, TSS, NH3-N, TRC, E. coli, CBOD, CBOD % Removal, TSS % Removal 54% TRC TSS, TSS % Removal, CBOD % Removal pH, E. coli, Mercury, Zinc
Design Flow in Million Gallons per Day:	3.5 MGD	
Major:	Yes	
Description of Discharge:	Outfall Number 0011; Effluent discharge to a UT to Tallasseehatchee Creek, which is classified as Fish & Wildlife. Outfall Number 001S; Stormwater discharge to a UT to Tallasseehatchee Creek, which is classified as Fish & Wildlife.	

Discussion: This is a permit reissuance due to expiration. Limits for Five Day Carbonaceous Biochemical Oxygen Demand (CBOD), Total Ammonia-Nitrogen (NH3-N), and Dissolved Oxygen (DO) were developed based on a Waste Load Allocation (WLA) model that was completed by ADEM's Water Quality Branch (WQB) on February 29, 2016. The monthly average limit for CBOD is 25.0 mg/L. The monthly average limits for NH3-N summer (May-November and winter (December-April) are 2.0 mg/L and 3.0 mg/L, respectively. The daily minimum DO limit is 6.0 mg/L.

The pH daily minimum and daily maximum limits of 6.0 to 8.5 S.U, respectively, were developed to be supportive of the water-use classification of the receiving stream. The Total Residual Chlorine (TRC) limits of 0.02 mg/L (monthly average) and 0.03 mg/L

(daily maximum) are based on EPA's recommended water quality values and on the current Toxicity Rationale, which considers the available dilution in the receiving stream. In accordance with a letter dated August 11, 1998 from EPA Headquarters and a 1991 memorandum from EPA Region 4's Environmental Services Division (ESD), due to testing and method detection limitations, a Total Residual Chlorine measurement below 0.05 mg/L shall be considered below detection for compliance purposes. Monitoring for TRC is only applicable if chlorine is utilized for disinfection purposes.

The imposed E. coli limits were determined based on the water-use classification of the receiving streams. Since the UT to Tallasseehatchee Creek is classified as Fish & Wildlife, the limits for June-September for the monthly average and daily maximum are 126 col/100mL and 487 col/100mL, respectively. The limits for October -May for the monthly average and daily maximum are 548 col/100mL and 2507 col/100mL, respectively.

The Total Suspended Solids (TSS) and TSS % removal limits of 30.0 mg/L monthly average and 85.0%, respectively, are based on the requirements of 40 CFR part 133.102 regarding Secondary Treatment. A minimum percent removal limit of 85.0% is imposed for CBOD also in accordance with 40 CFR 133.102 regarding Secondary Treatment.

This permit requires the Permittee to monitor and report the nutrient-related parameters of Total Kjeldahl Nitrogen (TKN), Nitrate plus Nitrite Nitrogen (N02+N03-N) and Total Phosphorus (TP). Monitoring for these nutrient related parameters is imposed so that sufficient information will be available regarding the nutrient contribution from this point source, should it be necessary at some later time to impose nutrient limits on this discharge.

Storm water runoff monitoring is being imposed by this permit based on 40 CFR Part 122. The designated outfall for storm water runoff monitoring is 001S. Storm water runoff is to be monitored annually.

Because this is a major facility (design capacity greater than 1 MGD) treating both municipal and industrial wastewater, chronic toxicity testing with two species (Ceriodaphnia and Pimephales) is being imposed on this permit. Toxicity testing is imposed for both survival and life-cycle impairment (i.e., growth and reproduction). Chronic toxicity at the IWC of 54 percent is required once per year during the month of November. Due to the Department's anti-degradation policy being met, the IWC is not backsliding. If the toxicity tests of the effluent from Outfall 001T indicate chronic toxicity, then toxicity tests may be required to be conducted during the months of February, May, August and November.

Because this is a major facility treating both municipal and industrial wastewater, the Department completed a reasonable potential analysis (RPA) of the discharge based on the application and DMR data. The RPA indicates whether pollutants in treated effluent have potential to contribute to excursions of Alabama's in-stream water quality standards. Based on the analytical data submitted by the Permittee, it appears reasonable potential may exist to cause an in-stream water quality criteria exceedance for zinc and mercury. As a result, the Department is imposing a monthly average and daily maximum discharge limitation for Total Recoverable Zinc of 582 µg/L. Additionally, the Department is imposing monthly average and daily maximum discharge limitations for Total Recoverable Mercury of 0.022 µg/L and 3.93 µg/L, respectively. Due to the

Department's anti-degradation policy being met, the Mercury limits are not backsliding. The RPA also shows a reasonable potential for Arsenic to exceed the in-stream water criteria. However, per the Department's request, the Permittee performed additional Arsenic testing in the form of Trivalent Arsenic. This was done in order to more accurately determine if the reasonable potential for in-stream water quality to be exceeded could be attributed to the Permittee or the background stream data. Because there are no industrial dischargers expected to contribute Arsenic and the results from the Trivalent Arsenic testing were all below detect, it is determined that the Permittee is not expected to be a contributor to excursions of Alabama's in-stream water quality standards. Free Available Cyanide will no longer be required because all test results were below the detection limit on the previous permit.

The monitoring frequency for DO, pH, TSS, NH3-N, TRC, E. coli and CBOD is thrice per week. The monitoring frequency for Zinc, TKN, N02+N03-N and TP is once per month. TSS % Removal and CBOD % Removal are to be calculated once per month. The monitoring frequency for Mercury is once per quarter. Flow is to be continuously monitored daily.

Tallasseehatchee Creek is a Tier I stream and is not listed on the most recent 303(d) list. There are no TMDLs affecting this discharge.

ADEM Administrative Rule 335-6-10-.12 requires applicants for new or expanded discharges to Tier II waters demonstrate that the proposed discharge is necessary for important economic or social development in the area in which the waters are located. The application submitted by the facility is not for a new or expanded discharge to a Tier II water body, so the applicant is not required to demonstrate that the discharge is necessary for economic and social development.

Prepared by: Dustin Stokes

TOXICITY AND DISINFECTION RATIONALE

Facility Name:	**Jacksonville WWTP**	
NPDES Permit Number:	**AL0022586**	
Receiving Stream:	**UT to Tallasseehatchee Creek**	
Facility Design Flow (Q_w):	**3.500 MGD**	
Receiving Stream $7Q_{10}$:	**4.620 cfs**	
Receiving Stream $1Q_{10}$:	**3.470 cfs**	
Winter Headwater Flow (WHF):	**6.16 cfs**	
Summer Temperature for CCC:	**28 deg. Celsius**	
Winter Temperature for CCC:	**18 deg. Celsius**	
Headwater Background NH_3-N Level:	**0.11 mg/l**	
Receiving Stream pH:	**7.0 s.u.**	
Headwater Background FC Level (summer):	**N./A.**	**(Only applicable for facilities with diffusers.)**
(winter)	**N./A.**	

The Stream Dilution Ration (SDR) is calculated using the 7Q10 for all stream classifications.

$$\text{Stream Dilution Ration (SDR)} = \frac{Qw}{7Q10 + Qw} = \textbf{53.96\%}$$

AMMONIA TOXICITY LIMITATIONS

Toxicity-based ammonia limits are calculated in accordance with the *Ammonia Toxicity Protocol* and the *General Guidance for Writing Water Quality Based Toxicity Permits.*

If the Limiting Dilution is less than 1%, the waterbody is considered stream-dominated and the CMC applies.
If the Limiting Dilution is greater than 1%, the waterbody is considered effluent-dominated and the CCC applies.

$$\text{Limiting Dilution} = \frac{Q_w}{7Q_{10} + Q_w}$$

$$= \textbf{53.96\%} \qquad \textbf{Effluent-Dominated, CCC Applies}$$

Criterion Maximum Concentration (CMC): $CMC=0.411/(1+10^{(7.204-pH)}) + 58.4/(1+10^{(pH-7.204)})$

Criterion Continuous Concentration (CCC): $CCC=[0.0577/(1+10^{(7.688-pH)}) + 2.487/(1+10^{(pH-7.688)})] * Min[2.85,1.45*10^{(0.028*(25-T))}]$

	CMC	CCC
Allowable Summer Instream NH_3-N:	**36.09 mg/l**	**2.48 mg/l**
Allowable Winter Instream NH_3-N:	**36.09 mg/l**	**4.72 mg/l**

$$\text{Summer } NH_3\text{-N Toxicity Limit} = \frac{[(\text{Allowable Instream } NH_3\text{-N}) * (7Q_{10} + Q_w)] - [(\text{Headwater } NH_3\text{-N}) * (7Q_{10})]}{Q_w}$$

= 4.5 mg/l NH3-N at 7Q10

$$\text{Winter } NH_3\text{-N Toxicity Limit} = \frac{[(\text{Allowable Instream } NH_3\text{-N}) * (WHF + Q_w)] - [(\text{Headwater } NH_3\text{-N}) * (WHF)]}{Q_w}$$

= 10.0 mg/l NH3-N at Winter Flow

The ammonia limits established in the permit will be the lesser of the DO-based ammonia limit (from the wasteload allocation model) or the toxicity limits calculated above.

	DO-based NH3-N limit	Toxicity-based NH3-N limit
Summer	**2.00 mg/l NH3-N**	**4.50 mg/l NH3-N**
Winter	**3.00 mg/l NH3-N**	**10.00 mg/l NH3-N**

Summer: The DO based limit of 2.00 mg/l NH3-N applies.
Winter: The DO based limit of 3.00 mg/l NH3-N applies.

TOXICITY TESTING REQUIREMENTS (REFERENCE: MUNICIPAL BRANCH TOXICITY PERMITTING STRATEGY)

The following factors trigger toxicity testing requirements:

1. Facility design flow is equal to or greater than 1.0 MGD (major facility).
2. There are significant industrial contributors (SID permits).

Acute toxicity testing is specified for A&I receiving streams, or for stream dilution ratios of 1% or less.
Chronic toxicity testing is specified for all other situations requiring toxicity testing.

Chronic toxicity testing is required

Instream Waste Concentration (IWC) = $\frac{Qw}{7Q10 + Qw}$ = **53.96%** Note: This number will be rounded up for toxicity testing purposes.

DISINFECTION REQUIREMENTS

Bacteria limits are required, and will be the water quality limit for the receiving stream, except where diffusers are used the limit may be adjusted for the dilution provided by the diffuser.

See the attached Disinfection Guidance for applicable stream standards.

(Non-coastal limits apply)
Applicable Stream Classification: **Fish & Wildlife**
Disinfection Type: **Chlorination**
Limit calculation method: **Limits based on meeting stream standards at the point of discharge.**

	Stream Standard (colonies/100ml)	Effluent Limit (colonies/100ml)
E. Coli (applies to Non-coastal and Shellfish Harvesting Coastal)		
Monthly limit as monthly average (October through May):	548	**548**
Monthly limit as monthly aveage (June through September):	126	**126**
Daily Max (October through May):	2507	**2507**
Daily Max (June through September):	487	**487**
Enterococci (applies to Coastal)		
Monthly limit as geometric mean (October through May):	Not applicable	**Not applicable**
Monthly limit as geometric mean (June through September):	Not applicable	**Not applicable**
Daily Max (October through May):	Not applicable	**Not applicable**
Daily Max (June through September):	Not applicable	**Not applicable**

MAXIMUM ALLOWABLE CHLORINATION LIMITS

Toxicity-based chlorine limits are calculated in accordance with the General Guidance for Writing Water Quality Based Toxicity Permits.

Chlorine has been shown to be acutely toxic at 0.019 mg/l and chronically toxic at 0.011 mg/l.

Maximum allowable TRC in effluent:	0.020 mg/l (chronic)	(0.011)/(SDR)
Maximum allowable TRC in effluent:	0.035 mg/l (acute)	(0.019)/(SDR)

NOTE: A maximum chlorine limit will be imposed such that the instream concentration will not exceed acutely toxic concentrations in A & I streams and chronically toxic concentrations in all other streams, but may not exceed 1.0 mg/l.

Prepared By: Dustin Stokes Date: 3/8/2016

Facility Name: Jacksonville WWTP

NPDES No.: AL0022586

$$Q_d * C_d + Q_{d2} * C_{d2} + Q_s * C_s = Q_r * C_r$$

ID	Pollutant	Carcinogen "Yes"	Type	Background from upstream source (C_{d2}) Daily Max	Background from upstream source (C_{d2}) Monthly Ave	Background Instream (C_s) Daily Max	Background Instream (C_s) Monthly Ave	Enter Max Daily Discharge as reported by Applicant (C_{dmax})	Enter Avg Daily Discharge as reported by Applicant (C_{davg})	Partition Coefficient (Stream / Lake)
				µg/l	µg/l	µg/l	µg/l	µg/l	µg/l	
1	Antimony		Metals	0	0	0	0	0	0	-
2	**Arsenic*,****	YES	Metals	0	0	0	0	0	0	0.574
3	Beryllium		Metals	0	0	0	0	0	0	-
4	Cadmium**		Metals	0	0	0	0	0	0	0.236
5	Chromium / Chromium III**		Metals	0	0	0	0	0	0	0.210
6	Chromium / Chromium VI**		Metals	0	0	0	0	0	0	
7	Copper**		Metals	0	0	0	0	0	0	0.388
8	Lead**		Metals	0	0	0	0	0	0	0.206
9	Mercury**		Metals	0	0	0	0	0.022	0.0069	0.302
10	Nickel**		Metals	0	0	0	0	0	0	0.506
11	Selenium		Metals	0	0	0	0	0	0	-
12	Silver		Metals	0	0	0	0	0	0	-
13	Thallium		Metals	0	0	0	0	0	0	-
14	Zinc**		Metals	0	0	0	0	190	88	0.330
15	Cyanide		Metals	0	0	0	0	0	0	-
16	Total Phenolic Compounds		Metals	0	0	0	0	0	0	-
17	Hardness (As CaCO3)		Metals	0	0	0	0	166000	162000	-
18	Acrolein		VOC	0	0	0	0	0	0	-
19	**Acrylonitrile***	YES	VOC	0	0	0	0	0	0	-
20	**Aldrin**	YES	VOC	0	0	0	0	0	0	-
21	**Benzene***	YES	VOC	0	0	0	0	0	0	-
22	**Bromoform***	YES	VOC	0	0	0	0	0	0	-
23	**Carbon Tetrachloride***	YES	VOC	0	0	0	0	0	0	-
24	**Chlordane**	YES	VOC	0	0	0	0	0	0	-
25	Clorobenzene		VOC	0	0	0	0	0	0	-
26	**Chlorodibromo-Methane***	YES	VOC	0	0	0	0	0	0	-
27	Chloroethane		VOC	0	0	0	0	0	0	-
28	2-Chloro-Ethylvinyl Ether		VOC	0	0	0	0	0	0	-
29	**ChioroForm***	YES	VOC	0	0	0	0	0	0	-
30	**4,4'-DDD**	YES	VOC	0	0	0	0	0	0	-
31	**4,4'-DDE**	YES	VOC	0	0	0	0	0	0	-
32	**4.4'-DDT**	YES	VOC	0	0	0	0	0	0	-
33	**Dichlorobromo-Methane***	YES	VOC	0	0	0	0	0	0	-
34	1, 1-Dichloroethane		VOC	0	0	0	0	0	0	-
35	**1, 2-Dichloroethane***	YES	VOC	0	0	0	0	0	0	-
36	Trans-1, 2-Dichloro-Ethylene		VOC	0	0	0	0	0	0	-
37	**1, 1-Dichloroethylene***	YES	VOC	0	0	0	0	0	0	-
38	1, 2-Dichloropropane		VOC	0	0	0	0	0	0	-
39	1, 3-Dichloro-Propylene		VOC	0	0	0	0	0	0	-
40	**Dieldrin**	YES	VOC	0	0	0	0	0	0	-
41	Ethylbenzene		VOC	0	0	0	0	0	0	-
42	Methyl Bromide		VOC	0	0	0	0	0	0	-
43	Methyl Chloride		VOC	0	0	0	0	0	0	-
44	**Methylene Chloride***	YES	VOC	0	0	0	0	0	0	-
45	**1, 1, 2, 2-Tetrachloro-Ethane***	YES	VOC	0	0	0	0	0	0	-
46	**Tetrachloro-Ethylene***	YES	VOC	0	0	0	0	0	0	-
47	Toluene		VOC	0	0	0	0	0	0	-
48	**Toxaphene**	YES	VOC	0	0	0	0	0	0	-
49	**Tributyltine (TBT)**	YES	VOC	0	0	0	0	0	0	-
50	1, 1, 1-Trichloroethane		VOC	0	0	0	0	0	0	-
51	**1, 1, 2-Trichloroethane***	YES	VOC	0	0	0	0	0	0	-
52	**Trichlorethylene***	YES	VOC	0	0	0	0	0	0	-
53	**Vinyl Chloride***	YES	VOC	0	0	0	0	0	0	-
54	P-Chloro-M-Cresol		Acids	0	0	0	0	0	0	-
55	2-Chlorophenol		Acids	0	0	0	0	0	0	-
56	2, 4-Dichlorophenol		Acids	0	0	0	0	0	0	-
57	2, 4-Dimethylphenol		Acids	0	0	0	0	0	0	-
58	4, 6-Dinitro-O-Cresol		Acids	0	0	0	0	0	0	-
59	2, 4-Dinitrophenol		Acids	0	0	0	0	0	0	-
60	**4,6-Dinitro-2-methylophenol**	YES	Acids	0	0	0	0	0	0	-
61	**Dioxin (2,3,7,8-TCDD)**	YES	Acids	0	0	0	0	0	0	-
62	2-Nitrophenol		Acids	0	0	0	0	0	0	-
63	4-Nitrophenol		Acids	0	0	0	0	0	0	-
64	**Pentachlorophenol***	YES	Acids	0	0	0	0	0	0	-
65	Phenol		Acids	0	0	0	0	0	0	-
66	**2, 4, 6-Trichlorophenol***	YES	Acids	0	0	0	0	0	0	-
67	Acenaphthene		Bases	0	0	0	0	0	0	-
68	Acenaphthylene		Bases	0	0	0	0	0	0	-
69	Anthracene		Bases	0	0	0	0	0	0	-
70	Benzidine		Bases	0	0	0	0	0	0	-
71	**Benzo(A)Anthracene***	YES	Bases	0	0	0	0	0	0	-
72	**Benzo(A)Pyrene***	YES	Bases	0	0	0	0	0	0	-
73	3, 4 Benzo-Fluoranthene		Bases	0	0	0	0	0	0	-
74	Benzo(GHI)Perylene		Bases	0	0	0	0	0	0	-
75	Benzo(K)Fluoranthene		Bases	0	0	0	0	0	0	-
76	Bis (2-Chloroethoxy) Methane		Bases	0	0	0	0	0	0	-
77	**Bis (2-Chloroethyl)-Ether***	YES	Bases	0	0	0	0	0	0	-
78	Bis (2-Chloroiso-Propyl) Ether		Bases	0	0	0	0	0	0	-
79	**Bis (2-Ethylhexyl) Phthalate***	YES	Bases	0	0	0	0	0	0	-
80	4-Bromophenyl Phenyl Ether		Bases	0	0	0	0	0	0	-
81	Butyl Benzyl Phthalate		Bases	0	0	0	0	0	0	-
82	2-Chloronaphthalene		Bases	0	0	0	0	0	0	-
83	4-Chlorophenyl Phenyl Ether		Bases	0	0	0	0	0	0	-
84	**Chrysene***	YES	Bases	0	0	0	0	0	0	-
85	Di-N-Butyl Phthalate		Bases	0	0	0	0	0	0	-
86	Di-N-Octyl Phthalate		Bases	0	0	0	0	0	0	-
87	**Dibenzo(A,H)Anthracene***	YES	Bases	0	0	0	0	0	0	-
88	1, 2-Dichlorobenzene		Bases	0	0	0	0	0	0	-
89	1, 3-Dichlorobenzene		Bases	0	0	0	0	0	0	-
90	1, 4-Dichlorobenzene		Bases	0	0	0	0	0	0	-
91	**3, 3-Dichlorobenzene***	YES	Bases	0	0	0	0	0	0	-
92	Diethyl Phthalate		Bases	0	0	0	0	0	0	-
93	Dimethyl Phthalate		Bases	0	0	0	0	0	0	-
94	**2, 4-Dinitrotoluene***	YES	Bases	0	0	0	0	0	0	-
95	2, 6-Dinitrotoluene		Bases	0	0	0	0	0	0	-
96	1,2-Diphenylhydrazine		Bases	0	0	0	0	0	0	-
97	**Endosulfan (alpha)**	YES	Bases	0	0	0	0	0	0	-
98	**Endosulfan (beta)**	YES	Bases	0	0	0	0	0	0	-
99	**Endosulfan sulfate**	YES	Bases	0	0	0	0	0	0	-
100	**Endrin**	YES	Bases	0	0	0	0	0	0	-
101	**Endrin Aldeyhide**	YES	Bases	0	0	0	0	0	0	-
102	Fluoranthene		Bases	0	0	0	0	0	0	-
103	Fluorene		Bases	0	0	0	0	0	0	-
104	Heptochlor	YES	Bases	0	0	0	0	0	0	-
105	Heptachlor Epoxide	YES	Bases	0	0	0	0	0	0	-
106	**Hexachlorobenzene***	YES	Bases	0	0	0	0	0	0	-
107	**Hexachlorobutadiene***	YES	Bases	0	0	0	0	0	0	-
108	**Hexachlorocyclohexan (alpa)**	YES	Bases	0	0	0	0	0	0	-
109	**Hexachlorocyclohexan (beta)**	YES	Bases	0	0	0	0	0	0	-
110	**Hexachlorocyclohexan (gamma)**	YES	Bases	0	0	0	0	0	0	-
111	HexachlorocycloPentadiene		Bases	0	0	0	0	0	0	-
112	Hexachloroethane		Bases	0	0	0	0	0	0	-
113	**Indeno(1, 2, 3-CK)Pyrene***	YES	Bases	0	0	0	0	0	0	-
114	Isophorone		Bases	0	0	0	0	0	0	-
115	Naphthalene		Bases	0	0	0	0	0	0	-
116	Nitrobenzene		Bases	0	0	0	0	0	0	-
117	**N-Nitrosodi-N-Propylamine***	YES	Bases	0	0	0	0	0	0	-
118	**N-Nitrosodi-N-Methylamine***	YES	Bases	0	0	0	0	0	0	-
119	**N-Nitrosodi-N-Phenylamine***	YES	Bases	0	0	0	0	0	0	-
120	**PCB-1016**	YES	Bases	0	0	0	0	0	0	-
121	**PCB-1221**	YES	Bases	0	0	0	0	0	0	-
122	**PCB-1232**	YES	Bases	0	0	0	0	0	0	-
123	**PCB-1242**	YES	Bases	0	0	0	0	0	0	-
124	**PCB-1248**	YES	Bases	0	0	0	0	0	0	-
125	**PCB-1254**	YES	Bases	0	0	0	0	0	0	-
126	**PCB-1260**	YES	Bases	0	0	0	0	0	0	-
127	Phenanthrene		Bases	0	0	0	0	0	0	-
128	Pyrene		Bases	0	0	0	0	0	0	-
129	1, 2, 4-Trichlorobenzene		Bases	0	0	0	0	0	0	-

3.5	Enter Q_d = wastewater discharge flow from facility (MGD)
5.415302	Q_s = wastewater discharge flow (cfs) (this value is calculated from the MGD)
0	Enter or estimated, Qd2 = background stream flow from upstream source (cfs)
4.62	Enter 7Q10, Q_s = background stream flow in cfs above point of discharge
3.47	Enter or estimated, 1Q10, Q_s = background stream flow in cfs above point of discharge (1Q10 estimated at 75% of 7Q10)
0	Enter flow from upstream discharge Qd2 = background stream flow in MGD above point of discharge
11.9	Enter Mean Annual Flow, Q_s = background stream flow in cfs above point of discharge
6.16	Enter 7Q2, Q_s = background stream flow in cfs above point of discharge (For LWF class streams)
Enter to Left	Enter C_s = background in-stream pollutant concentration in µg/l (assuming this is zero "0" unless there is data)
Q_s +Qd2+Q_s	Q_r = resultant in-stream flow, after discharge
Calculated on other	C_r = resultant in-stream pollutant concentration in µg/l in the stream (after complete mixing occurs)
100	Enter, Background Hardness above point of discharge (assumed 50 South of Birmingham and 100 North of Birmingham)
7.00 s.u.	Enter, Background pH above point of discharge
YES	Enter, Is discharge to a stream? "YES" Other option would be to a Lake (This changes the partition coefficients for the metals)

** Using Partition Coefficients*

July 18, 2016

Modified: 8/4/09

Facility Name: Jacksonville WWTP

NPDES No.: AL0022586

						Freshwater F&W classification.					Freshwater Acute (µg/l) Q_s =1Q10					Freshwater Chronic (µg/l) Q_s = 7Q10				Human Health Consumption Fish only (ug/l) Carcinogen Q_s = Annual Average Non-Carcinogen Q_s = 7Q10			
ID	Pollutant	RP?	Carcinogen yes	Background from upstream source (Cd2) Daily Max	Max Daily Discharge as reported by Applicant (C_{max})	Water Quality Criteria (C_t)	Draft Permit Limit (C_{max})	20% of Draft Permit Limit	RP?	Background from upstream source (Cd2) Monthly Ave	Avg Daily Discharge as reported by Applicant (C_{avg})	Water Quality Criteria (C_t)	Draft Permit Limit (C_{avg})	20% of Draft Permit Limit	RP?	Water Quality Criteria (C_t)	Draft Permit Limit (C_{avg})	20% of Draft Permit Limit	RP?
1	Antimony			0	0	-	-	-	-	0	0	-	-	-	-	3.73E+02	6.82E+02	1.36E+02	No
2	Arsenic		YES	0	0	592.334	871.889	194.378	No	0	0	261.324	484.270	96.854	No	3.03E-01	9.68E-01	1.94E-01	No
3	Beryllium			0	0	-	-	-	-	0	0	-	-	-	-	-	-	-	-
4	Cadmium			0	0	8.533	14.000	2.800	No	0	0	1.042	1.932	0.386	No	-	-	-	-
5	Chromium/ Chromium III			0	0	2713.159	4451.689	890.338	No	0	0	352.926	654.021	130.804	No	-	-	-	-
6	Chromium/ Chromium VI			0	0	16.000	26.252	5.250	No	0	0	11.000	20.385	4.077	No	-	-	-	-
7	Copper			0	0	34.637	56.831	11.366	No	0	0	23.082	42.774	8.555	No	1.30E+03	2.41E+03	4.82E+02	No
8	Lead			0	0	313.502	514.387	102.877	No	0	0	12.217	22.639	4.528	No	-	-	-	-
9	Mercury	YES		0	0.022	2.400	3.938	0.788	No	0	0.0069	0.012	0.022	0.004	Yes	4.24E-02	7.86E-02	1.57E-02	No
10	Nickel			0	0	927.200	1521.326	304.266	No	0	0	102.983	190.842	38.168	No	9.93E+02	1.84E+03	3.68E+02	No
11	Selenium			0	0	20.000	32.816	6.563	No	0	0	5.000	9.266	1.853	No	2.43E+03	4.50E+03	9.01E+02	No
12	Silver			0	0	3.217	5.278	1.056	No	0	0	-	-	-	-	-	-	-	-
13	Thallium			0	0	-	-	-	-	0	0	-	-	-	-	2.74E-01	5.07E-01	1.01E-01	No
14	Zinc	YES		0	190	355.092	582.627	116.525	Yes	0	88	357.897	663.418	132.684	No	1.48E+04	2.76E+04	5.52E+03	No
15	Cyanide			0	0	22.000	36.087	7.219	No	0	0	5.200	9.636	1.927	No	9.33E+03	1.73E+04	3.46E+03	No
16	Total Phenolic Compounds			0	0	-	-	-	-	0	0	-	-	-	-	-	-	-	-
17	Hardness (As CaCO3)			0	166000	-	-	-	-	0	182000	-	-	-	-	-	-	-	-
18	Acrolein			0	0	-	-	-	-	0	0	-	-	-	-	5.43E+00	1.01E+01	2.01E+00	No
19	Acrylonitrile		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.44E-01	4.61E-01	9.21E-02	No
20	Aldrin		YES	0	0	3.000	4.922	0.984	No	0	0	1.300	2.409	0.482	No	2.94E-05	9.40E-05	1.88E-05	No
21	Benzene		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.55E+01	4.95E+01	9.89E+00	No
22	Bromoform		YES	0	0	-	-	-	-	0	0	-	-	-	-	7.88E+01	2.52E+02	5.04E+01	No
23	Carbon Tetrachloride		YES	0	0	-	-	-	-	0	0	-	-	-	-	9.57E-01	3.06E+00	6.12E-01	No
24	Chlordane		YES	0	0	2.400	3.938	0.788	No	0	0	0.004	0.008	0.002	No	4.73E-04	1.51E-03	3.02E-04	No
25	Clorobenzene			0	0	-	-	-	-	0	0	-	-	-	-	9.06E+02	1.68E+03	3.36E+02	No
26	Chlorodibramo-Methane		YES	0	0	-	-	-	-	0	0	-	-	-	-	7.41E+00	2.37E+01	4.74E+00	No
27	Chloroethane			0	0	-	-	-	-	0	0	-	-	-	-	-	-	-	-
28	2-Chloro-Ethylvinyl Ether			0	0	-	-	-	-	0	0	-	-	-	-	-	-	-	-
29	ChloroForm		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.02E+02	3.26E+02	6.52E+01	No
30	4,4' - DDD		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.81E-04	5.80E-04	1.16E-04	No
31	4,4' - DDE		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.28E-04	4.09E-04	8.19E-05	No
32	4,4' - DDT		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.28E-04	4.09E-04	8.19E-05	No
33	Dichlorobromo-Methane		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.00E+01	3.21E+01	6.42E+00	No
34	1, 1-Dichloroethane			0	0	-	-	-	-	0	0	-	-	-	-	-	-	-	-
35	1, 2-Dichloroethane		YES	0	0	-	-	-	-	0	0	-	-	-	-	2.14E+01	6.83E+01	1.37E+01	No
36	Trans-1, 2-Dichloro-Ethylene			0	0	-	-	-	-	0	0	-	-	-	-	5.91E+03	1.06E+04	2.19E+03	No
37	1, 1-Dichloroethylene		YES	0	0	-	-	-	-	0	0	-	-	-	-	4.17E+03	1.33E+04	2.66E+03	No
38	1, 2-Dichloropropane			0	0	-	-	-	-	0	0	-	-	-	-	8.49E+00	1.57E+01	3.15E+00	No
39	1, 3-Dichloro-Propylene			0	0	-	-	-	-	0	0	-	-	-	-	1.23E+01	2.28E+01	4.55E+00	No
40	Dieldrin		YES	0	0	0.240	0.394	0.079	No	0	0	0.056	0.104	0.021	No	3.12E-05	9.98E-05	2.00E-05	No
41	Ethylbenzene			0	0	-	-	-	-	0	0	-	-	-	-	1.24E+03	2.31E+03	4.61E+02	No
42	Methyl Bromide			0	0	-	-	-	-	0	0	-	-	-	-	8.71E+02	1.61E+03	3.23E+02	No
43	Methyl Chloride			0	0	-	-	-	-	0	0	-	-	-	-	-	-	-	-
44	Methylene Chloride		YES	0	0	-	-	-	-	0	0	-	-	-	-	3.46E+02	1.11E+03	2.21E+02	No
45	1, 1, 2, 2-Tetrachloro-Ethane		YES	0	0	-	-	-	-	0	0	-	-	-	-	2.33E+00	7.46E+00	1.49E+00	No
46	Tetrachloro-Ethylene		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.92E+00	6.13E+00	1.23E+00	No
47	Toluene			0	0	-	-	-	-	0	0	-	-	-	-	8.72E+03	1.62E+04	3.23E+03	No
48	Toxaphene		YES	0	0	0.730	1.198	0.240	No	0	0	0.0002	0.000	0.000	No	1.62E-04	5.18E-04	1.04E-04	No
49	Tributyltin (TBT)		YES	0	0	0.460	0.755	0.151	No	0	0	0.072	0.133	0.027	No	-	-	-	-
50	1, 1, 1-Trichloroethane			0	0	-	-	-	-	0	0	-	-	-	-	-	-	-	-
51	1, 1, 2-Trichloroethane		YES	0	0	-	-	-	-	0	0	-	-	-	-	9.10E+00	2.91E+01	5.82E+00	No
52	Trichlorethylene		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.75E+01	5.58E+01	1.12E+01	No
53	Vinyl Chloride		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.42E+00	4.55E+00	9.11E-01	No
54	P-Chloro-M-Cresol			0	0	-	-	-	-	0	0	-	-	-	-	-	-	-	-
55	2-Chlorophenol			0	0	-	-	-	-	0	0	-	-	-	-	8.71E+01	1.61E+02	3.23E+01	No
56	2, 4-Dichlorophenol			0	0	-	-	-	-	0	0	-	-	-	-	1.72E+02	3.19E+02	6.37E+01	No
57	2, 4-Dimethylphenol			0	0	-	-	-	-	0	0	-	-	-	-	4.98E+02	9.22E+02	1.84E+02	No
58	4, 6-Dinitro-O-Cresol			0	0	-	-	-	-	0	0	-	-	-	-	-	-	-	-
59	2, 4-Dinitrophenol			0	0	-	-	-	-	0	0	-	-	-	-	3.11E+03	5.77E+03	1.15E+03	No
60	4,6-Dinitro-2-methylphenol		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.65E+02	5.29E+02	1.06E+02	No
61	Dioxin (2,3,7,8-TCDD)		YES	0	0	-	-	-	-	0	0	-	-	-	-	2.67E-08	8.53E-08	1.71E-08	No
62	2-Nitrophenol			0	0	-	-	-	-	0	0	-	-	-	-	-	-	-	-
63	4-Nitrophenol			0	0	-	-	-	-	0	0	-	-	-	-	-	-	-	-
64	Pentachlorophenol		YES	0	0	8.723	14.313	2.863	No	0	0	6.893	12.402	2.480	No	1.77E+00	5.65E+00	1.13E+00	No
65	Phenol			0	0	-	-	-	-	0	0	-	-	-	-	5.00E+05	9.27E+05	1.85E+05	No
66	2, 4, 6-Trichlorophenol		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.41E+00	4.52E+00	9.04E-01	No
67	Acenaphthene			0	0	-	-	-	-	0	0	-	-	-	-	5.79E+02	1.07E+03	2.14E+02	No
68	Acenaphthylene			0	0	-	-	-	-	0	0	-	-	-	-	-	-	-	-
69	Anthracene			0	0	-	-	-	-	0	0	-	-	-	-	2.33E+04	4.32E+04	8.65E+03	No
70	Benzidine			0	0	-	-	-	-	0	0	-	-	-	-	1.16E-04	2.15E-04	4.30E-05	No
71	Benzo(A)Anthracene		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.07E-02	3.41E-02	6.81E-03	No
72	Benzo(A)Pyrene		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.07E-02	3.41E-02	6.81E-03	No
73	3, 4-Benzo-Fluoranthene			0	0	-	-	-	-	0	0	-	-	-	-	1.07E-02	1.97E-02	3.95E-03	No
74	Benzo(GHI)Perylene			0	0	-	-	-	-	0	0	-	-	-	-	-	-	-	-
75	Benzo(K)Fluoranthene			0	0	-	-	-	-	0	0	-	-	-	-	1.07E-02	1.97E-02	3.95E-03	No
76	Bis (2-Chloroethoxy) Methane			0	0	-	-	-	-	0	0	-	-	-	-	-	-	-	-
77	Bis (2-Chloroethyl)-Ether		YES	0	0	-	-	-	-	0	0	-	-	-	-	3.07E-01	9.83E-01	1.97E-01	No
78	Bis (2-Chloroiso-Propyl) Ether			0	0	-	-	-	-	0	0	-	-	-	-	3.78E+04	7.00E+04	1.40E+04	No
79	Bis (2-Ethylhexyl) Phthalate		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.28E+00	4.10E+00	8.20E-01	No
80	4-Bromophenyl Phenyl Ether			0	0	-	-	-	-	0	0	-	-	-	-	-	-	-	-
81	Butyl Benzyl Phthalate			0	0	-	-	-	-	0	0	-	-	-	-	1.13E+03	2.09E+03	4.18E+02	No
82	2-Chloronaphthalene			0	0	-	-	-	-	0	0	-	-	-	-	9.24E+02	1.71E+03	3.42E+02	No
83	4-Chlorophenyl Phenyl Ether			0	0	-	-	-	-	0	0	-	-	-	-	-	-	-	-
84	Chrysene		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.07E-02	3.41E-02	6.81E-03	No
85	Di-N-Butyl Phthalate			0	0	-	-	-	-	0	0	-	-	-	-	2.62E+03	4.86E+03	9.72E+02	No
86	Di-N-Octyl Phthalate			0	0	-	-	-	-	0	0	-	-	-	-	-	-	-	-
87	Dibenzo(A,H)Anthracene		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.07E-02	3.41E-02	6.81E-03	No
88	1, 2-Dichlorobenzene			0	0	-	-	-	-	0	0	-	-	-	-	7.55E+02	1.40E+03	2.80E+02	No
89	1, 3-Dichlorobenzene			0	0	-	-	-	-	0	0	-	-	-	-	5.62E+02	1.04E+03	2.08E+02	No
90	1, 4-Dichlorobenzene			0	0	-	-	-	-	0	0	-	-	-	-	1.12E+02	2.08E+02	4.17E+01	No
91	3, 3-Dichlorobenzene		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.66E-02	5.31E-02	1.06E-02	No
92	Diethyl Phthalate			0	0	-	-	-	-	0	0	-	-	-	-	2.56E+04	4.74E+04	9.48E+03	No
93	Dimethyl Phthalate			0	0	-	-	-	-	0	0	-	-	-	-	6.48E+05	1.20E+06	2.40E+05	No
94	2, 4-Dinitrotoluene		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.98E+00	6.33E+00	1.27E+00	No
95	2, 6-Dinitrotoluene			0	0	-	-	-	-	0	0	-	-	-	-	-	-	-	-
96	1,2-Diphenylhydrazine			0	0	-	-	-	-	0	0	-	-	-	-	1.17E-01	2.17E-01	4.34E-02	No
97	Endosulfan (alpha)		YES	0	0	0.22	0.361	0.072	No	0	0	0.056	0.104	0.021	No	5.19E+01	1.66E+02	3.32E+01	No
98	Endosulfan (beta)		YES	0	0	0.22	0.361	0.072	No	0	0	0.056	0.104	0.021	No	5.19E+01	1.66E+02	3.32E+01	No
99	Endosulfan sulfate		YES	0	0	-	-	-	-	0	0	-	-	-	-	5.19E+01	1.66E+02	3.32E+01	No
100	Endrin		YES	0	0	0.086	0.141	0.028	No	0	0	0.036	0.067	0.013	No	3.53E-02	1.13E-01	2.26E-02	No
101	Endrin Aldeyhde		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.76E+00	5.64E+00	1.13E+00	No
102	Fluoranthene			0	0	-	-	-	-	0	0	-	-	-	-	8.12E+01	1.50E+02	3.01E+01	No
103	Fluorene			0	0	-	-	-	-	0	0	-	-	-	-	3.11E+03	5.77E+03	1.15E+03	No
104	Heptachlor		YES	0	0	0.52	0.853	0.171	No	0	0	0.004	0.007	0.001	No	4.63E-05	1.48E-04	2.96E-05	No
105	Heptachlor Epoxide		YES	0	0	0.52	0.853	0.171	No	0	0	0.004	0.007	0.001	No	2.29E-05	7.32E-05	1.46E-05	No
106	Hexachlorobenzene		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.66E-04	5.37E-04	1.07E-04	No
107	Hexachlorobutadiene		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.08E+01	3.44E+01	6.88E+00	No
108	Hexachlorocyclohexan (alpha)		YES	0	0	-	-	-	-	0	0	-	-	-	-	2.85E-03	9.11E-03	1.82E-03	No
109	Hexachlorocyclohexan (beta)		YES	0	0	-	-	-	-	0	0	-	-	-	-	9.97E-03	3.19E-02	6.38E-03	No
110	Hexachlorocyclohexan (gamma)		YES	0	0	0.95	1.559	0.312	No	0	0	-	-	-	-	1.08E+00	3.44E+00	6.88E-01	No
111	HexachlorocycloPentadiene			0	0	-	-	-	-	0	0	-	-	-	-	6.45E+02	1.20E+03	2.39E+02	No
112	Hexachloroethane			0	0	-	-	-	-	0	0	-	-	-	-	1.92E+00	3.55E+00	7.11E-01	No
113	Indeno(1, 2, 3-CK)Pyrene		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.07E-02	3.41E-02	6.81E-03	No
114	Isophorone			0	0	-	-	-	-	0	0	-	-	-	-	5.61E+02	1.04E+03	2.08E+02	No
115	Naphthalene			0	0	-	-	-	-	0	0	-	-	-	-	-	-	-	-
116	Nitrobenzene			0	0	-	-	-	-	0	0	-	-	-	-	4.04E+02	7.48E+02	1.50E+02	No
117	N-Nitrosodi-N-Propylamine		YES	0	0	-	-	-	-	0	0	-	-	-	-	2.95E-01	9.43E-01	1.89E-01	No
118	N-Nitrosodi-N-Methylamine		YES	0	0	-	-	-	-	0	0	-	-	-	-	1.78E+00	5.63E+00	1.13E+00	No
119	N-Nitrosodi-N-Phenylamine		YES	0	0	-	-	-	-	0	0	-	-	-	-	3.50E+00	1.12E+01	2.24E+00	No
120	PCB-1016		YES	0	0	-	-	-	-	0	0	0.014	0.026	0.005	No	3.74E-05	1.20E-04	2.39E-05	No
121	PCB-1221		YES	0	0	-	-	-	-	0	0	0.014	0.026	0.005	No	3.74E-05	1.20E-04	2.39E-05	No
122	PCB-1232		YES	0	0	-	-	-	-	0	0	0.014	0.026	0.005	No	3.74E-05	1.20E-04	2.39E-05	No
123	PCB-1242		YES	0	0	-	-	-	-	0	0	0.014	0.026	0.005	No	3.74E-05	1.20E-04	2.39E-05	No
124	PCB-1248		YES	0	0	-	-	-	-	0	0	0.014	0.026	0.005	No	3.74E-05	1.20E-04	2.39E-05	No
125	PCB-1254		YES	0	0	-	-	-	-	0	0	0.014	0.026	0.005	No	3.74E-05	1.20E-04	2.39E-05	No
126	PCB-1260		YES	0	0	-	-	-	-	0	0	0.014	0.026	0.005	No	3.74E-05	1.20E-04	2.39E-05	No
127	Phenanthrene			0	0	-	-	-	-	0	0	-	-	-	-	-	-	-	-
128	Pyrene			0	0	-	-	-	-	0	0	-	-	-	-	2.33E+03	4.32E+03	8.65E+02	No
129	1, 2, 4-Trichlorobenzene			0	0	-	-	-	-	0	0	-	-	-	-	4.09E+01	7.58E+01	1.52E+01	No

Permit Number	Monitor Pd End Date	Parameter	Monthly Average	Maximum Daily	Unit
AL0022586	12/31/11	Mercury	0.0147	0.0147	ug/l
AL0022586	03/31/12	Mercury	0.004	0.004	ug/l
AL0022586	06/30/12	Mercury	0.0032	0.0032	ug/l
AL0022586	09/30/12	Mercury	0.0026	0.0026	ug/l
AL0022586	12/31/12	Mercury	0.004	0.004	ug/l
AL0022586	03/31/13	Mercury	0.009	0.009	ug/l
AL0022586	06/30/13	Mercury	0.014	0.014	ug/l
AL0022586	09/30/13	Mercury	0.007	0.007	ug/l
AL0022586	12/31/13	Mercury	0.012	0.022	ug/l
AL0022586	03/31/14	Mercury	0.008	0.008	ug/l
AL0022586	06/30/14	Mercury	0.001	0.001	ug/l
AL0022586	09/30/14	Mercury	0.006	0.006	ug/l
AL0022586	12/31/14	Mercury	0.008	0.008	ug/l
AL0022586	03/31/15	Mercury	0.016	0.016	ug/l
AL0022586	06/30/15	Mercury	0.005	0.005	ug/l
AL0022586	09/30/15	Mercury	0	0	ug/l
AL0022586	12/31/15	Mercury	0.002	0.002	ug/l

Average (ug/L)	0.0069	Maximum (ug/L)	0.022

Permit Number	Monitor Period	Parameter	Monthly Average	Maximum Daily	Unit
AL0022586	10/31/11	Cyanide	0	0	ug/l
AL0022586	11/30/11	Cyanide	0	0	ug/l
AL0022586	12/31/11	Cyanide	0	0	ug/l
AL0022586	1/31/12	Cyanide	0	0	ug/l
AL0022586	2/29/12	Cyanide	0	0	ug/l
AL0022586	3/31/12	Cyanide	0	0	ug/l
AL0022586	4/30/12	Cyanide	0	0	ug/l
AL0022586	5/31/12	Cyanide	0	0	ug/l
AL0022586	6/30/12	Cyanide	0	0	ug/l
AL0022586	7/31/12	Cyanide	0	0	ug/l
AL0022586	8/31/12	Cyanide	0	0	ug/l
AL0022586	9/30/12	Cyanide	0	0	ug/l
AL0022586	10/31/12	Cyanide	0	0	ug/l
AL0022586	11/30/12	Cyanide	0	0	ug/l
AL0022586	12/31/12	Cyanide	0	0	ug/l
AL0022586	1/31/13	Cyanide	0	0	ug/l
AL0022586	2/28/13	Cyanide	0	0	ug/l
AL0022586	3/31/13	Cyanide	0	0	ug/l
AL0022586	4/30/13	Cyanide	0	0	ug/l
AL0022586	5/31/13	Cyanide	0	0	ug/l
AL0022586	6/30/13	Cyanide	0	0	ug/l
AL0022586	7/31/13	Cyanide	0	0	ug/l
AL0022586	8/31/13	Cyanide	0	0	ug/l
AL0022586	9/30/13	Cyanide	0	0	ug/l
AL0022586	10/31/13	Cyanide	0	0	ug/l
AL0022586	11/30/13	Cyanide	0	0	ug/l
AL0022586	12/31/13	Cyanide	0	0	ug/l
AL0022586	1/31/14	Cyanide	0	0	ug/l
AL0022586	2/28/14	Cyanide	0	0	ug/l
AL0022586	3/31/14	Cyanide	0	0	ug/l
AL0022586	4/30/14	Cyanide	0	0	ug/l
AL0022586	5/31/14	Cyanide	0	0	ug/l
AL0022586	6/30/14	Cyanide	0	0	ug/l
AL0022586	7/31/14	Cyanide	0	0	ug/l
AL0022586	8/31/14	Cyanide	0	0	ug/l
AL0022586	9/30/14	Cyanide	0	0	ug/l
AL0022586	10/31/14	Cyanide	0	0	ug/l
AL0022586	11/30/14	Cyanide	0	0	ug/l
AL0022586	12/31/14	Cyanide	0	0	ug/l
AL0022586	1/31/15	Cyanide	0	0	ug/l
AL0022586	2/28/15	Cyanide	0	0	ug/l
AL0022586	3/31/15	Cyanide	0	0	ug/l
AL0022586	4/30/15	Cyanide	0	0	ug/l
AL0022586	5/31/15	Cyanide	0	0	ug/l
AL0022586	6/30/15	Cyanide	0	0	ug/l
AL0022586	7/31/15	Cyanide	0	0	ug/l
AL0022586	8/31/15	Cyanide	0	0	ug/l
AL0022586	9/30/15	Cyanide	0	0	ug/l
AL0022586	10/31/15	Cyanide	0	0	ug/l
AL0022586	11/30/15	Cyanide	0	0	ug/l
AL0022586	12/31/15	Cyanide	0	0	ug/l
AL0022586	1/31/16	Cyanide	0	0	ug/l
AL0022586	Application	Cyanide	0	0	ug/l
AL0022586	Application	Cyanide	0	0	ug/l
AL0022586	Application	Cyanide	0	0	ug/l

Average (ug/L)	0.0000	Maximum (ug/L)	0

Waste Load Allocation Summary

REQUEST INFORMATION

request number: 3301

From:	Dustin Stokes	In Branch/Section	Municipal		
Date Submitted	1/28/2016	Date Required	2/27/2016	FUND Code	605
Receiving Waterbody	Tallasseehatchee Creek UT	Date Permit application received by NPDES program	12/14/2015		
Previous Stream Name					
Facility Name	Jacksonville WWTP	(Name of Discharger-WQ will use to file)			
		Previous Discharger Name			
River Basin	Coosa	Outfall Latitude	33.8245	(decimal degrees)	
*County	Calhoun	Outfall Longitude	-85.78298	(decimal degrees)	
Permit Number	AL0022586	Permit Type	Permit Reissuance		
		Permit Status	Active		
		Type of Discharger	MUNICIPAL		

Do other discharges exist that may impact the model? ☑ Yes ☐ No

If yes, impacting dischargers names.	Impacting dischargers permit numbers.
Whispering Pines WWTP Alexandria School WWTP Alexandria Mall WWTP	AL0057703 AL0055549 AL0073946

			Note: The flow rates given should be those requested for modeling.
Existing Discharge Design Flow	3.5	MGD	
Proposed Discharge Design Flow	3.5	MGD	

Comments included ☑ Yes ☐ No

Information Verified By: TCG

Year File Was Created: 1984

Lat/Long Method: GPS

12 Digit HUC Code	031501060402		
Use Classification	F&W		
Site Visit Completed?	☑ Yes ☐ No	Date of Site Visit	2/12/2016
Waterbody Impaired?	☐ Yes ☑ No	Date of WLA Response	2/29/2016
Antidegradation	☐ Yes ☑ No	Approved TMDL?	☐ Yes ☑ No
Waterbody Tier Level	Tier I		
Use Support Category	3	Approval Date of TMDL	

Waste Load Allocation Information

Modeled Reach Length	24.67	Miles	Date of Allocation	2/29/2016	
Name of Model Used	SWQM		Allocation Type	2 Seasons	
Model Completed by	Taylor Griswell		Type of Model Used	Desk-top	
Allocation Developed by	Water Quality Branch				

Waste Load Allocation Summary

Annual Effluent Limits		Conventional Parameters		Conventional Parameters		Other Parameters		Other Parameters	
		Qw 3.5 MGD		Qw 3.5 MGD		Qw MGD		Qw MGD	
Qw	MGD	Season	Summer	Season	Winter	Season		Season	
		From	May	From	Dec	From		From	
		Through	Nov	Through	Apr	Through		Through	
CBOD5		CBOD5	25 mg/L	CBOD5	25 mg/L	TP		TP	
NH3-N		NH3-N	2 mg/L	NH3-N	3 mg/L	TN		TN	
TKN		TKN		TKN		TSS		TSS	
D.O.		D.O.	6 mg/L	D.O.	6 mg/L				

"Monitor Only" Parameters for Effluent:	Parameter	Frequency	Parameter	Frequency
	TP	Monthly		
	NO2+NO3-N	Monthly		
	TKN	Monthly		

Water Quality Characteristics Immediately Upstream of Discharge

Parameter	Summer		Winter	
CBODu	2	mg/l	2	mg/l
NH3-N	0.11	mg/l	0.11	mg/l
Temperature	28	℃	18	℃
pH	7	su	7	su

Hydrology at Discharge Location

Drainage Area Qualifier				Method Used to Calculate
Exact	Drainage Area	9.43	sq mi	
	Stream 7Q10	4.62	cfs	ADEM Estimate w/USGS Gage Data
	Stream 1Q10	3.47	cfs	75%of 7Q10
	Stream 7Q2	6.16	cfs	ADEM Estimate w/USGS Gage Data
	Annual Average	11.9	cfs	

Comments and/or Notations: Three other NPDES facilities are included in this model. Outputs from these facilities were used in this updated model. See respective WLA files for models of the other facilities.

Please print or type in the unshaded areas only.

Form Approved. OMB No. 2040-0086.

FORM 1 GENERAL

EPA

U.S. ENVIRONMENTAL PROTECTION AGENCY
GENERAL INFORMATION
Consolidated Permits Program
(Read the "General Instructions" before starting.)

I. EPA I.D. NUMBER

F

LABEL ITEMS

- I. EPA I.D. NUMBER
- III. FACILITY NAME
- V. FACILITY MAILING ADDRESS
- VI. FACILITY LOCATION

PLEASE PLACE LABEL IN THIS SPACE

GENERAL INSTRUCTIONS

If a preprinted label has been provided, affix it in the designated space. Review the information carefully; if any of it is incorrect, cross through it and enter the correct data in the appropriate fill-in area below. Also, if any of the preprinted data is absent *(the area to the left of the label space lists the information that should appear)*, please provide it in the proper fill-in area(s) below. If the label is complete and correct, you need not complete Items I, III, V, and VI *(except VI-B which must be completed regardless)*. Complete all items if no label has been provided. Refer to the instructions for detailed item descriptions and for the legal authorizations under which this data is collected.

II. POLLUTANT CHARACTERISTICS

INSTRUCTIONS: Complete A through J to determine whether you need to submit any permit application forms to the EPA. If you answer "yes" to any questions, you must submit this form and the supplemental form listed in the parenthesis following the question. Mark "X" in the box in the third column if the supplemental form is attached. If you answer "no" to each question, you need not submit any of these forms. You may answer "no" if your activity is excluded from permit requirements; see Section C of the instructions. See also, Section D of the instructions for definitions of **bold-faced terms**.

SPECIFIC QUESTIONS	Mark "X" YES	NO	FORM ATTACHED
A. Is this facility a **publicly owned treatment works** which results in a **discharge to waters of the U.S.**? (FORM 2A)	X		X
B. Does or will this facility *(either existing or proposed)* include a **concentrated animal feeding operation** or **aquatic animal production facility** which results in a **discharge to waters of the U.S.**? (FORM 2B)		X	
C. Is this a facility which currently results in **discharges to waters of the U.S.** other than those described in A or B above? (FORM 2C)		X	
D. Is this a proposed facility *(other than those described in A or B above)* which will result in a **discharge to waters of the U.S.**? (FORM 2D)		X	
E. Does or will this facility treat, store, or dispose of **hazardous wastes**? (FORM 3)		X	
F. Do you or will you inject at this facility industrial or municipal effluent below the lowermost stratum containing, within one quarter mile of the well bore, underground sources of drinking water? (FORM 4)		X	
G. Do you or will you inject at this facility any produced water or other fluids which are brought to the surface in connection with conventional oil or natural gas production, inject fluids used for enhanced recovery of oil or natural gas, or inject fluids for storage of liquid hydrocarbons? (FORM 4)		X	
H. Do you or will you inject at this facility fluids for special processes such as mining of sulfur by the Frasch process, solution mining of minerals, in situ combustion of fossil fuel, or recovery of geothermal energy? (FORM 4)		X	
I. Is this facility a proposed **stationary source** which is one of the 28 industrial categories listed in the instructions and which will potentially emit 100 tons per year of any air pollutant regulated under the Clean Air Act and may affect or be located in an attainment area? (FORM 5)		X	
J. Is this facility a proposed **stationary source** which is NOT one of the 28 industrial categories listed in the instructions and which will potentially emit 250 tons per year of any air pollutant regulated under the Clean Air Act and may affect or be located in an **attainment area**? (FORM 5)		X	

III. NAME OF FACILITY

1 SKIP: JACKSONVILLE WASTEWATER TREATMENT PLANT

IV. FACILITY CONTACT

A. NAME & TITLE *(last, first, & title)*: 2 JOHNNY L. SMITH, Mayor / Superintendent

B. PHONE *(area code & no.)*: (256) 435-7611

V. FACILTY MAILING ADDRESS

A. STREET OR P.O. BOX: 3 330 CHURCH AVENUE SE

B. CITY OR TOWN: 4 JACKSONVILLE WASTEWATER TREATMENT PLANT

C. STATE: AL

D. ZIP CODE: 36265

VI. FACILITY LOCATION

A. STREET, ROUTE NO. OR OTHER SPECIFIC IDENTIFIER: 5 655 NISBET STREET NW

B. COUNTY NAME: CALHOUN

C. CITY OR TOWN: 6 JACKSONVILLE

D. STATE: AL

E. ZIP CODE: 36265

F. COUNTY CODE *(if known)*:

RECEIVED DEC 14 2015 IND / MUN BRANCH

RECEIVED DEC 14 2015 IND / MUN BRANCH

CONTINUED FROM THE FRONT

VII. SIC CODES *(4-digit, in order of priority)*

A. FIRST	B. SECOND
7 (specify) N/A	7 (specify) N/A

C. THIRD	D. FOURTH
7 (specify) N/A	7 (specify) N/A

VIII. OPERATOR INFORMATION

A. NAME: JACKSONVILLE WATER WORKS, GAS AND SEWER BOARD

B. Is the name listed in Item VIII-A also the owner? ☑ YES ☐ NO

C. STATUS OF OPERATOR *(Enter the appropriate letter into the answer box; if "Other," specify.)*

F = FEDERAL
S = STATE
P = PRIVATE
M = PUBLIC *(other than federal or state)*
O = OTHER *(specify)*

M (specify)

D. PHONE *(area code & no.)*: A (256) 435-7611

E. STREET OR P.O. BOX: 330 CHURCH AVENUE SE

F. CITY OR TOWN	G. STATE	H. ZIP CODE	IX. INDIAN LAND
JACKSONVILLE	AL	36265	Is the facility located on Indian lands? ☐ YES ☑ NO

X. EXISTING ENVIRONMENTAL PERMITS

A. NPDES *(Discharges to Surface Water)*	D. PSD *(Air Emissions from Proposed Sources)*
9 N AL0022586	9 P
B. UIC *(Underground Injection of Fluids)*	**E. OTHER *(specify)***
9 U	9 (specify)
C. RCRA *(Hazardous Wastes)*	**E. OTHER *(specify)***
9 R	9 (specify)

XI. MAP

Attach to this application a topographic map of the area extending to at least one mile beyond property boundaries. The map must show the outline of the facility, the location of each of its existing and proposed intake and discharge structures, each of its hazardous waste treatment, storage, or disposal facilities, and each well where it injects fluids underground. Include all springs, rivers, and other surface water bodies in the map area. See instructions for precise requirements.

XII. NATURE OF BUSINESS *(provide a brief description)*

XIII. CERTIFICATION *(see instructions)*

I certify under penalty of law that I have personally examined and am familiar with the information submitted in this application and all attachments and that, based on my inquiry of those persons immediately responsible for obtaining the information contained in the application, I believe that the information is true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment.

A. NAME & OFFICIAL TITLE *(type or print)*	B. SIGNATURE	C. DATE SIGNED
JOHNNY L. SMITH, MAYOR/Superintendent	Johnny L. Smith	11/23/15

COMMENTS FOR OFFICIAL USE ONLY

FACILITY NAME AND PERMIT NUMBER:
JACKSONVILLE WATERWORKS, GAS AND SEWER BOARD

Form Approved 1/14/99
OMB Number 2040-0086

FORM 2A NPDES

NPDES FORM 2A APPLICATION OVERVIEW

APPLICATION OVERVIEW

Form 2A has been developed in a modular format and consists of a "Basic Application Information" packet and a "Supplemental Application Information" packet. The Basic Application Information packet is divided into two parts. All applicants must complete Parts A and C. Applicants with a design flow greater than or equal to 0.1 mgd must also complete Part B. Some applicants must also complete the Supplemental Application Information packet. The following items explain which parts of Form 2A you must complete.

BASIC APPLICATION INFORMATION:

A. **Basic Application Information for all Applicants.** All applicants must complete questions A.1 through A.8. A treatment works that discharges effluent to surface waters of the United States must also answer questions A.9 through A.12.

B. **Additional Application Information for Applicants with a Design Flow ≥ 0.1 mgd.** All treatment works that have design flows greater than or equal to 0.1 million gallons per day must complete questions B.1 through B.6.

C. **Certification.** All applicants must complete Part C (Certification).

SUPPLEMENTAL APPLICATION INFORMATION:

D. **Expanded Effluent Testing Data.** A treatment works that discharges effluent to surface waters of the United States and meets one or more of the following criteria must complete Part D (Expanded Effluent Testing Data):

1. Has a design flow rate greater than or equal to 1 mgd,
2. Is required to have a pretreatment program (or has one in place), or
3. Is otherwise required by the permitting authority to provide the information.

E. **Toxicity Testing Data.** A treatment works that meets one or more of the following criteria must complete Part E (Toxicity Testing Data):

1. Has a design flow rate greater than or equal to 1 mgd,
2. Is required to have a pretreatment program (or has one in place), or
3. Is otherwise required by the permitting authority to submit results of toxicity testing.

F. **Industrial User Discharges and RCRA/CERCLA Wastes.** A treatment works that accepts process wastewater from any significant industrial users (SIUs) or receives RCRA or CERCLA wastes must complete Part F (Industrial User Discharges and RCRA/CERCLA Wastes). SIUs are defined as:

1. All industrial users subject to Categorical Pretreatment Standards under 40 Code of Federal Regulations (CFR) 403.6 and 40 CFR Chapter I, Subchapter N (see instructions); and
2. Any other industrial user that:
   a. Discharges an average of 25,000 gallons per day or more of process wastewater to the treatment works (with certain exclusions); or
   b. Contributes a process wastestream that makes up 5 percent or more of the average dry weather hydraulic or organic capacity of the treatment plant; or
   c. Is designated as an SIU by the control authority.

G. **Combined Sewer Systems.** A treatment works that has a combined sewer system must complete Part G (Combined Sewer Systems).

ALL APPLICANTS MUST COMPLETE PART C (CERTIFICATION)

FACILITY NAME AND PERMIT NUMBER:
JACKSONVILLE WATERWORKS, GAS AND SEWER BOARD

Form Approved 1/14/99
OMB Number 2040-0086

BASIC APPLICATION INFORMATION

PART A. BASIC APPLICATION INFORMATION FOR ALL APPLICANTS:

All treatment works must complete questions A.1 through A.8 of this Basic Application Information packet.

A.1. Facility Information.

Facility name: JACKSONVILLE WASTEWATER TREATMENT PLANT

Mailing Address: 330 CHURCH AVENUE SE
JACKSONVILLE, ALABAMA 36265

Contact person: JOHNNY L. SMITH

Title: MAYOR

Telephone number: (256) 435-7611

Facility Address (not P.O. Box): 655 Nisbet NW
JACKSONVILLE ALABAMA 36265

A.2. Applicant Information. If the applicant is different from the above, provide the following:

Applicant name: JACKSONVILLE WATER WORKS, GAS AND SEWER BOARD

Mailing Address: 330 CHURCH AVENUE
JACKSONVILLE, ALABAMA 36265

Contact person: JOHNNY L. SMITH

Title: MAYOR/SUPERINTENDENT

Telephone number: (256) 435-7611

Is the applicant the owner or operator (or both) of the treatment works?

✓ owner ✓ operator

Indicate whether correspondence regarding this permit should be directed to the facility or the applicant.

____ facility ____ applicant

A.3. Existing Environmental Permits. Provide the permit number of any existing environmental permits that have been issued to the treatment works (include state-issued permits).

NPDES AL0022586 PSD ____

UIC ____ Other ____

RCRA ____ Other ____

A.4. Collection System Information. Provide information on municipalities and areas served by the facility. Provide the name and population of each entity and, if known, provide information on the type of collection system (combined vs. separate) and its ownership (municipal, private, etc.).

Name	Population Served	Type of Collection System	Ownership
CITY OF JACKSONVILLE	11,000	SEPARATE	MUNICIPAL

Total population served ____

RECEIVED
JAN 22 2016
IND / MUN BRANCH

A.5. Indian Country.

a. Is the treatment works located in Indian Country?

_____ Yes ✓ No

b. Does the treatment works discharge to a receiving water that is either in Indian Country or that is upstream from (and eventually flows through) Indian Country?

_____ Yes ✓ No

A.6. Flow. Indicate the design flow rate of the treatment plant (i.e., the wastewater flow rate that the plant was built to handle). Also provide the average daily flow rate and maximum daily flow rate for each of the last three years. Each year's data must be based on a 12-month time period with the 12th month of "this year" occurring no more than three months prior to this application submittal.

a. Design flow rate 3.5 mgd

	Two Years Ago	Last Year	This Year	
b. Annual average daily flow rate	1.313	2.259	1.902	mgd
c. Maximum daily flow rate	1.901	3.439	2.874	mgd

A.7. Collection System. Indicate the type(s) of collection system(s) used by the treatment plant. Check all that apply. Also estimate the percent contribution (by miles) of each.

✓ Separate sanitary sewer	100 %
_____ Combined storm and sanitary sewer	0 %

A.8. Discharges and Other Disposal Methods.

a. Does the treatment works discharge effluent to waters of the U.S.? ✓ Yes _____ No

If yes, list how many of each of the following types of discharge points the treatment works uses:

i. Discharges of treated effluent	1
ii. Discharges of untreated or partially treated effluent	0
iii. Combined sewer overflow points	0
iv. Constructed emergency overflows (prior to the headworks)	0
v. Other _____	0

b. Does the treatment works discharge effluent to basins, ponds, or other surface impoundments that do not have outlets for discharge to waters of the U.S.? _____ Yes ✓ No

If yes, provide the following for each surface impoundment:

Location: _____

Annual average daily volume discharged to surface impoundment(s) 0 mgd

Is discharge _____ continuous or _____ intermittent?

c. Does the treatment works land-apply treated wastewater? _____ Yes ✓ No

If yes, provide the following for each land application site:

Location: _____

Number of acres: _____

Annual average daily volume applied to site: _____ Mgd

Is land application _____ continuous or _____ intermittent?

d. Does the treatment works discharge or transport treated or untreated wastewater to another treatment works? _____ Yes ✓ No

If yes, describe the mean(s) by which the wastewater from the treatment works is discharged or transported to the other treatment works (e.g., tank truck, pipe).

If transport is by a party other than the applicant, provide:

Transporter name: _____

Mailing Address: _____

_____

Contact person: _____

Title: _____

Telephone number: _____

For each treatment works that receives this discharge, provide the following:

Name: _____

Mailing Address: _____

_____

Contact person: _____

Title: _____

Telephone number: _____

If known, provide the NPDES permit number of the treatment works that receives this discharge. _____

Provide the average daily flow rate from the treatment works into the receiving facility. _____ mgd

e. Does the treatment works discharge or dispose of its wastewater in a manner not included in A.8.a through A.8.d above (e.g., underground percolation, well injection)? _____ Yes ✔ No

If yes, provide the following for each disposal method:

Description of method (including location and size of site(s) if applicable):

_____

Annual daily volume disposed of by this method: _____

Is disposal through this method _____ continuous or _____ intermittent?

FACILITY NAME AND PERMIT NUMBER:
JACKSONVILLE WATERWORKS, GAS AND SEWER BOARD

Form Approved 1/14/99
OMB Number 2040-0086

WASTEWATER DISCHARGES:

If you answered "yes" to question A.8.a, complete questions A.9 through A.12 **once for each outfall** (including bypass points) through which effluent is discharged. Do not include information on combined sewer overflows in this section. **If you answered "no" to question A.8.a**, go to Part B, "Additional Application Information for Applicants with a Design Flow Greater than or Equal to 0.1 mgd."

A.9. Description of Outfall.

a. Outfall number 001

b. Location

JACKSONVILLE (City or town, if applicable)	36265 (Zip Code)
CALHOUN (County)	ALABAMA (State)
33 deg.49'28" (Latitude)	85 deg. 46'58" (Longitude)

c. Distance from shore (if applicable) N/A ft.

d. Depth below surface (if applicable) N/A ft.

e. Average daily flow rate 1.902 mgd

f. Does this outfall have either an intermittent or a periodic discharge? ____ Yes ✓ No (go to A.9.g.)

If yes, provide the following information:

Number of times per year discharge occurs: ____

Average duration of each discharge: ____

Average flow per discharge: ____ mgd

Months in which discharge occurs: ____

g. Is outfall equipped with a diffuser? ____ Yes ✓ No

A.10. Description of Receiving Waters.

a. Name of receiving water UT Tallasseehatchee Creek (0011, 0015)

b. Name of watershed (if known) Coosa River Watershed (Tallapoosa Basin)

United States Soil Conservation Service 14-digit watershed code (if known): 031501060402

c. Name of State Management/River Basin (if known): ____

United States Geological Survey 8-digit hydrologic cataloging unit code (if known): 03150107

d. Critical low flow of receiving stream (if applicable):
acute ____ cfs chronic ____ cfs

e. Total hardness of receiving stream at critical low flow (if applicable): ____ mg/l of $CaCO_3$

FACILITY NAME AND PERMIT NUMBER:
JACKSONVILLE WATERWORKS, GAS AND SEWER BOARD

Form Approved 1/14/99
OMB Number 2040-0086

A.11. Description of Treatment.

a. What levels of treatment are provided? Check all that apply.

✓ Primary ✓ Secondary

____ Advanced ____ Other. Describe: ____

b. Indicate the following removal rates (as applicable):

Design BOD_5 removal or Design $CBOD_5$ removal	85	%
Design SS removal	85	%
Design P removal		%
Design N removal		%
Other ____		%

c. What type of disinfection is used for the effluent from this outfall? If disinfection varies by season, please describe.

Ultraviolet

If disinfection is by chlorination, is dechlorination used for this outfall? ____ Yes ____ No

d. Does the treatment plant have post aeration? ✓ Yes ____ No

A.12. Effluent Testing Information. All Applicants that discharge to waters of the US must provide effluent testing data for the following parameters. Provide the indicated effluent testing required by the permitting authority for each outfall through which effluent is discharged. Do not include information on combined sewer overflows in this section. All information reported must be based on data collected through analysis conducted using 40 CFR Part 136 methods. In addition, this data must comply with QA/QC requirements of 40 CFR Part 136 and other appropriate QA/QC requirements for standard methods for analytes not addressed by 40 CFR Part 136. At a minimum, effluent testing data must be based on at least three samples and must be no more than four and one-half years apart.

Outfall number: DSN 001

PARAMETER	MAXIMUM DAILY VALUE		AVERAGE DAILY VALUE		
	Value	Units	Value	Units	Number of Samples
pH (Minimum)	6.9	s.u.			
pH (Maximum)	7.8	s.u.			
Flow Rate	2.87	MGD	1.902	MGD	
Temperature (Winter)	74 DEGREES	DEGREES F.			
Temperature (Summer)	82 DEGREES	DEGREES F.			

* For pH please report a minimum and a maximum daily value

POLLUTANT		MAXIMUM DAILY DISCHARGE		AVERAGE DAILY DISCHARGE			ANALYTICAL METHOD	ML / MDL
		Conc.	Units	Conc.	Units	Number of Samples		
CONVENTIONAL AND NONCONVENTIONAL COMPOUNDS.								
BIOCHEMICAL OXYGEN	BOD-5							
DEMAND (Report one)	CBOD-5	115	mg/l	4.7	mg/l			
FECAL COLIFORM		188	COUNT	15.6	COUNT			
TOTAL SUSPENDED SOLIDS (TSS)		9.5	mg/l	6.1	mg/l			

END OF PART A.
REFER TO THE APPLICATION OVERVIEW TO DETERMINE WHICH OTHER PARTS OF FORM 2A YOU MUST COMPLETE

BASIC APPLICATION INFORMATION

PART B. ADDITIONAL APPLICATION INFORMATION FOR APPLICANTS WITH A DESIGN FLOW GREATER THAN OR EQUAL TO 0.1 MGD (100,000 gallons per day).

All applicants with a design flow rate ≥ 0.1 mgd must answer questions B.1 through B.6. All others go to Part C (Certification).

B.1. Inflow and Infiltration. Estimate the average number of gallons per day that flow into the treatment works from inflow and/or infiltration.

250,000 gpd

Briefly explain any steps underway or planned to minimize inflow and infiltration.

PLANT UPGRADE IN PROGRESS.

B.2. Topographic Map. Attach to this application a topographic map of the area extending at least one mile beyond facility property boundaries. This map must show the outline of the facility and the following information. (You may submit more than one map if one map does not show the entire area.)

a. The area surrounding the treatment plant, including all unit processes.

b. The major pipes or other structures through which wastewater enters the treatment works and the pipes or other structures through which treated wastewater is discharged from the treatment plant. Include outfalls from bypass piping, if applicable.

c. Each well where wastewater from the treatment plant is injected underground.

d. Wells, springs, other surface water bodies, and drinking water wells that are: 1) within 1/4 mile of the property boundaries of the treatment works, and 2) listed in public record or otherwise known to the applicant.

e. Any areas where the sewage sludge produced by the treatment works is stored, treated, or disposed.

f. If the treatment works receives waste that is classified as hazardous under the Resource Conservation and Recovery Act (RCRA) by truck, rail, or special pipe, show on the map where that hazardous waste enters the treatment works and where it is treated, stored, and/or disposed.

B.3. Process Flow Diagram or Schematic. Provide a diagram showing the processes of the treatment plant, including all bypass piping and all backup power sources or redundancy in the system. Also provide a water balance showing all treatment units, including disinfection (e.g, chlorination and dechlorination). The water balance must show daily average flow rates at influent and discharge points and approximate daily flow rates between treatment units. Include a brief narrative description of the diagram.

B.4. Operation/Maintenance Performed by Contractor(s).

Are any operational or maintenance aspects (related to wastewater treatment and effluent quality) of the treatment works the responsibility of a contractor? ____Yes ✔ No

If yes, list the name, address, telephone number, and status of each contractor and describe the contractor's responsibilities (attach additional pages if necessary).

Name: _____

Mailing Address: _____

_____

Telephone Number: _____

Responsibilities of Contractor: _____

B.5. Scheduled Improvements and Schedules of Implementation. Provide information on any uncompleted implementation schedule or uncompleted plans for improvements that will affect the wastewater treatment, effluent quality, or design capacity of the treatment works. If the treatment works has several different implementation schedules or is planning several improvements, submit separate responses to question B.5 for each. (If none, go to question B.6.)

a. List the outfall number (assigned in question A.9) for each outfall that is covered by this implementation schedule.

N/A

b. Indicate whether the planned improvements or implementation schedule are required by local, State, or Federal agencies.

____Yes ✔ No

c If the answer to B.5.b is "Yes," briefly describe, including new maximum daily inflow rate (if applicable).

N/A

d. Provide dates imposed by any compliance schedule or any actual dates of completion for the implementation steps listed below, as applicable. For improvements planned independently of local, State, or Federal agencies, indicate planned or actual completion dates, as applicable. Indicate dates as accurately as possible.

Implementation Stage	Schedule MM / DD / YYYY	Actual Completion MM / DD / YYYY
– Begin construction	___/___/_____	___/___/_____
– End construction	___/___/_____	___/___/_____
– Begin discharge	___/___/_____	___/___/_____
– Attain operational level	___/___/_____	___/___/_____

e. Have appropriate permits/clearances concerning other Federal/State requirements been obtained? ____Yes ____No

Describe briefly: _____

_____

B.6. EFFLUENT TESTING DATA (GREATER THAN O.1 MGD ONLY).

Applicants that discharge to waters of the US must provide effluent testing data for the following parameters. Provide the indicated effluent testing required by the permitting authority for each outfall through which effluent is discharged. Do not include information on combined sewer overflows in this section. All information reported must be based on data collected through analysis conducted using 40 CFR Part 136 methods. In addition, this data must comply with QA/QC requirements of 40 CFR Part 136 and other appropriate QA/QC requirements for standard methods for analytes not addressed by 40 CFR Part 136. At a minimum, effluent testing data must be based on at least three pollutant scans and must be no more than four and one-half years old.

Outfall Number: DSN 001

POLLUTANT	MAXIMUM DAILY DISCHARGE		AVERAGE DAILY DISCHARGE			ANALYTICAL METHOD	ML / MDL
	Conc.	Units	Conc.	Units	Number of Samples		
CONVENTIONAL AND NONCONVENTIONAL COMPOUNDS.							
AMMONIA (as N)	0.7	MG/L	0.21	MG/L	3XWK		
CHLORINE (TOTAL RESIDUAL, TRC)	N/A	MG/L	N/A				
DISSOLVED OXYGEN	8.69	MG/L	8.69	MG/L	3XWK		
TOTAL KJELDAHL NITROGEN (TKN)	*B	MG/L	*B	MG/L	MO		
NITRATE PLUS NITRITE NITROGEN	4.13	MG/L	4.13	MG/L	MO		
OIL and GREASE	NOT REQ'D						
PHOSPHORUS (Total)	2.41	MG/L	2.41	MG/L	MO		
TOTAL DISSOLVED SOLIDS (TDS)		MG/L		MG/L	MO		
OTHER							

END OF PART B.
REFER TO THE APPLICATION OVERVIEW TO DETERMINE WHICH OTHER PARTS OF FORM 2A YOU MUST COMPLETE

FACILITY NAME AND PERMIT NUMBER:
JACKSONVILLE WATERWORKS, GAS AND SEWER BOARD

Form Approved 1/14/99
OMB Number 2040-0086

BASIC APPLICATION INFORMATION

PART C. CERTIFICATION

All applicants must complete the Certification Section. Refer to instructions to determine who is an officer for the purposes of this certification. All applicants must complete all applicable sections of Form 2A, as explained in the Application Overview. Indicate below which parts of Form 2A you have completed and are submitting. By signing this certification statement, applicants confirm that they have reviewed Form 2A and have completed all sections that apply to the facility for which this application is submitted.

Indicate which parts of Form 2A you have completed and are submitting:

✔ Basic Application Information packet

Supplemental Application Information packet:

✔ Part D (Expanded Effluent Testing Data)

✔ Part E (Toxicity Testing: Biomonitoring Data)

✔ Part F (Industrial User Discharges and RCRA/CERCLA Wastes)

____ Part G (Combined Sewer Systems)

ALL APPLICANTS MUST COMPLETE THE FOLLOWING CERTIFICATION.

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system or those persons directly responsible for gathering the information, the information is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

Name and official title: JOHNNY L. SMITH, MAYOR/SUPERINTENDENT

Signature: Johnny L Smith

Telephone number: (256) 435-7611

Date signed: 1/19/16

Upon request of the permitting authority, you must submit any other information necessary to assess wastewater treatment practices at the treatment works or identify appropriate permitting requirements.

SEND COMPLETED FORMS TO:

FACILITY NAME AND PERMIT NUMBER:
JACKSONVILLE WATERWORKS, GAS AND SEWER BOARD

Form Approved 1/14/99
OMB Number 2040-0086

SUPPLEMENTAL APPLICATION INFORMATION

PART D. EXPANDED EFFLUENT TESTING DATA

Refer to the directions on the cover page to determine whether this section applies to the treatment works.

Effluent Testing: 1.0 mgd and Pretreatment Treatment Works. If the treatment works has a design flow greater than or equal to 1.0 mgd or it has (or is required to have) a pretreatment program, or is otherwise required by the permitting authority to provide the data, then provide effluent testing data for the following pollutants. Provide the indicated effluent testing information and any other information required by the permitting authority for each outfall through which effluent is discharged. Do not include information on combined sewer overflows in this section. All information reported must be based on data collected through analyses conducted using 40 CFR Part 136 methods. In addition, these data must comply with QA/QC requirements of 40 CFR Part 136 and other appropriate QA/QC requirements for standard methods for analytes not addressed by 40 CFR Part 136. Indicate in the blank rows provided below any data you may have on pollutants not specifically listed in this form. At a minimum, effluent testing data must be based on at least three pollutant scans and must be no more than four and one-half years old.

Outfall number: 001 (Complete once for each outfall discharging effluent to waters of the United States.)

POLLUTANT	MAXIMUM DAILY DISCHARGE				AVERAGE DAILY DISCHARGE					ANALYTICAL METHOD	ML/ MDL
	Conc.	Units	Mass	Units	Conc.	Units	Mass	Units	Number of Samples		
METALS (TOTAL RECOVERABLE), CYANIDE, PHENOLS, AND HARDNESS.											
ANTIMONY	<0.002	mg/l	<0.01	lb/d	<0.005	mg/l	<0.01	lbs/d	3	200.8	0.005 mg/l
ARSENIC	0.022	mg/l	0.002	lb/d	<0.005	mg/l	<0.02	lbs/d	3	200.8	0.010 mg/l
BERYLLIUM	<0.001	mg/l	<0.002	lb/d	<0.001	mg/l	<0.02	lbs/d	3	200.8	0.001 mg/l
CADMIUM	<0.020	mg/l	<0.002	lb/d	<0.001	mg/l	<0.02	lbs/d	3	200.8	0.001 mg/l
CHROMIUM	<0.028	mg/l	<0.10	lb/d	<0.02	mg/l	<0.10	lbs/d	3	200.8	0.050 mg/l
COPPER	<0.009	mg/l	<0.12	lb/d	<0.02	mg/l	<0.12	lbs/d	3	200.8	0.050 mg/l
LEAD	<0.001	mg/l	<0.01	lb/d	<0.001	mg/l	<0.01	lbs/d	3	200.9	0.005 mg/l
MERCURY	<0.001	mg/l	<0.03	lb/d	<0.001	mg/l	<0.01	lbs/d	3	245.2	µg/l
NICKEL	<0.001	mg/l	<0.10	lb/d	<0.001	mg/l	<0.10	lbs/d	3	200.8	0.005 mg/l
SELENIUM	<0.001	mg/l	<0.12	lb/d	<0.001	mg/l	<0.02	lbs/d	3	200.8	0.050 mg/l
SILVER	<0.001	mg/l	<0.10	lb/d	<0.001	mg/l	<0.10	lbs/d	3	200.8	0.001 mg/l
THALLIUM	<0.001	mg/l	<0.002	lb/d	<0.001	mg/l	<0.002	lbs/d	3	200.8	0.050 mg/l
ZINC	0.19	mg/l	0.10	lb/d	0.088	mg/l	0.10	lbs/d	3	200.7	0.010 mg/l
CYANIDE	<0.02	mg/l	<0.03	lb/d	<0.02	mg/l	<0.03	lbs/d	3	335.4	0.010 mg/l
TOTAL PHENOLIC COMPOUNDS	<0.04	mg/l	<0.02	lb/d	<0.04	mg/l	<0.02	lbs/d	3	420.1	0.010mg/l
HARDNESS (AS $CaCO_3$)	166	mg/l	145	lb/d	162	mg/l	122	lbs/d	3	314A	1.00 mg/l
Use this space (or a separate sheet) to provide information on other metals requested by the permit writer.											

FACILITY NAME AND PERMIT NUMBER:
JACKSONVILLE WATERWORKS, GAS AND SEWER BOARD

Form Approved 1/14/99
OMB Number 2040-0086

Outfall number: 001 (Complete once for each outfall discharging effluent to waters of the United States.) JA14059ADEM3510-2A 11-14

POLLUTANT	MAXIMUM DAILY DISCHARGE				AVERAGE DAILY DISCHARGE					ANALYTICAL METHOD	ML/ MDL
	Conc.	Units	Mass	Units	Conc.	Units	Mass	Units	Number of Samples		
VOLATILE ORGANIC COMPOUNDS.											
ACROLEIN	<20.0.	µg/l	N/A	lb/day	<50.0	µg/l	N/A	lb/d	3	624	<20.0 µg/l
ACRYLONITRILE	<20.0	µg/l	N/A	lb/day	<50.0	µg/l	N/A	lb/d	3	624	<20.0 µg/l
BENZENE	<2.0	µg/l	N/A	lb/day	<5.0	µg/l	N/A	lb/d	3	624	<2.0 µg/l
BROMOFORM	<2.0	µg/l	N/A	lb/day	<5.0	µg/l	N/A	lb/d	3	624	<2.0 µg/l
CARBON TETRACHLORIDE	<2.0	µg/l	N/A	lb/day	<5.0	µg/l	N/A	lb/d	3	624	<2.0 µg/l
CLOROBENZENE	<2.0	µg/l	N/A	lb/day	<5.0	µg/l	N/A	lb/d	3	624	<2.0 µg/l
CHLORODIBROMO-METHANE	<2.0	µg/l	N/A	lb/day	<5.0	µg/l	N/A	lb/d	3	624	<2.0 µg/l
CHLOROETHANE	<2.0	µg/l	N/A	lb/day	<5.0	µg/l	N/A	lb/d	3	624	<2.0 µg/l
2-CHLORO-ETHYLVINYL ETHER	<20.0	µg/l	N/A	lb/day	<50.0	µg/l	N/A	lb/d	3	624	<20.0 µg/l
CHLOROFORM	<2.0	µg/l	N/A	lb/day	<5.0	µg/l	N/A	lb/d	3	624	<2.0 µg/l
DICHLOROBROMO-METHANE	<2.0	µg/l	N/A	lb/day	<5.0	µg/l	N/A	lb/d	3	624	<2.0 µg/l
1,1-DICHLOROETHANE	<2.0	µg/l	N/A	lb/day	<5.0	µg/l	N/A	lb/d	3	624	<2.0 µg/l
1,2-DICHLOROETHANE	<2.0	µg/l	N/A	lb/day	<5.0	µg/l	N/A	lb/d	3	624	<2.0 µg/l
TRANS-1,2-DICHLORO-ETHYLENE	<2.0	µg/l	N/A	lb/day	<5.0	µg/l	N/A	lb/d	3	624	<2.0 µg/l
1,1-DICHLOROETHYLENE	<2.0	µg/l	N/A	lb/day	<5.0	µg/l	N/A	lb/d	3	624	<2.0 µg/l
1,2-DICHLOROPROPANE	<2.0	µg/l	N/A	lb/day	<5.0	µg/l	N/A	lb/d	3	624	<2.0 µg/l
1,3-DICHLORO-PROPYLENE	<2.0	µg/l	N/A	lb/day	<5.0	µg/l	N/A	lb/d	3	624	<2.0 µg/l
ETHYLBENZENE	<2.0	µg/l	N/A	lb/day	<5.0	µg/l	N/A	lb/d	3	624	<2.0 µg/l
METHYL BROMIDE	<2.0	µg/l	N/A	lb/day	<5.0	µg/l	N/A	lb/d	3	624	<2.0 µg/l
METHYL CHLORIDE	<2.0	µg/l	N/A	lb/day	<5.0	µg/l	N/A	lb/d	3	624	<2.0 µg/l
METHYLENE CHLORIDE	<2.0	µg/l	N/A	lb/day	<5.0	µg/l	N/A	lb/d	3	624	<2.0 µg/l
1,1,2,2-TETRACHLORO-ETHANE	<2.0	µg/l	N/A	lb/day	<5.0	µg/l	N/A	lb/d	3	624	<2.0 µg/l
TETRACHLORO-ETHYLENE	<2.0	µg/l	N/A	lb/day	<5.0	µg/l	N/A	lb/d	3	624	<2.0 µg/l
TOLUENE	<2.0	µg/l	N/A	lb/day	<5.0	µg/l	N/A	lb/d	3	624	<2.0 µg/l

FACILITY NAME AND PERMIT NUMBER:
JACKSONVILLE WATERWORKS, GAS AND SEWER BOARD

Form Approved 1/14/99
OMB Number 2040-0086

Outfall number: 001 (Complete once for each outfall discharging effluent to waters of the United States.)

POLLUTANT	MAXIMUM DAILY DISCHARGE				AVERAGE DAILY DISCHARGE					ANALYTICAL METHOD	ML/ MDL
	Conc.	Units	Mass	Units	Conc.	Units	Mass	Units	Number of Samples		
1,1,1-TRICHLOROETHANE	<2.0	µg/l	N/A	lb/d	<2.0	µg/l	N/A	lb/d	3	624	<2.0 ug/l
1,1,2-TRICHLOROETHANE	<2.0	µg/l	N/A	lb/d	<2.0	µg/l	N/A	lb/d	3	624	<2.0 ug/l
TRICHLORETHYLENE	<2.0	µg/l	N/A	lb/d	<2.0	µg/l	N/A	lb/d	3	624	<2.0 ug/l
VINYL CHLORIDE	<2.0	µg/l	N/A	lb/d	<2.0	µg/l	N/A	lb/d	3	624	<2.0 ug/l
Use this space (or a separate sheet) to provide information on other volatile organic compounds requested by the permit writer.											
ACID-EXTRACTABLE COMPOUNDS											
P-CHLORO-M-CRESOL	<5.0	µg/l	<0.02	lb/d	<5.0	µg/l	<0.02	lb/d	3	625	<5.0 µg/l
2-CHLOROPHENOL	<5.0	µg/l	<0.02	lb/d	<5.0	µg/l	<0.02	lb/d	3	625	<5.0 µg/l
2,4-DICHLOROPHENOL	<5.0	µg/l	<0.02	lb/d	<5.0	µg/l	<0.02	lb/d	3	625	<5.0 µg/l
2,4-DIMETHYLPHENOL	<5.0	µg/l	<0.02	lb/d	<5.0	µg/l	<0.02	lb/d	3	625	<5.0 µg/l
4,6-DINITRO-O-CRESOL	<5.0	µg/l	<0.10	lb/d	<5.0	µg/l	<0.10	lb/d	3	625	<5.0 µg/l
2,4-DINITROPHENOL	<5.0	µg/l	<0.10	lb/d	<5.0	µg/l	<0.10	lb/d	3	625	<5.0 µg/l
2-NITROPHENOL	<5.0	µg/l	<0.02	lb/d	<5.0	µg/l	<0.02	lb/d	3	625	<5.0 µg/l
4-NITROPHENOL	<5.0	µg/l	<0.10	lb/d	<5.0	µg/l	<0.10	lb/d	3	625	<5.0 µg/l
PENTACHLOROPHENOL	<5.0	µg/l	<0.05	lb/d	<5.0	µg/l	<0.05	lb/d	3	625	<5.0 µg/l
PHENOL	<5.0	µg/l	<0.02	lb/d	<5.0	µg/l	<0.02	lb/d	3	625	<5.0 µg/l
2,4,6-TRICHLOROPHENOL	<5.0	µg/l	<0.02	lb/d	<5.0	µg/l	<0.02	lb/d	3	625	<5.0 µg/l
Use this space (or a separate sheet) to provide information on other acid-extractable compounds requested by the permit writer.											
BASE-NEUTRAL COMPOUNDS.											
ACENAPHTHENE	<5.0	µg/l	<0.02	lb/d	<5.0	µg/l	<0.02	lb/d	3	625	<5.0 µg/l
ACENAPHTHYLENE	<5.0	µg/l	<0.02	lb/d	<5.0	µg/l	<0.02	lb/d	3	625	<5.0 µg/l
ANTHRACENE	<5.0	µg/l	<0.02	lb/d	<5.0	µg/l	<0.02	lb/d	3	625	<5.0 µg/l
BENZIDINE	<5.0	µg/l	<0.02	lb/d	<5.0	µg/l	<0.10	lb/d	3	625	<5.0 µg/l
BENZO(A)ANTHRACENE	<5.0	µg/l	<0.02	lb/d	<5.0	µg/l	<0.02	lb/d	3	625	<5.0 µg/l
BENZO(A)PYRENE	<5.0	µg/l	<0.02	lb/d	<5.0	µg/l	<0.02	lb/d	3	625	<5.0 µg/l

FACILITY NAME AND PERMIT NUMBER:
JACKSONVILLE WATERWORKS, GAS AND SEWER BOARD

Form Approved 1/14/99
OMB Number 2040-0086

Outfall number: 001 (Complete once for each outfall discharging effluent to waters of the United States.)

POLLUTANT	MAXIMUM DAILY DISCHARGE				AVERAGE DAILY DISCHARGE					ANALYTICAL METHOD	ML/ MDL
	Conc.	Units	Mass	Units	Conc.	Units	Mass	Units	Number of Samples		
3,4 BENZO-FLUORANTHENE	<5.0	µg/l	<0.08	lb/d	<5.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/l
BENZO(GHI)PERYLENE	<5.0	µg/l	<0.08	lb/d	<5.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/l
BENZO(K)FLUORANTHENE	<5.0	µg/l	<0.08	lb/d	<5.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/l
BIS (2-CHLOROETHOXY) METHANE	<5.0	µg/l	<0.08	lb/d	<5.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/l
BIS (2-CHLOROETHYL)-ETHER	<50.0	µg/l	<0.08	lb/d	<50.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/l
BIS (2-CHLOROISO-PROPYL) ETHER	<5.0	µg/l	<0.08	lb/d	<5.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/l
BIS (2-ETHYLHEXYL) PHTHALATE	<5.0	µg/l	<0.08	lb/d	<5.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/l
4-BROMOPHENYL PHENYL ETHER	<5.0	µg/l	<0.08	lb/d	<5.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/l
BUTYL BENZYL PHTHALATE	<5.0	µg/l	<0.08	lb/d	<5.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/l
2-CHLORONAPHTHALENE	<5.0	µg/l	<0.08	lb/d	<5.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/l
4-CHLORPHENYL PHENYL ETHER	<5.0	µg/l	<0.08	lb/d	<5.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/l
CHRYSENE	<5.0	µg/l	<0.08	lb/d	<5.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/l
DI-N-BUTYL PHTHALATE	<5.0	µg/l	<0.08	lb/d	<5.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/l
DI-N-OCTYL PHTHALATE	<5.0	µg/l	<0.08	lb/d	<5.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/l
DIBENZO(A,H) ANTHRACENE	<5.0	µg/l	<0.08	lb/d	<5.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/l
1,2-DICHLOROBENZENE	<5.0	µg/l	<0.08	lb/d	<5.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/l
1,3-DICHLOROBENZENE	<5.0	µg/l	<0.08	lb/d	<5.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/ll
1,4-DICHLOROBENZENE	<5.0	µg/l	<0.08	lb/d	<5.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/ll
3,3-DICHLOROBENZIDINE	<5.0	µg/l	<0.08	lb/d	<5.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/ll
DIETHYL PHTHALATE	<5.0	µg/l	<0.08	lb/d	<5.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/ll
DIMETHYL PHTHALATE	<5.0	µg/l	<0.08	lb/d	<5.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/ll
2,4-DINITROTOLUENE	<5.0	µg/l	<0.08	lb/d	<5.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/ll
2,6-DINITROTOLUENE	<5.0	µg/l	<0.08	lb/d	<5.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/ll
1,2-DIPHENYLHYDRAZINE	<5.0	µg/l	<0.08	lb/d	<5.0	µg/l	<0.08	lb/d	3	625	<5.0 µg/ll

FACILITY NAME AND PERMIT NUMBER:
JACKSONVILLE WATERWORKS, GAS AND SEWER BOARD

Form Approved 1/14/99
OMB Number 2040-0086

Outfall number: 001 (Complete once for each outfall discharging effluent to waters of the United States.)

POLLUTANT	MAXIMUM DAILY DISCHARGE				AVERAGE DAILY DISCHARGE					ANALYTICAL METHOD	ML/ MDL
	Conc.	Units	Mass	Units	Conc.	Units	Mass	Units	Number of Samples		
FLUORANTHENE	<5.0	µg/l	<0.06	lb/d	<5.0	µg/l	<.067	lb/d	3	625	<5.0 µg/l
FLUORENE	<5.0	µg/l	<.067	lb/d	<5.0	µg/l	<.067	lb/d	3	625	<5.0 µg/l
HEXACHLOROBENZENE	<5.0	µg/l	<.067	lb/d	<5.0	µg/l	<.067	lb/d	3	625	<5.0 µg/l
HEXACHLOROBUTADIENE	<5.0	µg/l	<.067	lb/d	<5.0	µg/l	<.067	lb/d	3	625	<5.0 µg/l
HEXACHLOROCYCLO-PENTADIENE	<5.0	µg/l	<.067	lb/d	<5.0	µg/l	<.067	lb/d	3	625	<5.0 µg/l
HEXACHLOROETHANE	<5.0	µg/l	<.067	lb/d	<5.0	µg/l	<.067	lb/d	3	625	<5.0 µg/l
INDENO(1,2,3-CD)PYRENE	<5.0	µg/l	<.067	lb/d	<5.0	µg/l	<.067	lb/d	3	625	<5.0 µg/l
ISOPHORONE	<5.0	µg/l	<.067	lb/d	<5.0	µg/l	<.067	lb/d	3	625	<5.0 µg/l
NAPHTHALENE	<5.0	µg/l	<.067	lb/d	<5.0	µg/l	<.067	lb/d	3	625	<5.0 µg/l
NITROBENZENE	<5.0	µg/l	<.067	lb/d	<5.0	µg/l	<.067	lb/d	3	625	<5.0 µg/l
N-NITROSODI-N-PROPYLAMINE	<5.0	µg/l	<.067	lb/d	<5.0	µg/l	<.067	lb/d	3	625	<5.0 µg/l
N-NITROSODI- METHYLAMINE	<5.0	µg/l	<.067	lb/d	<5.0	µg/l	<.067	lb/d	3	625	<5.0 µg/l
N-NITROSODI-PHENYLAMINE	<5.0	µg/l	<.067	lb/d	<5.0	µg/l	<.067	lb/d	3	625	<5.0 µg/l
PHENANTHRENE	<5.0	µg/l	<.067	lb/d	<5.0	µg/l	<.067	lb/d	3	625	<5.0 µg/l
PYRENE	<5.0	µg/l	<.067	lb/d	<5.0	µg/l	<.067	lb/d	3	625	<5.0 µg/l
1,2,4-TRICHLOROBENZENE	<5.0	µg/l	<.067	lb/d	<5.0	µg/l	<.067	lb/d	3	625	<5.0 µg/l

Use this space (or a separate sheet) to provide information on other base-neutral compounds requested by the permit writer.

Use this space (or a separate sheet) to provide information on other pollutants (e.g., pesticides) requested by the permit writer.

END OF PART D.
REFER TO THE APPLICATION OVERVIEW TO DETERMINE WHICH OTHER PARTS OF FORM 2A YOU MUST COMPLETE

SUPPLEMENTAL APPLICATION INFORMATION

PART E. TOXICITY TESTING DATA

POTWs meeting one or more of the following criteria must provide the results of whole effluent toxicity tests for acute or chronic toxicity for each of the facility's discharge points: 1) POTWs with a design flow rate greater than or equal to 1.0 mgd; 2) POTWs with a pretreatment program (or those that are required to have one under 40 CFR Part 403); or 3) POTWs required by the permitting authority to submit data for these parameters.

- At a minimum, these results must include quarterly testing for a 12-month period within the past 1 year using multiple species (minimum of two species), or the results from four tests performed at least annually in the four and one-half years prior to the application, provided the results show no appreciable toxicity, and testing for acute and/or chronic toxicity, depending on the range of receiving water dilution. Do not include information on combined sewer overflows in this section. All information reported must be based on data collected through analysis conducted using 40 CFR Part 136 methods. In addition, this data must comply with QA/QC requirements of 40 CFR Part 136 and other appropriate QA/QC requirements for standard methods for analytes not addressed by 40 CFR Part 136.
- In addition, submit the results of any other whole effluent toxicity tests from the past four and one-half years. If a whole effluent toxicity test conducted during the past four and one-half years revealed toxicity, provide any information on the cause of the toxicity or any results of a toxicity reduction evaluation, if one was conducted.
- If you have already submitted any of the information requested in Part E, you need not submit it again. Rather, provide the information requested in question E.4 for previously submitted information. If EPA methods were not used, report the reasons for using alternate methods. If test summaries are available that contain all of the information requested below, they may be submitted in place of Part E.

If no biomonitoring data is required, do not complete Part E. Refer to the Application Overview for directions on which other sections of the form to complete.

E.1. Required Tests.

Indicate the number of whole effluent toxicity tests conducted in the past four and one-half years.

✔ chronic ✔ acute

E.2. Individual Test Data. Complete the following chart for each whole effluent toxicity test conducted in the last four and one-half years. Allow one column per test (where each species constitutes a test). Copy this page if more than three tests are being reported.

	Test number: 1	Test number: 1	Test number:
a. Test information.			
Test species & test method number	PIMEPHALES PROMELAS	CERIODAPHNIA DUBIA	
Age at initiation of test	<24 HOURS	<24 HOURS	
Outfall number	DSN 001	DSN 001	
Dates sample collected	11/6-11/13/2012	11/6-11/13/2012	
Date test started	11/4/2012	11/4/2012	
Duration	7 DAYS	7 DAYS	
b. Give toxicity test methods followed.			
Manual title	CHRONIC TOX MANUAL	CHRONIC TOX MANUAL	
Edition number and year of publication	4TH EDITION, OCT 2002	4TH EDITION, OCT 2002	
Page number(s)			
c. Give the sample collection method(s) used. For multiple grab samples, indicate the number of grab samples used.			
24-Hour composite	AS PER NPDES PERMIT	AS PER NPDES PERMIT	
Grab			
d. Indicate where the sample was taken in relation to disinfection. (Check all that apply for each)			
Before disinfection			
After disinfection	X	X	
After dechlorination			

FACILITY NAME AND PERMIT NUMBER: JACKSONVILLE WATERWORKS, GAS AND SEWER BOARD			

Form Approved 1/14/99
OMB Number 2040-0086

	Test number: 1	Test number: 1	Test number:
e. Describe the point in the treatment process at which the sample was collected.			
Sample was collected:	Effluent	Effluent	
f. For each test, include whether the test was intended to assess chronic toxicity, acute toxicity, or both.			
Chronic toxicity	X	X	
Acute toxicity	X	X	
g. Provide the type of test performed.			
Static			
Static-renewal	X	X	
Flow-through			
h. Source of dilution water. If laboratory water, specify type; if receiving water, specify source.			
Laboratory water	MHSF	MHSF	
Receiving water			
i. Type of dilution water. It salt water, specify "natural" or type of artificial sea salts or brine used.			
Fresh water	X	X	
Salt water			
j. Give the percentage effluent used for all concentrations in the test series.			
	65%	65%	
k. Parameters measured during the test. (State whether parameter meets test method specifications)			
pH	7.54 - 7.90	7.69 - 8.03	
Salinity			
Temperature	24.1 - 25.0 DEG C	24.0 - 25.0 DEG C	
Ammonia	<0.1	<0.1	
Dissolved oxygen	6.0 -.8.9	7.9 - 9.0	
l. Test Results.			
Acute:			
Percent survival in 100% effluent	100 %	100 %	%
LC_{50}	2.05	7.45	
95% C.I.	2.29 %	2.81 %	%
Control percent survival	100 %	100 %	%
Other (describe)			

Chronic:			
NOEC	1.0 G/L %	3.0 G/L %	%
IC_{25}	70 %	70 %	%
Control percent survival	100 %	95 %	%
Other (describe)	LOEC 2.5 G/L	LOEC 1.56 G/L	

m. Quality Control/Quality Assurance.

Is reference toxicant data available?	YES	YES	
Was reference toxicant test within acceptable bounds?	YES	YES	
What date was reference toxicant test run (MM/DD/YYYY)?	11/20/2012	11/20/2012	
Other (describe)			

E.3. Toxicity Reduction Evaluation. Is the treatment works involved in a Toxicity Reduction Evaluation?

____Yes ✔ No If yes, describe: _____

_____

_____

E.4. Summary of Submitted Biomonitoring Test Information. If you have submitted biomonitoring test information, or information regarding the cause of toxicity, within the past four and one-half years, provide the dates the information was submitted to the permitting authority and a summary of the results.

Date submitted: _____ (MM/DD/YYYY)

Summary of results: (see instructions)

_____

_____

END OF PART E.
REFER TO THE APPLICATION OVERVIEW TO DETERMINE WHICH OTHER PARTS OF FORM 2A YOU MUST COMPLETE.

FACILITY NAME AND PERMIT NUMBER:
JACKSONVILLE WATERWORKS, GAS AND SEWER BOARD

Form Approved 1/14/99
OMB Number 2040-0086

SUPPLEMENTAL APPLICATION INFORMATION

PART F. INDUSTRIAL USER DISCHARGES AND RCRA/CERCLA WASTES

All treatment works receiving discharges from significant industrial users or which receive RCRA, CERCLA, or other remedial wastes must complete Part F.

GENERAL INFORMATION:

F.1. Pretreatment Program. Does the treatment works have, or is it subject to, an approved pretreatment program?

____Yes ✔ No

F.2. Number of Significant Industrial Users (SIUs) and Categorical Industrial Users (CIUs). Provide the number of each of the following types of industrial users that discharge to the treatment works.

a. Number of non-categorical SIUs. 1

b. Number of CIUs. NONE

SIGNIFICANT INDUSTRIAL USER INFORMATION:

Supply the following information for each SIU. If more than one SIU discharges to the treatment works, copy questions F.3 through F.8 and provide the information requested for each SIU.

F.3. Significant Industrial User Information. Provide the name and address of each SIU discharging to the treatment works. Submit additional pages as necessary.

Name: PARKER HANNIFIN CORPORATION

Mailing Address: 2651 ALABAMA HIGHWAY 21 NORTH
JACKSONVILLE, ALABAMA 36265

F.4. Industrial Processes. Describe all of the industrial processes that affect or contribute to the SIU's discharge.

F.5. Principal Product(s) and Raw Material(s). Describe all of the principal processes and raw materials that affect or contribute to the SIU's discharge.

Principal product(s): INSTRUMENTATION

Raw material(s):

F.6. Flow Rate.

a. Process wastewater flow rate. Indicate the average daily volume of process wastewater discharged into the collection system in gallons per day (gpd) and whether the discharge is continuous or intermittent.

18,268 gpd (✔ continuous or ____ intermittent)

b. Non-process wastewater flow rate. Indicate the average daily volume of non-process wastewater flow discharged into the collection system in gallons per day (gpd) and whether the discharge is continuous or intermittent.

____ gpd (____ continuous or ____ intermittent)

F.7. Pretreatment Standards. Indicate whether the SIU is subject to the following:

a. Local limits ____Yes ✔ No

b. Categorical pretreatment standards ____Yes ✔ No

If subject to categorical pretreatment standards, which category and subcategory?

F.8. Problems at the Treatment Works Attributed to Waste Discharged by the SIU. Has the SIU caused or contributed to any problems (e.g., upsets, interference) at the treatment works in the past three years?

____Yes ✔ No If yes, describe each episode.

RCRA HAZARDOUS WASTE RECEIVED BY TRUCK, RAIL, OR DEDICATED PIPELINE:

F.9. RCRA Waste. Does the treatment works receive or has it in the past three years received RCRA hazardous waste by truck, rail, or dedicated pipe? ____Yes ___No (go to F.12.)

F.10. Waste Transport. Method by which RCRA waste is received (check all that apply):

_____Truck _____Rail _____Dedicated Pipe

F.11. Waste Description. Give EPA hazardous waste number and amount (volume or mass, specify units).

EPA Hazardous Waste Number	Amount	Units

CERCLA (SUPERFUND) WASTEWATER, RCRA REMEDIATION/CORRECTIVE ACTION WASTEWATER, AND OTHER REMEDIAL ACTIVITY WASTEWATER:

F.12. Remediation Waste. Does the treatment works currently (or has it been notified that it will) receive waste from remedial activities?

____Yes (complete F.13 through F.15.) ____No

Provide a list of sites and the requested information (F.13 - F.15.) for each current and future site.

F.13. Waste Origin. Describe the site and type of facility at which the CERCLA/RCRA/or other remedial waste originates (or is expected to originate in the next five years).

F.14. Pollutants. List the hazardous constituents that are received (or are expected to be received). Include data on volume and concentration, if known. (Attach additional sheets if necessary).

F.15. Waste Treatment.

a. Is this waste treated (or will it be treated) prior to entering the treatment works?

____Yes ____No

If yes, describe the treatment (provide information about the removal efficiency):

b. Is the discharge (or will the discharge be) continuous or intermittent?

____Continuous ____Intermittent If intermittent, describe discharge schedule.

END OF PART F.
REFER TO THE APPLICATION OVERVIEW TO DETERMINE WHICH OTHER PARTS OF FORM 2A YOU MUST COMPLETE

FACILITY NAME AND PERMIT NUMBER:
JACKSONVILLE WATERWORKS, GAS AND SEWER BOARD

Form Approved 1/14/99
OMB Number 2040-0086

SUPPLEMENTAL APPLICATION INFORMATION

PART G. COMBINED SEWER SYSTEMS

If the treatment works has a combined sewer system, complete Part G.

G.1. System Map. Provide a map indicating the following: (may be included with Basic Application Information)

a. All CSO discharge points.

b. Sensitive use areas potentially affected by CSOs (e.g., beaches, drinking water supplies, shellfish beds, sensitive aquatic ecosystems, and outstanding natural resource waters).

c. Waters that support threatened and endangered species potentially affected by CSOs.

G.2. System Diagram. Provide a diagram, either in the map provided in G.1. or on a separate drawing, of the combined sewer collection system that includes the following information:

a. Locations of major sewer trunk lines, both combined and separate sanitary.

b. Locations of points where separate sanitary sewers feed into the combined sewer system.

c. Locations of in-line and off-line storage structures.

d. Locations of flow-regulating devices.

e. Locations of pump stations.

CSO OUTFALLS:

Complete questions G.3 through G.6 once for each CSO discharge point.

G.3. Description of Outfall.

a. Outfall number _____

b. Location _____
(City or town, if applicable) (Zip Code)

_____
(County) (State)

_____
(Latitude) (Longitude)

c. Distance from shore (if applicable) _____ ft.

d. Depth below surface (if applicable) _____ ft.

e. Which of the following were monitored during the last year for this CSO?

____Rainfall ____CSO pollutant concentrations ____CSO frequency

____CSO flow volume ____Receiving water quality

f. How many storm events were monitored during the last year? _____

G.4. CSO Events.

a. Give the number of CSO events in the last year.

_____ events (___ actual or ___ approx.)

b. Give the average duration per CSO event.

_____ hours (____ actual or ____ approx.)

c. Give the average volume per CSO event.

_____ million gallons (_____ actual or _____ approx.)

d. Give the minimum rainfall that caused a CSO event in the last year.

_____ inches of rainfall

G.5. Description of Receiving Waters.

a. Name of receiving water: _____

b. Name of watershed/river/stream system: _____

United States Soil Conservation Service 14-digit watershed code (if known): _____

c. Name of State Management/River Basin: _____

United States Geological Survey 8-digit hydrologic cataloging unit code (if known): _____

G.6. CSO Operations.

Describe any known water quality impacts on the receiving water caused by this CSO (e.g., permanent or intermittent beach closings, permanent or intermittent shell fish bed closings, fish kills, fish advisories, other recreational loss, or violation of any applicable State water quality standard).

_____

_____

END OF PART G.
REFER TO THE APPLICATION OVERVIEW TO DETERMINE WHICH OTHER PARTS OF FORM 2A YOU MUST COMPLETE.

GUARDIAN SYSTEMS, INC.

1108 Ashville Road
P.O. Box 190
Leeds, Alabama 35094

Telephone (205) 699-6647
Toll Free (866) 729-7211
Fax (205) 699-3882

Jacksonville Utilities Board
655 Nesbit Street
Jacksonville, AL 36265-

Report Date: 05/12/2016
Receive Date: 04/27/2016
Receive Time: 11:20

Attention: Mr. Chris Patterson

Control No : 1604-00420 Sample # 001
Sampler : RM
Sample ID: Field Blank

Sample Date: 04/27/2016
Sample Time: 6:25

Laboratory Certificate

PARAMETER	RESULTS	UNITS	ANALYST	DATE	TIME	METHOD	REF
Arsenic, Trivalent	<0.008	ug/L	OS	05/03/2016	12:00	1632A	

This Certificate is Continued On Next Page.

METHOD REFERENCES

1. Methods for Chemical Analysis of Water and Wastes. EPA-600/4-79-20, revised March 1983, August 1993 May 1994
2. Standard Methods for the Examination of Water and Waste Water, 18th, 19th, 20th, and 22nd Edition, 2012
3. Test Methods for Evaluating Solid Wastes Physical Chemical Method SW-846, 3rd Edition, Updated IV December 1996
4. 1987 ASTM Annual Standards
5. Code of Federal Regulations, Title 40, Part 136, Appendix A, Revised July 1995
6. Methods for the Determination of Organic Compounds in Drinking Water, EPA-600/4-88/039, Revised July 1991, August 1995
7. NIOSH Manual of Anaytical Methods, 4th Edition, May 1996

GUARDIAN SYSTEMS, INC.

1108 Ashville Road
P.O. Box 190
Leeds, Alabama 35094

Telephone (205) 699-6647
Toll Free (866) 729-7211
Fax (205) 699-3882

Jacksonville Utilities Board
655 Nesbit Street
Jacksonville, AL 36265-

Report Date: 05/12/2016
Receive Date: 04/27/2016
Receive Time: 11:20

Attention: Mr. Chris Patterson

Control No : 1604-00420 Sample # 002
Sampler : RM
Sample ID: Effluent

Sample Date: 04/27/2016
Sample Time: 6:27

Laboratory Certificate

PARAMETER	RESULTS	UNITS	ANALYST	DATE	TIME	METHOD	REF
Arsenic, Trivalent	<0.008	ug/L	OS	05/03/2016	12:00	1632A	

Approved By:

TMB

METHOD REFERENCES

1. Methods for Chemical Analysis of Water and Wastes. EPA-600/4-79-20, revised March 1983, August 1993 May 1994
2. Standard Methods for the Examination of Water and Waste Water, 18th, 19th, 20th, and 22nd Edition, 2012
3. Test Methods for Evaluating Solid Wastes Physical Chemical Method SW-846, 3rd Edition, Updated IV December 1996
4. 1987 ASTM Annual Standards
5. Code of Federal Regulations, Title 40, Part 136, Appendix A, Revised July 1995
6. Methods for the Determination of Organic Compounds in Drinking Water, EPA-600/4-88/039, Revised July 1991, August 1995
7. NIOSH Manual of Anaytical Methods, 4th Edition, May 1996

Guardian Systems, Inc.
1108 Ashville Road, P.O. Box 190
Leeds, Alabama 35094
(205) 699-6647 (205) 699-3882 Fax
email: lbrymer@gsilab.com www.gsilab.com

Chain of Custody Record/ Analysis Report

Client: Chris Patterson	Phone: 256-435-9551
Company: City of Jacksonville	Fax: 256 782-0395
Address: 655 Nisbet St	P.O.#:
Address: Jacksonville Ala 36265	Email Address:
	Project:

Sample ID	Sample Description	Sample Date	Sample Time	Sample: Comp.*	Sample: Grab	Bottle: Glass	Bottle: Plastic	Preservative: HCl	Preservative: HNO_3	Preservative: H_2SO_4	Preservative: NaOH	Preservative: Cool 4°C	Preservative: Other**	Analysis Requested
1	Field Blank	4-27-16	6:25 Am				✓	✓				✓	✓	
2	Eff Grab	4-27-16	6:27 Am		✓		✓					✓		TRIVALENT ARSENIC

Sampled by: Roger Mills 4-27-16 6:27 Am Relinquished by: Roger Mills Date: 4-27-16 Time: 11:20 Am
Received by: Date: Time: Relinquished by: Date: Time:
Received by: Date: Time: Relinquished by: Date: Time:
Received for Laboratory by: Lori Brymer Date: 27 APR 16 Time: 1120
Was Shipped Container intact when received? Yes ✓ No ___ Initials LB Seals intact? Yes N/A No ___
Were all samples properly preserved? Yes ✓ No ___ Initials LB Sample temp. 4 °C
Comments:

Time On Site -	
Time Off Site -	

Put an "X" in the appropriate column for sample type and sample preservative. Write in analysis requested.
* For composite samples include start and stop date and time in comments section **Write in preservative used in comments

GUARDIAN SYSTEMS, INC.

1108 Ashville Road
P.O. Box 190
Leeds, Alabama 35094

Telephone (205) 699-6647
Toll Free (866) 729-7211
Fax (205) 699-3882

Jacksonville Utilities Board
655 Nesbit Street
Jacksonville, AL 36265-

Report Date: 06/09/2016
Receive Date: 05/17/2016
Receive Time: 9:15

Attention: Mr. Chris Patterson

Control No : 1605-00229 Sample # 001
Sampler : RM
Sample ID: Field Blank

Sample Date: 05/17/2016
Sample Time: 6:35

Laboratory Certificate

PARAMETER	RESULTS	UNITS	ANALYST	DATE	TIME	METHOD	REF
Arsenic, Trivalent	<0.008	mg/L	OS	05/25/2016	12:00	1632A	

This Certificate is Continued On Next Page.

METHOD REFERENCES

1. Methods for Chemical Analysis of Water and Wastes. EPA-600/4-79-20, revised March 1983, August 1993 May 1994
2. Standard Methods for the Examination of Water and Waste Water, 18th, 19th, 20th, and 22nd Edition, 2012
3. Test Methods for Evaluating Solid Wastes Physical Chemical Method SW-846, 3d Edition, Updated IV December 1996
4. 1987 ASTM Annual Standards
5. Code of Federal Regulations, Title 40, Part 136, Appendix A, Revised July 1995
6. Methods for the Determination of Organic Compounds in Drinking Water, EPA-600/4-88/039, Revised July 1991, August 1995
7. NIOSH Manual of Anaytical Methods, 4th Edition, May 1996

GUARDIAN SYSTEMS, INC.

1108 Ashville Road
P.O. Box 190
Leeds, Alabama 35094

Telephone (205) 699-6647
Toll Free (866) 729-7211
Fax (205) 699-3882

Jacksonville Utilities Board
655 Nesbit Street
Jacksonville, AL 36265-

Report Date: 06/09/2016
Receive Date: 05/17/2016
Receive Time: 9:15

Attention: Mr. Chris Patterson

Control No : 1605-00229 Sample # 002
Sampler : RM
Sample ID: Effluent #2

Sample Date: 05/17/2016
Sample Time: 6:35

Laboratory Certificate

PARAMETER	RESULTS	UNITS	ANALYST	DATE	TIME	METHOD	REF
Arsenic, Trivalent	<0.008	mg/L	OS	05/25/2016	12:00	1632A	

Approved By:

METHOD REFERENCES

1. Methods for Chemical Analysis of Water and Wastes. EPA-600/4-79-20, revised March 1983, August 1993 May 1994
2. Standard Methods for the Examination of Water and Waste Water, 18th, 19th, 20th, and 22nd Edition, 2012
3. Test Methods for Evaluating Solid Wastes Physical Chemical Method SW-846, 3rd Edition, Updated IV December 1996
4. 1987 ASTM Annual Standards
5. Code of Federal Regulations, Title 40, Part 136, Appendix A, Revised July 1995
6. Methods for the Determination of Organic Compounds in Drinking Water, EPA-600/4-88/039, Revised July 1991, August 1995
7. NIOSH Manual of Anaytical Methods, 4th Edition, May 1996

Guardian Systems, Inc.
1108 Ashville Road, P.O. Box 190
Leeds, Alabama 35094
(205) 699-6647
email: lbrymer@gsilab.com
(205) 699-3882 Fax
www.gsilab.com

Chain of Custody Record/ Analysis Report

Client: Chris Patterson	Phone: 256-435-9551
Company: City of Jacksonville	Fax: 256-782-0385
Address: 655 Nis Bat St	P.O.#:
Address: Jacksonville Ala 36265	Email Address:
	Project:

Sample ID	Sample Description	Sample Date	Sample Time	Sample: Comp.*	Sample: Grab	Bottle: Glass	Bottle: Plastic	Preservative: HCl	Preservative: HNO_3	Preservative: H_2SO_4	Preservative: NaOH	Preservative: Cool 4°C	Preservative: Other **	Analysis Requested					
1	Field Blk	5-17-16	6:35AM				✓					✓	✓						
2	Eff Grab	5-17-16	6:38AM		✓		✓					✓		Trivalent	Arsenic				

Sampled by: Roger Mills	5-17-16	6:38AM	Relinquished by: Roger Mills	Date: 5-17-16	Time: 7:55AM
Received by: Shelton Brown	Date: 5-17-16	Time: 7:55AM	Relinquished by: Shelton Brown	Date: 5-17-16	Time: 9:15AM
Received by:	Date:	Time:	Relinquished by:	Date:	Time:
Received for Laboratory by: Lbrymer	Date: 17 May 16	Time: 915			
Was Shipped Container intact when received? Yes ✓ No ___ Initials LB			Seals intact? Yes NS No ___		
Were all samples properly preserved? Yes ✓ No ___ Initials LB			Sample temp. 4 °C		
Comments:					
Time On Site -					
Time Off Site -					

Put an "X" in the appropriate column for sample type and sample preservative. Write in analysis requested.
* For composite samples include start and stop date and time in comments section **Write in preservative used in comments

GUARDIAN SYSTEMS, INC.

1108 Ashville Road
P.O. Box 190
Leeds, Alabama 35094

Telephone (205) 699-6647
Toll Free (866) 729-7211
Fax (205) 699-3882

Jacksonville Utilities Board
655 Nesbit Street
Jacksonville, AL 36265-

Report Date: 07/06/2016
Receive Date: 06/14/2016
Receive Time: 9:55

Attention: Mr. Chris Patterson

Control No : 1606-00247 Sample # 001
Sampler : RM
Sample ID: Field Blank

Sample Date: 06/14/2016
Sample Time: 7:55

Laboratory Certificate

PARAMETER	RESULTS	UNITS	ANALYST	DATE	TIME	METHOD	REF
Arsenic, Trivalent	<0.008	mg/L	OS	06/17/2016	12:00	1632A	

This Certificate is Continued On Next Page.

METHOD REFERENCES

1. Methods for Chemical Analysis of Water and Wastes. EPA-600/4-79-20, revised March 1983, August 1993 May 1994
2. Standard Methods for the Examination of Water and Waste Water, 18th, 19th, 20th, and 22nd Edition, 2012
3. Test Methods for Evaluating Solid Wastes Physical Chemical Method SW-846, 3rd Edition, Updated IV December 1996
4. 1987 ASTM Annual Standards
5. Code of Federal Regulations, Title 40, Part 136, Appendix A, Revised July 1995
6. Methods for the Determination of Organic Compounds in Drinking Water, EPA-600/4-88/039, Revised July 1991, August 1995
7. NIOSH Manual of Anaytical Methods, 4th Edition, May 1996

GUARDIAN SYSTEMS, INC.

1108 Ashville Road
P.O. Box 190
Leeds, Alabama 35094

Telephone (205) 699-6647
Toll Free (866) 729-7211
Fax (205) 699-3882

Jacksonville Utilities Board
655 Nesbit Street
Jacksonville, AL 36265-

Report Date: 07/06/2016
Receive Date: 06/14/2016
Receive Time: 9:55

Attention: Mr. Chris Patterson

Control No : 1606-00247 Sample # 002
Sampler : RM
Sample ID: Effluent #2

Sample Date: 06/14/2016
Sample Time: 7:58

Laboratory Certificate

PARAMETER	RESULTS	UNITS	ANALYST	DATE	TIME	METHOD	REF
Arsenic, Trivalent	<0.008	mg/L	OS	06/17/2016	12:00	1632A	

Approved By: Linda Hall Miller
MP

METHOD REFERENCES

1. Methods for Chemical Analysis of Water and Wastes. EPA-600/4-79-20, revised March 1983, August 1993 May 1994
2. Standard Methods for the Examination of Water and Waste Water, 18th, 19th, 20th, and 22nd Edition, 2012
3. Test Methods for Evaluating Solid Wastes Physical Chemical Method SW-846, 3rd Edition, Updated IV December 1996
4. 1987 ASTM Annual Standards
5. Code of Federal Regulations, Title 40, Part 136, Appendix A, Revised July 1995
6. Methods for the Determination of Organic Compounds in Drinking Water, EPA-600/4-88/039, Revised July 1991, August 1995
7. NIOSH Manual of Anaytical Methods, 4th Edition, May 1996

Guardian Systems, Inc.
1108 Ashville Road, P.O. Box 190
Leeds, Alabama 35094
(205) 699-6647 (205) 699-3882 Fax
email: lbrymer@gsilab.com www.gsilab.com

Chain of Custody Record/ Analysis Report

Client: Chris Patterson	Phone: 256-435-9551
Company: City of Jacksonville	Fax: 256-782-0895
Address: 655 Nisbet ST	P.O.#:
Address: Jacksonville Ala 36265	Email Address:
	Project:

Sample ID	Sample Description	Sample Date	Sample Time	Sample: Comp.*	Sample: Grab	Bottle: Glass	Bottle: Plastic	Preservative: HCl	Preservative: HNO_3	Preservative: H_2SO_4	Preservative: NaOH	Preservative: Cool 4°C	Preservative: Other**	Analysis Requested					
1	Field Blank	6-14-16	7:55 AM				✓					✓	✓						
2	Eff Grab	6-14-16	7:58 AM			✓	✓					✓		Trivalent	Arsenic				

Sampled by: Hogan Mills 6-14-16 7:55 AM Relinquished by: Hogan Mills Date: 6-14-16 Time: 9:55 PM
Received by: Date: Time: Relinquished by: Date: Time:
Received by: Date: Time: Relinquished by: Date: Time:
Received for Laboratory by: Lee Brymer Date: 14 June 16 Time: 955
Was Shipped Container intact when received? Yes ✓ No ___ Initials LB Seals intact? Yes NA No ___
Were all samples properly preserved? Yes ✓ No ___ Initials LB Sample temp. 4 °C
Comments:

Time On Site -	
Time Off Site -	

Put an "X" in the appropriate column for sample type and sample preservative. Write in analysis requested.
* For composite samples include start and stop date and time in comments section **Write in preservative used in comments

SUPPLEMENTARY INFORMATION
NATIONAL POLLUTANT DISCHARGE ELIMINATION SYSTEM (NPDES)
PERMIT APPLICATION FORM 188- Municipal, Semi-Public & Private Facilities

ALABAMA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
WATER DIVISION – MUNICIPAL PERMIT SECTION
POST OFFICE BOX 301463
MONTGOMERY, ALABAMA 36130-1463

INSTRUCTIONS: APPLICATIONS SHOULD BE TYPED OR PRINTED IN INK AND SUBMITTED TO THE DEPARTMENT. PLEASE CONTINUE ON AN ATTACHED SHEET OF PAPER IF INSUFFICIENT SPACE IS AVAILABLE TO ADDRESS ANY ITEM BELOW. PLEASE MARK N/A IN THE APPROPRIATE BOX WHEN AN ITEM IS NON-APPLICABLE TO THE APPLICANT.

PURPOSE OF THIS APPLICATION

- ☐ INITIAL PERMIT APPLICATION FOR NEW FACILITY
- ☐ INITIAL PERMIT APPLICATION FOR EXISTING FACILITY
- ☐ MODIFICATION OF EXISTING PERMIT
- ☑ REISSUANCE OF EXISTING PERMIT
- ☐ REVOCATION & REISSUANCE OF EXISTING PERMIT

SECTION A – GENERAL INFORMATION

1. Facility Name: Jacksonville WWTP

   a. Operator Name: Chris Patterson

   b. Is the operator identified in 1.a, the owner of the facility? Yes ☐ No ☑
   If no, provide name and address of the operator and submit information indicating the operator's scope of responsibility for the facility.
   Chris Patterson, Jacksonville Water Works Gas & Sewer Board, 330 Church Avenue, SE, Jacksonville, AL 36265

   c. Name of Permittee* if different than Operator: Jacksonville Water Works Gas & Sewer Board
   **Permittee will be responsible for compliance with the conditions of the permit*

2. NPDES Permit Number: AL 0022586 (Not applicable if initial permit application)

3. Facility Location: (**Attach a map with location marked; street, route no. or other specific identifier**)
   Street: 655 Nisbet Street NW
   City: Jacksonville County: Calhoun State: Alabama Zip: 36265
   Facility (Front Gate) Location: Latitude (Deg Min Sec): 33 deg 49.531' Longitude (Deg. Min Sec): 85 deg 46.844'

4. Facility Mailing Address (Street or Post Office Box): 330 Church Avenue SE
   City: Jacksonville County: Calhoun State: Alabama Zip: 36265

5. Responsible Official (as described on page 6 of this application):
   Name and Title: Johnny L. Smith, Mayor
   Address: 330 Church Avenue, SE
   City: Jacksonville State: Alabama 36265
   Phone Number: (256) 435-7611
   Email Address: (Optional): mayor@jacksonville-al.org

RECEIVED
JAN 22 2016
IND / MUN BRANCH

6. Designated Facility/DMR Contact:

Name and Title: Chris Patterson, Manager

Phone Number: (256) 435-9551

DMR Email Address (Optional – for receipt of blank DMR Forms): jacksonville8@cableone.net

7. Designated Emergency Contact:

Name and Title: Chris Patterson, Manager

Phone Number: (256) 435-9551

Email Address **(Required)**: jacksonville8@cableone.net

8. Please complete this section if the Applicant's business entity is a Proprietorship or limited liability Corporation with a responsible official not listed in Item 5.

a) Proprietor:

Name: N/A

Address: 330 Church Avenue, SE

City: Jacksonville State: Alabama Zip: 36265

9. Permit numbers for Applicant's previously issued NPDES Permits and identification of any other State Environmental Permits presently held by the Applicant within the State of Alabama:

Permit Name	Permit Number	Held by
Jacksonville WWTP	AL0022586	Jacksonville WWG & SB

10. Identify all Administrative Complaints, Notices of Violation, Directives, or Administrative Orders, Consent Decrees, or Litigation concerning water pollution or other permit violations, if any against the Applicant within the State of Alabama in the past five years (attach additional sheets if necessary):

Facility Name	Permit Number	Type of Action	Date of Action
Jacksonville WWTP	Al0022586	ENOV	July 20, 2015
Jacksonville WWTP	AL0022586	EWL	May 6, 2014

SECTION B – WASTEWATER DISCHARGE INFORMATION

1. List the following historical monthly flow rates recorded for the past five years for each outfall:

Outfall Number	Highest in Last 12 Months MGD	Highest Daily Flow MGD	Average Flow MGD
001	4.986	7.397	1.902

2. Attach a process flow schematic of the treatment process, including the size of each unit operation.

3. Do you have, or plan to have, automatic sampling equipment or continuous wastewater flow metering equipment at this facility?

Current:	Flow Metering	Yes	☑	No	☐	N/A ☐
	Sampling Equipment	Yes	☑	No	☐	N/A ☐
Planned:	Flow Metering	Yes	☐	No	☐	N/A ☑
	Sampling Equipment	Yes	☐	No	☐	N/A ☑

If so, please attach a schematic diagram of the sewer system indicating the present or future location of this equipment and describe the equipment below:

4. Are any wastewater collection or treatment modifications or expansions planned during the next three years that could alter wastewater volumes or characteristics (Note: Permit Modification may be required)? Yes ☑ No ☐

Briefly describe these changes and any potential or anticipated effects on the wastewater quality and quantity: (Attach additional sheets if needed.)

Replacement of Process Units --- Grit/Grease Removal, Aeration Basins, UV, Aerobic Digestion

SECTION C – WASTE STORAGE AND DISPOSAL INFORMATION

Describe the location of all sites used for the storage of solids or liquids that have any potential for accidental discharge to a water of the state, either directly or indirectly via storm sewer, municipal sewer, municipal wastewater treatment plants, or other collection or distribution systems that are located at or operated by the subject existing or proposed NPDES-permitted facility. Indicate the location of any potential release areas and provide a map or detailed narrative description of the areas of concern as an attachment to this application:

Description of Waste	Description of Storage Location

Describe the location of any sites used for the ultimate disposal of solid or liquid waste materials or residuals (e.g. sludges) generated by any wastewater treatment system located at the facility.

Description of Waste	Quantity (lbs/day)	Disposal Method*
Drying Bed Sludge		Land Applied

***Indicate any wastes disposed at an off-site treatment facility and any wastes that are disposed on-site**

SECTION D – INDUSTRIAL INDIRECT DISCHARGE CONTRIBUTORS

1. List the existing and proposed industrial source wastewater contributions to the municipal wastewater treatment system (Attach other sheets if necessary)

Company Name	Description of Industrial Wastewater	Existing or Proposed	Flow (MGD)	Subject to SID Permit? Y/N
Parker Hannafin	Process Waste	Exist	0.018	Yes

2. Are industrial wastewater contributions regulated via a locally approved sewer use ordinance? Yes ☐ No ☐ If so, please attach a copy of the ordinance.

SECTION E – COASTAL ZONE INFORMATION

Is the discharge(s) located within the 10-foot elevation contour and within the limits of Mobile or Baldwin County?
Yes No ✓ If yes, then complete items A through M below:

		YES	NO
A.	Does the project require new construction?	☐	☐
B.	Will the project be a source of new air emissions?	☐	☐
C.	Does the project involve dredging and/or filling of a wetland area or water way?	☐	☐
	Has the Corps of Engineers (COE) permit been issued?	☐	☐
	Corps Project Number _____		
D.	Does the project involve wetlands and/or submersed grassbeds?	☐	☐
E.	Are oyster reefs located near the project site? (Include a map showing project and discharge location with respect to oyster reefs)	☐	☐
F.	Does the project involve the site development, construction and operation of an energy facility as defined in ADEM Admin. Code R. 335-8-1-.02(bb)?	☐	☐
G.	Does the project involve mitigation of shoreline or coastal area erosion?	☐	☐
H.	Does the project involve construction on beaches or dunes areas?	☐	☐
I.	Will the project interfere with public access to coastal waters?	☐	☐
J.	Does the project lie within the 100-year floodplain?	☐	☐
K.	Does the project involve the registration, sale, use, or application of pesticides?	☐	☐
L.	Does the project propose or require construction of a new well or to alter an existing groundwater well to pump more than 50 gallons per day (GPD)?	☐	☐
M.	Has the applicable permit for groundwater recovery or for groundwater well installation been obtained?	☐	☐

SECTION F – ANTI-DEGRADATION EVALUATION

It is the applicant's responsibility to demonstrate the social and economic importance of the proposed activity, if subject to antidegradation requirements. In accordance with 40 CFR 131.12 and Section 335-6-10-.04 of the Alabama Department of Environmental Management Administrative Code, the following information must be provided, if applicable. If further information is required to make this demonstration, attach additional sheets to the application.

1. Is this a new or increased discharge that began after April 3, 1991? Yes ☐ No ☑
   If "yes", complete question 2 below. If "no", do not complete this section.

2. Has an Anti-Degradation Analysis been previously conducted and submitted to the Department for the new or increased discharge referenced in question 1? Yes ☐ No ☐

   If "no" and the discharge is to a Tier II waterbody as defined in ADEM Admin. Code r. 335-6-10-.12(4), complete questions A through F below, ADEM Form 311-Alternatives Analysis, and either ADEM Form 312 or ADEM Form 313-Calculation of Total Annualized Project Costs (Public-Sector or Private-Sector Projects, whichever is applicable). ADEM Form 312 or ADEM Form 313, whichever is applicable, must be provided for **each** treatment discharge alternative considered technically viable. ADEM forms can be found on the Department's website at www.adem.alabama.gov/DeptForms. If "yes", do not complete this section.

   Information required for new or increased discharges to high quality waters:

   A. What environmental or public health problem will the discharger be correcting?

   B. Explain if and to what degree the discharger will be increasing employment as a result of the proposed discharge, either at its existing facility or as the result of the start-up of a related new facility or industry.

   C. Explain if and to what degree the discharge will prevent employment reductions?

   D. Describe any additional state or local taxes that the prospective discharger will be paying.

   E. Describe any public service the discharger will be providing to the community.

   F. Describe the economic or social benefit the discharger will be providing to the community.

SECTION G – EPA Application Forms

All Applicants must submit certain EPA permit application forms. More than one application form may be required from a municipal facility depending on the number and types of discharges or outfalls. The EPA application forms are found on the Department's website at www.adem.alabama.gov\programs\water. The required ADEM and EPA forms are summarized in Attachment 1.

SECTION H– ENGINEERING REPORT/BMP PLAN REQUIREMENTS

Any Engineering Report or Best Management Practice (BMP) Plans required to be submitted to ADEM by the applicant must be in accordance with ADEM 335-6-6-.08(i) & (j).

SECTION I– RECEIVING WATERS

Receiving Water(s)	303(d) Segment? (Y / N)	Included in TMDL?* (Y / N)
UT Tallassahatchee Creek	NO	NO

*If a TMDL Compliance Schedule is requested the following should be attached as supporting documentation:
(1) Justification for the proposed Compliance Schedule (e.g. time for design and installation of control equipment, etc.); (2) Monitoring results for the pollutant(s) of concern which have not previously been submitted to the Department (sample collection dates, analytical results (mass and concentration), methods utilized, MDL/ML, etc. should be reported as available); (3) Requested interim limitations, if applicable; (4) Date of final compliance with the TMDL limitations; and (5) Any other additional information available to support the requested compliance schedule.

SECTION H– APPLICATION CERTIFICATION

THE INFORMATION CONTAINED IN THIS FORM MUST BE CERTIFIED BY A RESPONSIBLE OFFICIAL AS DEFINED IN ADEM ADMINISTRATIVE RULE 335-6-6-.09 "SIGNATORY REQUIREMENTS FOR PERMIT APPLICATIONS" (SEE BELOW).

"I CERTIFY UNDER PENALTY OF LAW THAT THIS DOCUMENT AND ALL ATTACHMENTS WERE PREPARED UNDER MY DIRECTION OR SUPERVISION IN ACCORDANCE WITH A SYSTEM DESIGNED TO ASSURE THAT QUALIFIED PERSONNEL PROPERLY GATHER AND EVALUATE THE INFORMATION SUBMITTED. BASED ON MY INQUIRY OF THE PERSON OR PERSONS WHO MANAGE THE SYSTEM, OR THOSE PERSONS DIRECTLY RESONSIBLE FOR GATHERING THE INFORMATION, THE INFORMATION SUBMITTED IS, TO THE BEST OF MY KNOWLEDGE AND BELIEF, TRUE, ACCURATE, AND COMPLETE.I AM AWARE THAT THERE ARE SIGNIFICANT PENALTIES FOR SUBMITTING FALSE INFORMATION INCLUDING THE POSSIBILITY OF FINE AND IMPRISONMENT FOR KNOWING VIOLATIONS."

"I FURTHER CERTIFY UNDER PENALTY OF LAW THAT THE RESULTS OF ANY ANALYSES REPORTED AS LESS THAN DETECTABLE IN THIS APPLICATION OR IN ATTACHMENTS THERETO WERE PERFORMED USING THE EPA APPROVED TEST METHOD HAVING THE LOWEST DETECTION LIMIT READILY ACHIEVABLE FOR THE SUBSTANCE TESTED."

SIGNATURE OF RESPONSIBLE OFFICIAL: Johnny L Smith DATE SIGNED: 11/23/15

(TYPE OR PRINT)

NAME OF RESPONSIBLE OFFICIAL: JOHNNY L. SMITH

OFFICIAL TITLE OF RESPONSIBLE OFFICIAL: Mayor / Superintendent

MAILING ADDRESS: 330 CHURCH AVENUE SE

AREA CODE & PHONE NUMBER: 256-435-7611

SIGNATORY REQUIREMENTS FOR PERMIT APPLICATIONS

Responsible official is defined as follows:

1. In the case of a municipal, state, federal, or other public facility, the responsible official is either a principal executive officer or a ranking elected official of the municipality or other public entity.

2. In the case of a private or semi-public facility, the responsible official is either a principal executive officer or the owner of the corporation or other entity.

Attachment 1 to Supplementary Form
ADEM Form 311

Alternatives Analysis

Applicant/Project: N/A

All new or expanded discharges (except discharges eligible for coverage under general permits) covered by the NPDES permitting program are subject to the provisions of ADEM's antidegradation policy. Applicants for such discharges to Tier 2 waters are required to demonstrate " . . . that the proposed discharge is necessary for important economic or social development." As a part of this demonstration, the applicant must complete an evaluation of the discharge alternatives listed below, including a calculation of the total annualized project costs for each technically feasible alternative (using ADEM Form 312 for public-sector projects and ADEM Form 313 for private-sector projects). Alternatives with total annualized project costs that are less than 110% of the total annualized project costs for the Tier 2 discharge proposal are considered viable alternatives.

Alternative	Viable	Non-Viable	Comment
1 Land Application			
2 Pretreatment/Discharge to POTW			
3 Relocation of Discharge			
4 Reuse/Recycle			
5 Process/Treatment Alternatives			
6 On-site/Sub-surface Disposal			
(other project-specific alternatives considered by the applicant; attach additional sheets if necessary)			
7			
8			
9			

Pursuant to ADEM Administrative Code Rule 335-6-3-.04, I certify on behalf of the applicant that I have completed an evaluation of the discharge alternatives identified above, and reached the conclusions indicated.

Signature: _____
(Professional Engineer)

Date: _____

(Supporting documentation to be attached, referenced, or otherwise handled as appropriate.)

ADEM Form 311 3/02

Attachment 2 to Supplementary Form

Calculation of Total Annualized Project Costs for Public-Sector Projects

N/A

A. Capital Costs

Capital Cost of Project	$	
Other One-Time Costs of Project (Please List, if any):		
Wastewater Treatment Plant Improvements	$ 8,000,000	
	$	
	$	
Total Capital Costs (Sum column)	$ 0	(1)
Portion of Capital Costs to be Paid for with Grant Monies	$ 8,000,000	(2)
Capital Costs to be Financed [Calculate: (1) – (2)]	$	(3)
Type of Financing (e.g., G.O. bond, revenue bond, bank loan)	SRF Loan	
Interest Rate for Financing (expressed as decimal)	2.25%	(i)
Time Period of Financing (in years)	20	(n)
Annualization Factor = $\frac{i}{(1+i)^n - 1} + i$		(4)
Annualized Capital Cost [Calculate: (3) x (4)]		(5)

B. Operating and Maintenance Costs

Annual Costs of Operation and Maintenance (including but not limited to: monitoring, inspection, permitting fees, waste disposal charges, repair, administration and replacement.) (Please list below.)

	$	
	$	
	$	
	$	
Total Annual O & M Costs (Sum column)	$	(6)

C. Total Annual Cost of Pollution Control Project

Total Annual Cost of Pollution Control Project [(5) + (6)]	$	(7)

ADEM Form 312 3/02

Attachment 3 to Supplementary Form
ADEM Form 313

Calculation of Total Annualized Project Costs for Private-Sector Projects N/A

Capital Costs to be Financed (Supplied by applicant)	$	(1)
Interest rate for Financing (Expressed as a decimal)		(i)
Time Period of Financing (Assume 10 years*)	10 years	(n)
Annualization Factor $= \frac{i}{(1+i)^{10}-1} + i$		(2)
Annualized Capital Cost [Calculate: (1) x (2)]	$	(3)
Annual Cost of Operation and Maintenance (including but not limited to monitoring, inspection, permitting fees, waste disposal charges, repair, administration and replacement)**	$	(4)
Total Annual Cost of Pollution Control Project [(3) + (4)]	$	(5)

* While actual payback schedules may differ across projects and companies, assume equal annual payments over a 10-year period for consistency in comparing projects.

** For recurring costs that occur less frequently than once a year, pro rate the cost over the relevant number of years (e.g., for pumps replaced once every three years, include one-third of the cost in each year).

ADEM Form 313 3/02

Attachment 4 to Supplementary Form

NPDES PROGRAM N/A
PERMIT APPLICATION FORMS
ALABAMA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

TYPE DISCHARGE	ADEM FORMS	EPA FORMS
New or existing once through non-contact cooling water and/or cooling tower blowdown, and/or sanitary wastewater (non-process wastewater only). Note: POTWs must use Form 2A.	Supplemental Information Form 187 – (Industrial) or Form 188 (Municipal)	Forms 1 and 2E
Existing discharges of process wastewater	Supplemental Information Form 187 – (Industrial) or Form 188 (Municipal)	Forms 1 and 2C
New discharges of process wastewater	Supplemental Information Form 187 – (Industrial) or Form 188 (Municipal)	Forms 1 and 2D
New or existing discharges composed entirely of stormwater meeting the EPA definition of stormwater associated with industrial activity	Supplemental Information Form 187 – (Industrial) or Form 188 (Municipal)	Forms 1 and 2F
New or existing discharges composed of stormwater meeting the EPA definition of stormwater associated with industrial activity, and any other non-stormwater discharges.	Supplemental Information Form 187 – (Industrial) or Form 188 (Municipal)	Forms 1 and 2F and, as appropriate, Forms 2E, 2C, and/or 2D
New or existing Publicly-Owned Treatment Works (POTWs) and Privately-Owned Treatment Works composed of sanitary wastewater	Supplemental Information Form 187 – (Industrial) or Form 188 (Municipal)	Forms 1 and 2A
New or existing land application of process wastewater. Form 2F is required for stormwater runoff from the land application site, if the site is not completely bermed to prevent runoff.	Supplemental Information Form 187	Forms 1, 2F, and 2C or 2D, as appropriate
New or existing land application of sanitary wastewater. Form 2F is required for stormwater runoff from the land application site, if the site is not completely bermed to prevent runoff.	Supplemental Information Form 187 – (Industrial) or Form 188 (Municipal)	Forms 1, 2F, and 2A or 2E, as appropriate

Testing requirements: Test procedures for all analyses shall conform to 40 CFR Part 136. If more than one method of analysis is approved, then the method having the lowest detection level shall be used. Any facilities discharging to mercury impaired surface waters identified by EPA or ADEM [as identified on the latest §303(d) List] and any facility with a discharge that has reasonable potential to cause in-stream exceedence of a Water Quality Based Effluent Limit (WQBEL) shall be required to use EPA Method *1631E.*



JACKSONVILLE, ALABAMA

WWTP Location
2015

Utility Engineering Consultants, LLC

Please print or type in the unshaded areas only.

EPA ID Number (*copy from Item 1 of Form 1*)
JACKSONVILLE WWTP AL 0022586

Form Approved. OMB No. 2040-0086
Approval expires 5-31-92

FORM 2F NPDES

U.S. Environmental Protection Agency
Washington, DC 20460

Application for Permit to Discharge Storm Water Discharges Associated with Industrial Activity

Paperwork Reduction Act Notice

Public reporting burden for this application is estimated to average 28.6 hours per application, including time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding the burden estimate, any other aspect of this collection of information, or suggestions for improving this form, including suggestions which may increase or reduce this burden to: Chief, Information Policy Branch, PM-223, U.S. Environmental Protection Agency, 1200 Pennsylvania Avenue, NW, Washington, DC 20460, or Director, Office of Information and Regulatory Affairs, Office of Management and Budget, Washington, DC 20503.

I. Outfall Location

For each outfall, list the latitude and longitude of its location to the nearest 15 seconds and the name of the receiving water.

A. Outfall Number (*list*)	B. Latitude			C. Longitude			D. Receiving Water (*name*)
STORM 001	33	49	33	85	46	56	UT -TALLASSEEHATCHEE CREEK

II. Improvements

A. Are you now required by any Federal, State, or local authority to meet any implementation schedule for the construction, upgrading or operation of wastewater treatment equipment or practices or any other environmental programs which may affect the discharges described in this application? This includes, but is not limited to, permit conditions, administrative or enforcement orders, enforcement compliance schedule letters, stipulations, court orders, and grant or loan conditions.

1. Identification of Conditions, Agreements, Etc.	2. Affected Outfalls		3. Brief Description of Project	4. Final Compliance Date	
	number	source of discharge		a. req.	b. proj.
N/A					

B: You may attach additional sheets describing any additional water pollution (or other environmental projects which may affect your discharges) you now have under way or which you plan. Indicate whether each program is now under way or planned, and indicate your actual or planned schedules for construction.

III. Site Drainage Map

Attach a site map showing topography (or indicating the outline of drainage areas served by the outfalls(s) covered in the application if a topographic map is unavailable) depicting the facility including: each of its intake and discharge structures; the drainage area of each storm water outfall; paved areas and buildings within the drainage area of each storm water outfall, each known past or present areas used for outdoor storage of disposal of significant materials, each existing structural control measure to reduce pollutants in storm water runoff, materials loading and access areas, areas where pesticides, herbicides, soil conditioners and fertilizers are applied; each of its hazardous waste treatment, storage or disposal units (including each area not required to have a RCRA permit which is used for accumulating hazardous waste under 40 CFR 262.34); each well where fluids from the facility are injected underground; springs, and other surface water bodies which received storm water discharges from the facility.

Continued from the Front

IV. Narrative Description of Pollutant Sources

A. For each outfall, provide an estimate of the area (include units) of imperious surfaces (including paved areas and building roofs) drained to the outfall, and an estimate of the total surface area drained by the outfall.

Outfall Number	Area of Impervious Surface *(provide units)*	Total Area Drained *(provide units)*	Outfall Number	Area of Impervious Surface *(provide units)*	Total Area Drained *(provide units)*

B. Provide a narrative description of significant materials that are currently or in the past three years have been treated, stored or disposed in a manner to allow exposure to storm water; method of treatment, storage, or disposal; past and present materials management practices employed to minimize contact by these materials with storm water runoff; materials loading and access areas, and the location, manner, and frequency in which pesticides, herbicides, soil conditioners, and fertilizers are applied.

Raw sewage from the City of Jacksonville Collection System.

C. For each outfall, provide the location and a description of existing structural and nonstructural control measures to reduce pollutants in storm water runoff; and a description of the treatment the storm water receives, including the schedule and type of maintenance for control and treatment measures and the ultimate disposal of any solid or fluid wastes other than by discharge.

Outfall Number	Treatment	List Codes from Table 2F-1

V. Nonstormwater Discharges

A. I certify under penalty of law hat the outfall(s) covered by this application have been tested or evaluated for the presence of nonstormwater discharges, and that all nonstormwater discharged from these outfall(s) are identified in either an accompanying Form 2C or From 2E application for the outfall.

Name and Official Title *(type or print)*	Signature	Date Signed
Johnny L. Smith, MAYOR	Johnny L. Smith	1/19/16

B. Provide a description of the method used, the date of any testing, and the onsite drainage points that were directly observed during a test.

VI. Significant Leaks or Spills

Provide existing information regarding the history of significant leaks or spills of toxic or hazardous pollutants at the facility in the last three years, including the approximate date and location of the spill or leak, and the type and amount of material released.

NONE

RECEIVED
JAN 22 2016
IND / MUN BRANCH

EPA ID Number *(copy from Item 1 of Form 1)*
JACKSONVILLE WWTP AL 0022586

VII. Discharge Information

A, B, C, & D: See instructions before proceeding. Complete one set of tables for each outfall. Annotate the outfall number in the space provided. Table VII-A, VII-B, VII-C are included on separate sheets numbers VII-1 and VII-2.

E. Potential discharges not covered by analysis – is any toxic pollutant listed in table 2F-2, 2F-3, or 2F-4, a substance or a component of a substance which you currently use or manufacture as an intermediate or final product or byproduct?

☐ Yes (*list all such pollutants below*) ☑ No (*go to Section IX*)

VIII. Biological Toxicity Testing Data

Do you have any knowledge or reason to believe that any biological test for acute or chronic toxicity has been made on any of your discharges or on a receiving water in relation to your discharge within the last 3 years?

☐ Yes (*list all such pollutants below*) ☑ No (*go to Section IX*)

IX. Contract Analysis Information

Were any of the analyses reported in Item VII performed by a contract laboratory or consulting firm?

☐ Yes (*list the name, address, and telephone number of, and pollutants analyzed by, each such laboratory or firm below*) ☑ No (*go to Section X*)

A. Name	B. Address	C. Area Code & Phone No.	D. Pollutants Analyzed

X. Certification

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

A. Name & Official Title (*Type Or Print*)	B. Area Code and Phone No.
JOHNNY L. SMITH, MAYOR	(256) 435-7611
C. Signature: Johnny L Smith	D. Date Signed: 11/23/15

VII. Discharge information *(Continued from page 3 of Form 2F)*

Part A – You must provide the results of at least one analysis for every pollutant in this table. Complete one table for each outfall. See instructions for additional details.

Pollutant and CAS Number *(if available)*	Maximum Values *(include units)*		Average Values *(include units)*		Number of Storm Events Sampled	Sources of Pollutants
	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite		
Oil and Grease		N/A				
Biological Oxygen Demand (BOD5)						
Chemical Oxygen Demand (COD)						
Total Suspended Solids (TSS)						
Total Nitrogen						
Total Phosphorus						
pH	Minimum	Maximum	Minimum	Maximum		

Part B – List each pollutant that is limited in an effluent guideline which the facility is subject to or any pollutant listed in the facility's NPDES permit for its process wastewater (if the facility is operating under an existing NPDES permit). Complete one table for each outfall. See the instructions for additional details and requirements.

Pollutant and CAS Number *(if available)*	Maximum Values *(include units)*		Average Values *(include units)*		Number of Storm Events Sampled	Sources of Pollutants
	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite		

Continued from the Front

Part C - List each pollutant shown in Table 2F-2, 2F-3, and 2F-4 that you know or have reason to believe is present. See the instructions for additional details and requirements. Complete one table for each outfall.

Pollutant and CAS Number *(if available)*	Maximum Values *(include units)*		Average Values *(include units)*		Number of Storm Events Sampled	Sources of Pollutants
	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite	Grab Sample Taken During First 20 Minutes	Flow-Weighted Composite		

Part D – Provide data for the storm event(s) which resulted in the maximum values for the flow weighted composite sample.

1. Date of Storm Event	2. Duration of Storm Event *(in minutes)*	3. Total rainfall during storm event *(in inches)*	4. Number of hours between beginning of storm measured and end of previous measurable rain event	5. Maximum flow rate during rain event *(gallons/minute or specify units)*	6. Total flow from rain event *(gallons or specify units)*

7. Provide a description of the method of flow measurement or estimate.


EXISTING SLUDGE BEDS
EXISTING SLUDGE BEDS
EXISTING SLUDGE BEDS
EXISTING SLUDGE BEDS
EXISTING FILTER
EXISTING FILTER
EXISTING FINAL CLARIFIER
EXISTING FINAL CLARIFIER
ALABAMA HIGHWAY 204
EXISTING DIGESTER
EXISTING DIGESTER
EXISTING DIGESTER
EXISTING PRIMARY CLARIFIER
EXISTING GAS BURNER
EXISTING OFFICE
EXISTING GRIT REMOVAL
EXISTING FINAL CLARIFIER
EXISTING SHOP
EXISTING PUMP STATION
EXISTING CHLORINE CONTACT
EXISTING RERELATOR
EXISTING GRIT/GREASE
EXISTING SCREW PUMP
EXISTING BAR SCREEN
EXISTING AERATION REACTOR
EXISTING SECONDARY CLARIFIER
EXISTING POST AERATION
EXISTING CASCADE
EXISTING AERATION REACTOR
EXISTING SECONDARY CLARIFIER
EXISTING SLUDGE FILTER BEDS
EXISTING UV SYSTEM
Storm Water Outfall Location
Latitude 33deg 45' 55"
Longitude 85deg 46' 56"
SITE PLAN
SCALE 1" = 30'
JACKSONVILLE, ALABAMA
JACKSONVILLE SEWER SYSTEM IMPROVEMENTS
JACKSONVILLE W.W.T.P. UPGRADES
EXISTING SITE PLAN
NO. DATE REMARKS BY
REVISIONS
Utility Engineering Consultants, LLC
DESIGNED DEB
DRAWN MK
SCALE AS NOTED
DATE JULY, 2016
APPROVED
REFERENCE M:\DSB\SITE.DGN
JOB NO JAN4 059
SHEET 3 OF 126