




Final
Total Maximum Daily Load (TMDL)
for
Town Branch
Assessment Unit ID # AL03150203-0802-400
Pathogens (E. coli)

Alabama Department of Environmental Management
Water Quality Branch
Water Division
September 2011

Figure I: Town Branch Watershed



<i>Table of Contents</i>		<i>Page</i>
1.0	Executive Summary	1
2.0	Basis for §303(d) Listing	3
2.1	Introduction	3
2.2	Problem Definition	3
3.0	Technical Basis for TMDL Development	5
3.1	Water Quality Target Identification	5
3.2	Source Assessment	6
3.2.1	Point Sources in the Town Branch Watershed	6
3.2.2	Nonpoint Sources in the Town Branch Watershed	7
3.3	Land Use Assessment	7
3.4	Linkage Between Numeric Targets and Sources	9
3.5	Data Availability and Analysis	10
3.6	Critical Conditions	12
3.7	Margin of Safety	12
4.0	TMDL Development	13
4.1	Definition of a TMDL	13
4.2	Load Calculations	13
4.3	TMDL Summary	15
5.0	Follow Up Monitoring	16
6.0	Public Participation	16
7.0	Appendices	17
7.1	References	18
7.2	Water Quality Data	19
7.3	Town Branch Watershed Photos	22

List of Figures

Figure I	Town Branch Watershed	ii
Figure 3-1	Land Use Map for the Town Branch Watershed	8
Figure 3-2	Graph of Primary Land Uses in the Town Branch Watershed	9
Figure 3-3	Map of ADEM Sampling Station on Town Branch	11

List of Tables

Table 1-1	2010 E. coli Loads and Required Reductions	2
Table 1-2	E. coli TMDL for Town Branch	2
Table 3-1	Land Use Areas for the Town Branch Watershed	8
Table 3-2	2010 E-Coli Exceedances for the Town Branch Watershed	10
Table 3-3	Town Branch Sampling Station Description	12
Table 4-1	2010 E. coli Loads and Required Reductions	14
Table 4-2	E. coli TMDL for Town Branch	15
Table 5-1	§303(d) Follow Up Monitoring Schedule	16
Table 7-1	ADEM Pathogen Data Collected on Town Branch (2000, 2001)	20
Table 7-2	2010 ADEM Pathogen Data with Percent Reductions Collected from Town Branch	21

List of Photos

Photo 7-1	Town Branch at TOWNW-4 (State Route 10)	23
Photo 7-2	Town Branch at State Route 41	23
Photo 7-3	Pasture land in the Town Branch	24
Photo 7-4	Camden South WWTP Lagoon	24

1.0 *Executive Summary*

Section §303(d) of the Clean Water Act and EPA's Water Quality Planning and Management Regulations (40 CFR Part 130) require states to identify waterbodies which are not meeting their designated uses and to determine the Total Maximum Daily Load (TMDL) for pollutants causing the use impairment. A TMDL is the sum of individual wasteload allocations for point sources (WLAs), load allocations (LAs) for nonpoint sources including natural background levels, and a margin of safety (MOS).

Town Branch is on the §303(d) list for pathogens from its source to Pursley Creek. Town Branch forms in Wilcox County north of the city of Camden, in the Alabama River Basin. It flows through the city of Camden and empties into Pursley Creek. The total length of Town Branch is 4.35 miles, of which all 4.35 miles are on the §303(d) list. The total drainage area of the Town Branch watershed is 3.62 square miles, of which all 3.62 square miles drains to the impaired segment. Town Branch has a use classification of Fish & Wildlife (F&W). Town Branch represents a tributary to Pursley Creek, which was also listed for pathogens on the §303(d) use impairment list in 2008. The following Total Maximum Daily Load (TMDL), however, will only address the pathogen impaired segment of Town Branch.

Town Branch was first listed on the §303(d) list in 2006 based on data collected in 2000 and 2001 by the Alabama Department of Environmental Management (ADEM) which indicated the stream was impaired for fecal coliform. The data was collected from station TWNW-1 and can be found in Appendix 7.2, Table 7-1. Town Branch has subsequently been listed on the 2008 and 2010 §303(d) lists of impaired waterbodies.

In 2010, §303(d) sampling studies were performed by ADEM on Town Branch to further assess the water quality of the impaired stream. For purposes of this TMDL, the 2010 data will be used to assess the water quality of Town Branch because it was collected less than six years ago and provides the best picture of the current water quality of the stream. The January 2010 edition of *Alabama's Water Quality Assessment and Listing Methodology* section 4.8.2, prepared by ADEM, provides the rationale for the Department to use the most recent data to prepare a TMDL for an impaired waterbody when that data indicates a change in water quality has occurred. Also, as a result of the Alabama Environmental Management Commission's (EMC) adoption of the *Escherichia coli* (E. coli) criteria as the new bacterial indicator, this TMDL will be developed from E. coli data collected at station TWNW-1 in 2010; even though the 2000 and 2001 data that prompted the listing of Town Branch was based on the fecal coliform criteria. ADEM collected 32 samples from Town Branch at 3 stations in 2010. According to the data collected in 2010, Town Branch was not meeting the pathogen criterion applicable to its use classification of Fish and Wildlife. Therefore, a TMDL will be developed for pathogens (E. coli) on the listed reach.

A mass balance approach was used for calculating the pathogen TMDL for Town Branch. The mass balance approach utilizes the conservation of mass principle. Loads were calculated by multiplying the E. coli concentration times the respective instream flow and a conversion factor. The mass loading was calculated using the single sample exceedance that resulted in the highest percent reduction (Appendix 7.2, Table 7-2). In the same manner, an allowable load was calculated for the single sample E. coli criterion of 487 colonies/100 mL. More specifically, the

existing pathogen loading for this TMDL was calculated using the single sample exceedance concentration of 1413.6 colonies/100 mL from 7/12/2010 times the flow of the sample (0.37 cfs) and a conversion factor. The allowable loading, defined by the single sample criterion including a margin of safety, was calculated using the same flow value times the E. coli single sample target of 438.3 colonies/100 mL (487 colonies/100 mL – 10% Margin of Safety). The reduction required to meet the allowable loading was then calculated by subtracting the allowable loading from the existing loading. The single sample violation resulted in a pathogen loading reduction of 69%. There was also a geometric mean violation of 201.1 colonies/100 mL, which resulted in a pathogen loading reduction of only 44%. Therefore the single sample exceedance will be used for development of the subject TMDL.

Table 1-1 is a summary of the estimated existing load, allowable load, and percent reduction for the single sample criterion. Table 1-2 provides the details of the TMDL along with the corresponding reductions for Town Branch which are protective of E. coli water quality standards year round.

Table 1-1. 2010 E. coli Loads and Required Reductions

Source	Existing Load (colonies/day)	Allowable Load (colonies/day)	Required Reduction (colonies/day)	% Reduction
Nonpoint Source Load Single Sample	1.28E+10	3.97E+09	8.83E+09	69%
Nonpoint Source Load Geometric Mean	1.13E+09	6.38E+08	4.93E+08	44%
Point Source Load	1.68E+9 ^a	1.74+E10 ^a	0	0%

a. Point Source loads and load reductions are based on current permit limits of Fecal coliform as well as a design flow of 0.56 MGD for Camden South WWTP. Based on these figures, one can conclude that no reductions are necessary to achieve appropriate pathogen loading for the permitted facility.

Table 1-2. E. coli TMDL for Town Branch

TMDL	Margin of Safety (MOS)	Waste Load Allocation (WLA) ^a			Load Allocation (LA)	
		WWTPs ^b	MS4s ^c	Leaking Collection Systems ^d		
(col/day)	(col/day)	(col/day)	(% reduction)	(col/day)	(col/day)	(% reduction)
1.47E+10	4.41E+08	1.03+E10	NA	0	3.97E+09	69%

Note: NA = not applicable

a. There are no CAFOs in the Town Branch watershed. Future CAFOs will be assigned a waste load allocation (WLA) of zero.

b. WLAs for WWTPs are expressed as a daily maximum. Future WWTPs must meet the applicable instream water quality criteria for pathogens at the point of discharge.

c. Future MS4 areas would be required to demonstrate consistency with the assumptions and requirements of this TMDL.

d. The objective for leaking collection systems is a WLA of zero. It is recognized, however, that a WLA of 0 colonies/day may not be practical. For these sources, the WLA is interpreted to mean a reduction in E. coli loading to the maximum extent practicable, consistent with the requirement that these sources not contribute to a violation of the water quality criteria for E. coli.

e. TMDL was established using the single sample criterion of 487 colonies/100ml.

Compliance with the terms and conditions of existing and future NPDES permits will effectively implement the WLA and demonstrate consistency with the assumptions and requirements of the TMDL. Required load reductions in the LA portion of this TMDL can be implemented through voluntary measures and may be eligible for CWA §319 grants.

The Department recognizes that adaptive implementation of this TMDL will be needed to achieve applicable water quality criteria and we are committed towards targeting the load reductions to improve water quality in the Town Branch watershed. As additional data and/or information become available, it may become necessary to revise and/or modify the TMDL accordingly.

2.0 Basis for §303(d) Listing

2.1 Introduction

Section §303(d) of the Clean Water Act and EPA's Water Quality Planning and Management Regulations (40 CFR Part 130) require states to identify waterbodies which are not meeting their designated uses and to determine the total maximum daily load (TMDL) for pollutants causing use impairment. The TMDL process establishes the allowable loading of pollutants for a waterbody based on the relationship between pollution sources and instream water quality conditions, so that states can establish water-quality based controls to reduce pollution and restore and maintain the quality of their water resources (USEPA, 1991).

The State of Alabama has identified the 4.35 miles of Town Branch as impaired for pathogens. The §303(d) listing was originally reported on Alabama's 2006 List of Impaired Waters based on ADEM data collected in 2000 and 2001 and subsequently included on the 2008 and 2010 lists. The source of the impairment is listed on the 2010 §303(d) list as municipal, urban runoff/storm sewers.

2.2 Problem Definition

<u>Waterbody Impaired:</u>	Town Branch – From Pursley Creek to its source
<u>Impaired Reach Length:</u>	4.35 miles
<u>Impaired Drainage Area:</u>	3.62 square miles
<u>Water Quality Standard Violation:</u>	Pathogens (single sample, geomean)
<u>Pollutant of Concern:</u>	Pathogens (E. coli)
<u>Water Use Classification:</u>	Fish and Wildlife
<u>Usage Related to Classification:</u>	

The impaired stream segment is classified as Fish and Wildlife (F&W). Usage of waters in this classification is described in ADEM Admin. Code R. 335-6-10-.09(5)(a), (b), (c), and (d).

(a) *Best usage of waters: fishing, propagation of fish, aquatic life, and wildlife, and any other usage except for swimming and water-contact sports or as a source of water supply for drinking or food-processing purposes.*

(b) *Conditions related to best usage: the waters will be suitable for fish, aquatic life and wildlife propagation. The quality of salt and estuarine waters to which this classification is assigned will also be suitable for the propagation of shrimp and crabs.*

(c) *Other usage of waters: it is recognized that the waters may be used for incidental water contact and recreation during June through September, except that water contact is strongly discouraged in the vicinity of discharges or other conditions beyond the control of the Department or the Alabama Department of Public Health.*

(d) *Conditions related to other usage: the waters, under proper sanitary supervision by the controlling health authorities, will meet accepted standards of water quality for outdoor swimming places and will be considered satisfactory for swimming and other whole body water-contact sports.*

E. coli Criterion:

Criterion for acceptable bacteria levels for the F&W use classification is described in ADEM Admin. Code R. 335-6-10-.09(5)(e)7(i) and (ii) as follows:

7. *Bacteria:*

(i) *In non-coastal waters, bacteria of the E. coli group shall not exceed a geometric mean of 548 colonies/100 ml; nor exceed a maximum of 2,507 colonies/100 ml in any sample. In coastal waters, bacteria of the enterococci group shall not exceed a maximum of 275 colonies/100 ml in any sample. The geometric mean shall be calculated from no less than five samples collected at a given station over a 30-day period at intervals not less than 24 hours.*

(ii) *For incidental water contact and recreation during June through September, the bacterial quality of water is acceptable when a sanitary survey by the controlling health authorities reveals no source of dangerous pollution and when the geometric mean E. coli organism density does not exceed 126 colonies/100 ml nor exceed a maximum of 487 colonies/100 ml in any sample in non-coastal waters. In coastal waters, bacteria of the enterococci group shall not exceed a geometric mean of 35 colonies/100 ml nor exceed a maximum of 158 colonies/100 ml in any sample. The geometric mean shall be calculated from no less than five samples collected at a given station over a 30-day period at intervals not less than 24 hours. When the geometric bacterial coliform organism density exceeds these levels, the bacterial water quality shall be considered acceptable only if a second detailed sanitary survey and evaluation discloses no significant public health risk in the use of the waters. Waters in the immediate vicinity of discharges of sewage or other wastes likely to contain bacteria harmful to*

humans, regardless of the degree of treatment afforded these wastes, are not acceptable for swimming or other whole body water contact sports.

Criteria Exceeded:

Fecal coliform data collected by ADEM in 2000 and 2001 was used for listing Town Branch Creek on Alabama's 2006 §303(d) list. At the time of the listing, the binomial distribution function was employed to calculate the number of exceedances in each range of sample sizes collected over a six year period that exceed the single-sample maximum of 2000 colonies/100 mL. This number is the number of exceedances of the single-sample maximum criterion of 2000 colonies/100 mL for pathogens needed to say with 90% confidence that the criterion is exceeded in more than 10% of the population represented by the available samples. Waters in which samples collected over a six year period exceeding the single-sample maximum of 2000 colonies/100 mL is less than or equal to the allowable exceedances for that sample size or a geometric mean less than or equal to 200 colonies/100 mL (June-September) or 1000 colonies/100 mL (October-May) in at least five samples collected in a thirty day period were considered to comply with Alabama's water quality standard for pathogens. Waters in which the samples collected over a six year period exceeding the single-sample maximum of 2000 colonies/100 mL is greater than the allowable exceedances for that sample size or a geometric mean greater than 200 colonies/100 mL (June-September) or 1000 colonies/100 mL (October-May) in at least five samples collected in a thirty day period were considered impaired and listed for pathogens on Alabama's §303(d) list.

ADEM collected single sample data on Town Branch at TWNW-1 in 2000 and 2001. According to the 2006 §303(d) list fact sheet, Town Branch was listed as impaired based on this pathogen data collected by ADEM in 2000 and 2001 at station TWNW-1. Of 17 samples collected by ADEM in 2000 and 2001 at station TWNW-1, 2 samples exceeded the 2000 colonies/100 ml single sample criterion for fecal coliform causing the stream to be placed on the list of impaired streams.

3.0 Technical Basis for TMDL Development

3.1 Water Quality Target Identification

On December 11, 2009, the Alabama EMC adopted the E. coli criteria as the bacterial indicator to assess the levels of bacteria in freshwater. Prior to the adoption of the E. coli criteria, the fecal coliform criteria were used by ADEM as the bacterial indicator for freshwater. The E. coli criteria was recommended by the EPA as a better correlation to swimming and incidental water contact associated health effects than fecal coliform in the 1986 publication *Quality Criteria for Water*, (EPA 440/5-86-001). As a result of this bacterial indicator change, this TMDL will be developed from E. coli data collected at station TWNW-1 in 2010; even though the 2000 and 2001 data that prompted the listing of Town Branch was based on the fecal coliform criteria.

For the purpose of this TMDL a single sample E. coli target of 438.3 colonies/100 mL will be used. This target was derived by using a 10% explicit margin of safety from the single sample maximum of 487 colonies/100 mL criterion. This target is considered protective of water quality

standards and should not allow the single sample of 487 colonies/100 mL (June-September F&W criteria) to be exceeded.

3.2 Source Assessment

3.2.1 Point Sources in the Town Branch Watershed

A point source can be defined as a discernable, confined, and discrete conveyance from which pollutants are or may be discharged to surface waters. Point source contributions can typically be attributed to municipal wastewater facilities, illicit discharges, and leaking sewers in urban areas. Municipal wastewater treatment facilities are permitted through the National Pollutant Discharge Elimination System (NPDES) process administered by ADEM. In urban settings sewer lines can typically run parallel to streams in the floodplain. If there is a leaking sewer line, high concentrations of E. coli can flow into the stream or leach into the groundwater. Illicit discharges are found at facilities that are discharging E. coli bacteria when they are not permitted, or they are violating their defined permit limit by exceeding the E. coli concentration.

Continuous Point Sources

There is one point source, Camden South WWTP (AL0023680), in the Town Branch watershed which could cause or contribute to the E. coli loading. However, Camden South WWTP discharge is downstream of TWNW-1, the most downstream sampling station and therefore did not contribute to the E. coli exceedances. In addition, Camden South WWTP's Discharge Monitoring Reports (DMRs) confirm that their effluent was meeting their permit limits during the ambient monitoring period and therefore would not have caused or contributed to the E. coli exceedances. The allowable E. coli loading for the point source will be established as a concentration and applied end of pipe.

Any future NPDES regulated discharges that are considered by the Department to be a pathogen source will be required to meet the instream water quality criteria for pathogens at the point of discharge. Currently, Camden South WWTP has pathogen limits in the form of fecal coliform and is also reporting their pathogen data in fecal coliform (col/100 mL). During the next permit re-issuance, the pathogen criterion in the permit needs to be updated to ensure that applicable instream E. coli criterion for Town Branch is maintained.

Non-Continuous Point Sources

Currently there are no Municipal Separate Stormwater Sewer System (MS4) areas located within the Town Branch watershed.

Also, according to the ADEM database, there have been no reported sanitary sewer overflows (SSOs) that have occurred in the Town Branch watershed at the time of the stream sampling. SSOs have the potential to severely impact water quality and can often result in the violation of water quality standards. It is the responsibility of the NPDES wastewater discharger, or collection system operator for non-permitted "collection only" systems, to ensure that releases do not occur. Unfortunately releases to surface waters from SSOs are not always preventable or reported.

Future NPDES regulated stormwater discharges will be required to demonstrate consistency with the assumptions and requirements of this TMDL.

3.2.2 Nonpoint Sources in the Town Branch Watershed

Nonpoint sources of E. coli bacteria do not have a defined discharge point, but rather, occur over the entire length of a stream or waterbody. On the land surface, E. coli bacteria can accumulate over time in the soil and then are washed off during rain events. As the runoff transports the sediment over the land surface, more E. coli bacteria are collected and carried to the stream or waterbody. Therefore, there is some net loading of E. coli bacteria into the stream as dictated by the watershed hydrology.

Due to the absence of point sources above the sampling station, nonpoint sources are believed to be the primary source of E. coli bacteria in the Town Branch watershed. Land use in this watershed is primarily agriculture (pasture/hay and row crops) with 9.73%, and forested with 70.61%.

Agricultural land can be a source of E. coli bacteria. Runoff from pastures, animal feeding areas, improper land application of animal wastes, and animals with direct access to streams are all mechanisms that can contribute E. coli bacteria to waterbodies. To account for the potential influence from animals with direct access to stream reaches in the watershed, E. coli loads can be calculated as a direct source into the stream.

E. coli bacteria can also originate from forested areas due to the presence of wild animals such as deer, raccoons, turkey, waterfowl, etc. Wildlife deposit feces onto land surfaces where it can be transported during rainfall events to nearby streams. Control of these sources is usually limited to land management BMPs and may be impracticable in most cases. As a result, forested areas are not specifically targeted in this TMDL.

E. coli loading from urban areas is potentially attributable to multiple sources including storm water runoff, unpermitted discharges of wastewater, runoff from improper disposal of waste materials, failing septic tanks, and domestic animals. Septic systems are common in unincorporated portions of the watershed and may be direct or indirect sources of bacterial pollution via ground and surface waters. Onsite septic systems have the potential to deliver E. coli bacteria to surface waters due to system failure and malfunction.


3.3 Land Use Assessment

Land use for the Town Branch watershed was determined using ArcView with land use datasets derived from the 2006 National Land Cover Dataset (NLCD). Figure 3-1 and Table 3-1 display the land use areas for the Town Branch watershed. Figure 3-1 is a graph depicting the primary land uses in the Town Branch watershed.

The majority of the Town Branch watershed is 9.73% Agricultural, and 70.61% Forest. Other major land uses include Developed which accounts for approximately 18.97% of the watershed, Open Water which accounts for approximately 0.69%. If not managed properly, agriculture can

have significant nonpoint source impacts. Also, septic systems can be a main source of bacteria if not properly installed and maintained. Developed land includes both commercial and residential land uses.


Figure 3-1. Land Use Map for the Town Branch Watershed



**Table 3-1.
 Land Use Areas for the Town Branch Watershed**

Class Description	Count (30m)	Mi²	Acres	Percent
Open Water	72	0.03	16.01	0.69%
Agricultural Lands	1013	0.35	225.29	9.73%
Forested / Natural	7349	2.55	1634.38	70.61%
Developed Land (Grouped)	1974	0.69	439.01	18.97%
TOTALS →	10408	3.62	2314.69	100.00%

Figure 3-2. Graph of Primary Landuses in the Town Branch Watershed



3.4 Linkage Between Numeric Targets and Sources

The Town Branch watershed has three main landuses, namely developed, forest, and agriculture. Pollutant loadings from forested areas tend to be low due to their filtering capabilities and will be considered as background conditions. The most likely sources of pathogen loadings in Town Branch are from the agricultural land uses, urban run-off from rain events, unpermitted discharges of wastewater, and failing septic systems. It is not considered a logical approach to calculate individual components for nonpoint source loadings. Hence, there will not be individual loads or reductions calculated for the various nonpoint sources. The loadings and reductions will only be calculated as a single total nonpoint source load and reduction.

3.5 Data Availability and Analysis

ADEM collected water quality data for Town Creek at two stations, namely TWNW-1 and TWNW-2. . Of the 17 monthly samples that were collected in 2000 and 2001, 2 samples exceeded the 2000 colonies/100 mL single sample criterion for fecal coliform bacteria. Because the F&W fecal coliform single sample criterion was exceeded, Town Branch was initially placed on the 2006 §303(d) list and subsequently listed on the 2008 and 2010 lists. This data can be viewed in Appendix 7.2, Table 7-1.

In 2010, ADEM again collected water quality data on Town Branch as part of Alabama’s §303(d) Monitoring Program at three stations (TWNW-1, TWNW-2, and TWNW-4). As previously mentioned, the 2010 data will only be used for this assessment because it is less than 6 years old. The January 2010 edition of *Alabama’s Water Quality Assessment and Listing Methodology* section 4.8.2 prepared by ADEM provides the rationale for the Department to use the most recent data to prepare a TMDL for an impaired waterbody when that data indicates a change in water quality has occurred.

Figure 3-3 and Table 3-3 display location and description for the ADEM sampling stations. Of the 16 E. coli samples collected at TWNW-1 in 2010, one violated the single sample F&W maximum criterion of 487 col/100 ml. Of the two samples that qualified for a geometric mean calculation at TWNW-1 in 2010, one geometric mean (7/6/2010 through 7/15/210) exceeded the E.coli criterion of 126 col/100ml. Of the 15 E. coli samples collected at TWNW-2 in 2010, one violated the single sample F&W maximum criterion of 487 col/100 ml. Of the two samples that qualified for a geometric mean calculation at TWNW-2 in 2010, one geometric mean (7/6/2010 through 7/15/210) exceeded the E.coli criterion of 126 col/100ml. The only single sample taken at TWNW-4 was not a violation of the 487 col/100 ml. The geometric mean violation resulted in a 44% reduction, which was lower than the single sample event, therefore will not be used for TMDL development. Flow data was not available for all of the sampling events. Flow data from PURW-2 was used to calculate the flow by using the ratio method. The single sample exceedance event which resulted in the highest percent reduction was used in calculating the E. coli loading to Town Branch (refer to Appendix 7.2, Table 7-2).

**Table 3-2.
 2010 E-Coli Exceedances for the Town Branch Watershed**

Date	Station	Single Sample E-Coli (col/100ml)	Geometric Mean E-Coli (col/100ml)
7/6/2010	TWNW-1	27.5	201.1
7/12/2010	TWNW-1	1413.6	
7/13/2010	TWNW-1	314.0	
7/14/2010	TWNW-1	145.0	
7/15/2010	TWNW-1	186.0	
7/6/2010	TWNW-2	218.7	131.6
7/12/2010	TWNW-2	131.4	
7/13/2010	TWNW-2	165.8	
7/14/2010	TWNW-2	110.6	
7/15/2010	TWNW-2	74.9	
8/11/2010	TWNW-2	448.4	-

Figure 3-3. Map of ADEM Sampling Station on Town Branch




Table 3-3. Town Branch Sampling Station Description

Years	Station ID	Data Source	Station Location	Latitude	Longitude
2000 2001 2010	TWNW-1	ADEM	Town Branch at Camden South WWTP outfall	31.97640	-87.2945
2010	TWNW-2	ADEM	Town Branch at County Road 265	31.98386	-87.28539
2010	TWNW-4	ADEM	Town Branch at AL Highway 10	31.99845	-87.27981

3.6 Critical Conditions

Summer months (June-September) are generally considered critical conditions. This can be explained by the nature of storm events in the summer versus the winter. In summer, periods of dry weather interspersed with thunderstorms allow for the accumulation and washing off of E. coli bacteria into streams, resulting in spikes of E. coli bacteria counts. In winter, frequent low intensity rain events are more typical and do not allow for the build-up of E. coli bacteria on the land surface, resulting in a more uniform loading rate.

The impaired portion of the Town Branch watershed generally follows the trends described above for the summer months of June through September. The critical condition for this pathogen TMDL was taken to be the one with the highest E. coli single sample exceedance value. That value was 1413.6 colonies/100 mL that occurred on July 12, 2010 at station TWNW-1. The flow of 0.37 cfs was used for this sampling event.

3.7 Margin of Safety

There are two methods for incorporating a Margin of Safety (MOS) in the analysis: 1) implicitly incorporate the MOS using conservative model assumptions to develop allocations, or 2) by explicitly specifying a portion of the TMDL as the MOS and using the remainder for allocations.

Both an explicit and implicit MOS was incorporated into this TMDL. The MOS accounts for the uncertainty associated with the limited availability of E. coli data used in this analysis. An explicit MOS was applied to the TMDL by reducing the E. coli target single sample criterion concentration by ten percent and calculating a mass loading target with measured flow data. The single sample criterion was reduced by ten percent to achieve a target concentration of 438.3 colonies/100 mL. An implicit MOS was incorporated in the TMDL by basing the existing condition on the highest measured E. coli concentration that was collected during critical conditions.

4.0 TMDL Development

4.1 Definition of a TMDL

A total maximum daily load (TMDL) is the sum of individual wasteload allocations for point sources (WLAs), load allocations (LAs) for nonpoint sources including natural background levels, and a margin of safety (MOS). The margin of safety can be included either explicitly or implicitly and accounts for the uncertainty in the relationship between pollutant loads and the quality of the receiving waterbody. As discussed earlier, the MOS is explicit in this TMDL. A TMDL can be denoted by the equation:

$$\text{TMDL} = \Sigma \text{WLAs} + \Sigma \text{LAs} + \text{MOS}$$

The TMDL is the total amount of pollutant that can be assimilated by the receiving waterbody while achieving water quality standards under critical conditions.

For some pollutants, TMDLs are expressed on a mass loading basis (e.g. pounds per day). However, for pathogens, TMDL loads are typically expressed in terms of organism counts per day (colonies/day), in accordance with 40 CFR 130.2(i).

4.2 Load Calculations

A mass balance approach was used to calculate the pathogen TMDL for Town Branch. The mass balance approach utilizes the conservation of mass principle. Total mass loads can be calculated by multiplying the E. coli concentration times the instream flow times and a conversion factor. The existing load was calculated for the violation in 2010 that resulted in the highest percent reduction. This violation was a single sample exceedance. In the same manner, the allowable load was calculated for the single sample criterion of 487 colonies/100 mL. Although there were multiple single-sample and geometric mean violations in 2010, the TMDL was based on the highest calculated E. coli load percent reduction to achieve applicable water quality criteria.

Existing Conditions

The **single sample** mass loading was calculated by multiplying the single sample exceedance concentration of 1413.6 colonies/100 ml times the flow of the sample. This concentration was calculated based on measurement at TWNW-1 for the July 12, 2010, and can be found in Table 7-2, Appendix 7.2. The stream flow was 0.37 cfs at the time of the violation. The product of these two values times the conversion factor gives the total mass loading (colonies per day) of E. coli to Town Branch.

$$\frac{0.37 \text{ ft}^3}{\text{s}} \times \frac{1413.6 \text{ colonies}}{100 \text{ mL}} \times \frac{24465755 \text{ } 100 \text{ mL} * \text{s}}{\text{ft}^3 * \text{day}} = \frac{1.28 \times 10^{10} \text{ colonies}}{\text{day}}$$

Allowable Conditions

The **allowable load** to the watershed was calculated under the same physical conditions as discussed above for the single sample criterion. This is done by taking the product of the average flow used for the violation event times the conversion factor times the allowable concentration.

For the **single sample** E. coli target concentration of 438.3 colonies/100 mL. The allowable E. coli loading is:

$$\frac{0.37 \text{ ft}^3}{\text{s}} \times \frac{438.3 \text{ colonies}}{100 \text{ mL}} \times \frac{24465755 \text{ 100 mL} \cdot \text{s}}{\text{ft}^3 \cdot \text{day}} = \frac{3.97 \times 10^9 \text{ colonies}}{\text{day}}$$

The explicit margin of safety of 48.7 colonies/100 mL equals a daily loading of:

$$\frac{0.37 \text{ ft}^3}{\text{s}} \times \frac{48.7 \text{ colonies}}{100 \text{ mL}} \times \frac{24465755 \text{ 100 mL} \cdot \text{s}}{\text{ft}^3 \cdot \text{day}} = \frac{4.41 \times 10^8 \text{ colonies}}{\text{day}}$$

WWTP_{WLA} allowable loading includes Camden South WWTP. Camden South WWTP will have a permitted wasteflow of 0.56 million gallons per day (MGD) and daily maximum effluent E. coli concentration of 487 colonies/100 mL. Allowable mass loading from Camden South WWTP:

$$\frac{0.56 \times 10^6 \text{ gal}}{\text{day}} \times \frac{3785.41 \text{ mL}}{\text{gal}} \times \frac{487 \text{ colonies}}{100 \text{ mL}} = \frac{1.03 \times 10^{10} \text{ colonies}}{\text{day}}$$

The difference in the pathogen loading between the existing condition (violation event) and the allowable condition converted to a percent reduction represents the total load reduction needed to achieve the E. coli water quality criterion. The TMDL was calculated as the total daily E. coli load to Town Branch as evaluated at station TWNW-1 and the permitted load from South Camden WWTP. Table 4-1 shows the result of the E. coli TMDL and percent reduction for the single sample criterion.

Table 4-1. 2010 E. coli Load and Required Reduction

Source	Existing Load (colonies/day)	Allowable Load (colonies/day)	Required Reduction (colonies/day)	% Reduction
Nonpoint Source Load Single Sample	1.28E+10	3.97E+09	8.83E+09	69%
Nonpoint Source Load Geometric Mean	1.13E+09	6.38E+08	4.93E+08	44%
Point Source Load	1.68E+9 ^a	1.74+E10 ^a	0	0%

a. Point Source loads and load reductions are based on current permit limits of Fecal coliform as well as a design flow of 0.56 MGD for Camden South WWTP. Based on these figures, one can conclude that no reductions are necessary to achieve appropriate pathogen loading for the permitted facility.

From Table 4-1, compliance with the single sample criterion of 487 colonies/100 mL requires a reduction in the existing E. coli load of 69%. The TMDL, WLA, LA and MOS values necessary to achieve the applicable E. coli criterion are provided in Table 4-2 below.

Table 4-2. E. coli TMDL for Town Branch

TMDL	Margin of Safety (MOS)	Waste Load Allocation (WLA) ^a			Load Allocation (LA)	
		WWTPs ^b	MS4s ^c	Leaking Collection Systems ^d		
(col/day)	(col/day)	(col/day)	(% reduction)	(col/day)	(col/day)	(% reduction)
1.47E+10	4.41E+08	1.03+E10	NA	0	3.97E+09	69%

Note: NA = not applicable

- a. There are no CAFOs in the Town Branch watershed. Future CAFOs will be assigned a waste load allocation (WLA) of zero.
- b. WLAs for WWTPs are expressed as a daily maximum. Future WWTPs must meet the applicable instream water quality criteria for pathogens at the point of discharge.
- c. Future MS4 areas would be required to demonstrate consistency with the assumptions and requirements of this TMDL.
- d. The objective for leaking collection systems is a WLA of zero. It is recognized, however, that a WLA of 0 colonies/day may not be practical. For these sources, the WLA is interpreted to mean a reduction in E. coli loading to the maximum extent practicable, consistent with the requirement that these sources not contribute to a violation of the water quality criteria for E. coli.
- e. TMDL was established using the single sample criterion of 487 colonies/100ml.

4.3 TMDL Summary

Town Branch was placed on Alabama’s §303(d) list in 2006 based on data collected by ADEM in 2000 and 2001. In 2010, ADEM collected additional water quality data which confirmed the pathogen impairment and provided the basis for TMDL development.

A mass balance approach was used to calculate the E. coli TMDL for Town Branch. Based on the TMDL analysis, it was determined that a 69 % reduction in E. coli loading was necessary to achieve compliance with applicable water quality standards.

Compliance with the terms and conditions of existing and future NPDES sanitary and stormwater permits will effectively implement the WLA and demonstrate consistency with the assumptions and requirements of the TMDL. Required load reductions in the LA portion of this TMDL can be implemented through voluntary measures and may be eligible for CWA §319 grants.

The Department recognizes that adaptive implementation of this TMDL will be needed to achieve applicable water quality criteria, and we are committed towards targeting the load reductions to improve water quality in the Town Branch watershed. As additional data and/or information become available, it may become necessary to revise and/or modify the TMDL accordingly.

5.0 *Follow Up Monitoring*

ADEM has adopted a basin approach to water quality management; an approach that divides Alabama's fourteen major river basins into five groups. Each year, ADEM's water quality resources are concentrated in one of the five basin groups. One goal is to continue to monitor §303(d) listed waters. Monitoring will help further characterize water quality conditions resulting from the implementation of best management practices in the watershed. This monitoring will occur in each basin according to the schedule shown.

Table 5-1. 303(d) Follow Up Monitoring Schedule

River Basin Group	Year to be Monitored
Escatawpa / Mobile / Lower Tombigbee / Upper Tombigbee	2011
Black Warrior/Cahaba	2012
Chattahoochee / Chipola / Choctawhatchee / Perdido-Escambia	2013
Tennessee	2014
Alabama / Coosa / Tallapoosa	2015

6.0 *Public Participation*

As part of the public participation process, this TMDL was placed on public notice and made available for review and comment. The public notice was prepared and published in the four major daily newspapers in Montgomery, Huntsville, Birmingham, and Mobile, as well as submitted to persons who have requested to be on ADEM's postal and electronic mailing distributions. In addition, the public notice and subject TMDL was made available on ADEM's Website: www.adem.state.al.us. The public can also request paper or electronic copies of the TMDL by contacting Mr. Chris Johnson at 334-271-7827 or cljohnson@adem.state.al.us. The public was given an opportunity to review the TMDL and submit comments to the Department in writing. At the end of the public review period, all written comments received during the public notice period became part of the administrative record. ADEM considered all comments received by the public prior to finalization of this TMDL and subsequent submission to EPA Region 4 for final review and approval.

7.0 Appendices

Appendix 7.1 References

ADEM Administrative Code, 2010. Water Division - Water Quality Program, Chapter 335-6-10, Water Quality Criteria.

ADEM Administrative Code, 2010. Water Division - Water Quality Program, Chapter 335-6-11, Use Classifications for Interstate and Intrastate Waters.

Alabama's §303(d) Monitoring Program. 2000, 2001, & 2010. ADEM.

Alabama Department of Environmental Management (ADEM), Alabama's Water Quality Assessment and Listing Methodology, January 2010.

Alabama Department of Environmental Management, 2006 & 2008 §303(d) Lists and Fact Sheets. ADEM.

Alabama Department of Environmental Management (ADEM) Laboratory QA Manual, Chapter 5, Table 5-2: ADEM Laboratory Qualifier Codes and, June 13, 2005.

United States Environmental Protection Agency, 1991. Guidance for Water Quality-Based Decisions: The TMDL Process. Office of Water. EPA 440/4-91-001.

United States Environmental Protection Agency, 1986. Quality Criteria for Water. Office of Water. EPA 440/4-91-001.

Appendix 7.2 Water Quality Data

Table 7-1. ADEM Pathogen Data Collected on Town Branch (2000, 2001)

Station ID	Date	Stream Flow (cfs)	Fecal Coliform (col/100ml)	Fecal Coliform oor
TWNW-1	4/26/2000		76.00	
TWNW-1	5/17/2000		100.00	
TWNW-1	6/7/2000		210.00	
TWNW-1	9/25/2000		440.00	
TWNW-1	1/16/2001		100.00	
TWNW-1	2/20/2001		110.00	
TWNW-1	3/13/2001		3300.00	
TWNW-1	3/20/2001		6000.00	

Table 7-2. 2010 ADEM Pathogen Data with Percent Reductions Collected from Town Branch

Station ID	Date	Stream Flow (cfs)	E Coli (col/100ml)	Percent Reduction (Signal Sample)	E Coli oor	E Coli - Geomean	Percent Reduction (Geomean)
TWNW-1	4/7/10	0.832	31.3				
TWNW-1	5/5/10	2.566	387.3		H		
TWNW-1	6/2/10	0.947	61.3				
TWNW-1	7/6/10	0.279	27.5			201.1	43.62 %
TWNW-1	7/12/10		1413.6	69.00 %			
TWNW-1	7/13/10		314				
TWNW-1	7/14/10		145				
TWNW-1	7/15/10	0.0416	186				
TWNW-1	8/11/10		111.2				
TWNW-1	9/7/10		64.4			74.3	
TWNW-1	9/13/10	0.0737	70.3				
TWNW-1	9/14/10		209.8				
TWNW-1	9/15/10	0.0956	48.7				
TWNW-1	9/16/10	0.0656	48.8				
TWNW-1	10/20/10		224.7				
TWNW-1	11/3/10		34.5		H		
TWNW-2	5/5/10	1.7	755.6		H		
TWNW-2	6/2/10	1.157	101.4				
TWNW-2	7/6/10	0.055	218.7			131.6	13.83 %
TWNW-2	7/12/10		131.4				
TWNW-2	7/13/10		165.8				
TWNW-2	7/14/10	0.0885	110.6				
TWNW-2	7/15/10	0.1076	74.9				
TWNW-2	8/11/10		488.4	10.26 %			
TWNW-2	9/7/10	0.0486	59.8			84.5	
TWNW-2	9/13/10	0.0833	79.4				
TWNW-2	9/14/10		123.6				
TWNW-2	9/15/10	0.1291	113				
TWNW-2	9/16/10	0.1011	65				
TWNW-2	10/20/10		261.3				
TWNW-2	11/3/10	0.196	613.1		H		
TWNW-4	4/7/10		6.3				

H = The analytical hold times for analysis was exceeded.

Appendix 7.3

Town Branch Watershed Photos

Photo 7-1 Town Branch at TWNW-4 (State Route 10)



Photo 7-2 Town Branch at State Route 41



Photo 7-3 Pasture Land/Cattle Access in the Town Branch Watershed



Photo 7-4 Camden South WWTP Lagoon

