

PRELIMINARY DETERMINATION
PERMIT MODIFICATION AND VARIANCE

Perry County Associates, LLC
33 South Wood Ave, Suite 810
Iselin, NJ 08830

Arrowhead Landfill
Permit No. 53-03

October 10, 2025

HHNT, Inc. on behalf of Perry County Associates, LLC, has submitted to the Alabama Department of Environmental Management (ADEM) an application for modification of the Solid Waste Disposal Facility Permit for the Arrowhead Landfill (Permit No. 53-03). The permit modification includes a vertical expansion of the previously approved landfill units, implementation of a landfill gas collection and control system, a proposed renewable natural gas plant, and an updated operations plan. In addition, variances are requested from ADEM Admin. Code 335-13-4-.22(1)(b) and 335-13-4-.20(2)(c)2 requiring operating slopes and final grade not to exceed 25 percent (4:1), and ADEM Admin. Code 335-13-4-.22(1)(c) requiring daily cells not to exceed 8 feet in vertical thickness. The facility would be allowed to operate and close the facility with slopes not exceeding 33 percent (3:1), and completed daily cells may not exceed 15 feet in vertical thickness. A modification of a previously approved variance was requested and would be approved allowing the facility to operate a working face in 2 separate tracts simultaneously. All other permit conditions will remain the same.

The Arrowhead Landfill is located in Sections 21, 22, 27, and 28, Township 17 North, Range 6 East in Perry County, Alabama. The permitted facility consists of 973.85 acres with 425.33 acres permitted for disposal operations.

The Land Division has determined that the permit modification meets the applicable requirements of ADEM's Administrative Code Division 13 regulations.

Technical Contact:

Hunter Baker
Solid Waste Engineering Section
Land Division



SOLID WASTE DISPOSAL FACILITY PERMIT

PERMITTEE: Perry County Associates, LLC

FACILITY NAME: Arrowhead Landfill

FACILITY LOCATION: Sections 21, 22, 27 and 28, Township 17 North, Range 6 East in Perry County. The facility consists of 973.85 acres with a disposal area of 425.33 acres.

PERMIT NUMBER: 53-03

PERMIT TYPE: Municipal Solid Waste Landfill

WASTE APPROVED FOR DISPOSAL: Nonhazardous solid wastes, noninfectious putrescible and nonputrescible wastes including but not limited to household garbage, commercial waste, industrial waste, construction and demolition debris, tires, and other similar type materials. Special waste approved by ADEM may also be accepted.

APPROVED WASTE VOLUME: 15,000 tons per day

APPROVED SERVICE AREA: States of Alabama, Arkansas, Connecticut, Delaware, Florida, Georgia, Illinois, Indiana, Iowa, Kentucky, Louisiana, Maine, Maryland, Massachusetts, Michigan, Minnesota, Mississippi, Missouri, New Hampshire, New Jersey, New York, North Carolina, Ohio, Oklahoma, Pennsylvania, Rhode Island, South Carolina, Tennessee, Texas, Vermont, Virginia, West Virginia and Wisconsin

In accordance with and subject to the provisions of the Alabama Solid Wastes and Recyclable Materials Management Act, as amended, Code of Alabama 1975, SS 22-27-1 to 22-27-27 ("SWRMMA"), the Alabama Environmental Management Act, as amended, Code of Alabama 1975, SS 22-22A-1 to 22-22A-15, and rules and regulations adopted thereunder, and subject further to the conditions set forth in this permit, the Permittee is hereby authorized to dispose of the above-described solid wastes at the above-described facility location.

ISSUANCE DATE: March 3, 2023

EFFECTIVE DATE: March 3, 2023

MODIFICATION DATE: ???

EXPIRATION DATE: March 2, 2033

**ALABAMA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT
SOLID WASTE PERMIT**

Permittee: Perry County Associates, LLC
33 South Wood Ave
Suite 810
Iselin, NJ 08830

Landfill Name: Arrowhead Landfill

Landfill Location: Sections 21, 22, 27 and 28, Township 17 North, Range 6 East in Perry County, Alabama

Permit Number: 53-03

Landfill Type: Municipal Solid Waste

Pursuant to the Alabama Solid Wastes and Recyclable Materials Management Act, Code of Alabama 1975, §§ 22-27-1, *et seq.*, as amended, and attendant regulations promulgated thereunder by the Alabama Department of Environmental Management (ADEM or Department)), this permit is issued to Perry County Associates, LLC (hereinafter called the Permittee), to operate a solid waste disposal facility, known as the Arrowhead Landfill.

The Permittee must comply with all terms and conditions of this permit. This permit consists of the conditions set forth herein (including those in any attachments), and the applicable regulations contained in Chapters 335-13-1 through 335-13-16 of the ADEM Administrative Code (hereinafter referred to as the "ADEM Admin. Code"). Rules cited are set forth in this document for the purpose of Permittee reference. Any Rule that is cited incorrectly in this document does not constitute grounds for noncompliance on the part of the Permittee. Applicable ADEM Administrative Codes are those that are in effect on the date of issuance of this permit or any revisions approved after permit issuance.

This permit is based on the information submitted to the Department on August 5, 2021, for permit renewal and on February 3, 2025, for permit modification, and as amended, and is known as the Permit Application (hereby incorporated by reference and hereinafter referred to as the Application). Any inaccuracies found in this information could lead to the termination or modification of this permit and potential enforcement action. The Permittee must inform ADEM of any deviation from or changes in the information in the Application that would affect the Permittee's ability to comply with the applicable ADEM Admin. Code or permit conditions.

This permit is effective as of **March 3, 2023**, as modified on ???, and shall remain in effect until **March 2, 2033**, unless suspended or revoked.

Alabama Department of Environmental Management

Date Signed

SECTION I. STANDARD CONDITIONS

- A. Effect of Permit. The Permittee is allowed to dispose of nonhazardous solid waste in accordance with the conditions of this permit and ADEM Admin. Code 335-13. Issuance of this permit does not convey property rights of any sort or any exclusive privilege, nor does it authorize any injury to persons or property, any invasion of other private rights, or any infringement of state or local laws or regulations. Except for actions brought under Code of Alabama 1975, §§ 22-27-1, *et seq.*, as amended, compliance with the conditions of this permit shall be deemed to be compliance with applicable requirements in effect as of the date of issuance of this permit and any future revisions.
- B. Permit Actions. This permit may be suspended, revoked or modified for cause. The filing of a request for a permit modification or the notification of planned changes or anticipated noncompliance on the part of the Permittee, and the suspension or revocation does not stay the applicability or enforceability of any permit condition.
- C. Severability. The provisions of this permit are severable, and if any provision of this permit, or the application of any provision of this permit to any circumstance, is held invalid, the application of such provision to other circumstances, and the remainder of this permit, shall not be affected thereby.
- D. Definitions. For the purpose of this permit, terms used herein shall have the same meaning as those in ADEM Admin. Code 335-13, unless this permit specifically provides otherwise; where terms are not otherwise defined, the meaning associated with such terms shall be as defined by a standard dictionary reference or the generally accepted scientific or industrial meaning of the term.
1. "EPA" for purposes of this permit means the United States Environmental Protection Agency.
 2. "Permit Application" for the purposes of this permit, means all permit application forms, design plans, operational plans, closure plans, technical data, reports, specifications, plats, geological and hydrological reports, and other materials which are submitted to the Department in pursuit of a solid waste disposal permit.
- E. Duties and Requirements.
1. Duty to Comply. The Permittee must comply with all conditions of this permit except to the extent and for the duration such noncompliance is authorized by a variance granted by the Department. Any permit noncompliance constitutes a violation of Code of Alabama 1975, §§ 22-27-1 *et seq.*, as amended, and is grounds for enforcement action, permit suspension, revocation, modification, and/or denial of a permit renewal application.
 2. Duty to Reapply. If the Permittee wishes to continue an activity regulated by this permit after the expiration date of this permit, the Permittee must apply for and obtain a new permit. The renewal application must be submitted to the Department at least 180 days before this permit expires.
 3. Permit Expiration. This permit and all conditions therein will remain in effect beyond the permit's expiration date if the Permittee has submitted a timely, complete application as required by Section I.E.2., and, through no fault of the Permittee, the Department has not made a final decision regarding the renewal application.
 4. Need to Halt or Reduce Activity Not A Defense. It shall not be a defense for the Permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity to maintain compliance with the conditions of this permit.
 5. Duty to Mitigate. In the event of noncompliance with this permit, the Permittee shall take all reasonable steps to minimize releases to the environment, and shall carry out such measures as are reasonable to prevent significant adverse impacts on human health or the environment.

6. Proper Operation and Maintenance. The Permittee shall at all times properly operate and maintain all facilities and systems of control (and related appurtenances) that are installed or used by the Permittee to achieve compliance with the conditions of this permit.
7. Duty to Provide Information. If requested, the Permittee shall furnish to ADEM, within a reasonable time, any information that ADEM may reasonably need to determine whether cause exists for denying, suspending, revoking, or modifying this permit, or to determine compliance with this permit. If requested, the Permittee shall also furnish the Department with copies of records kept as a requirement of this permit.
8. Inspection and Entry. Upon presentation of credentials and other documents as may be required by law, the Permittee shall allow the employees of the Department or their authorized representative to:
 - a. Enter at reasonable times the Permittee's premises where the regulated facility or activity is located or conducted, or where records must be kept under the conditions of this permit.
 - b. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit.
 - c. Inspect, at reasonable times, any facilities, equipment (including monitoring and control equipment), practices, or operations regulated or required under this permit.
 - d. Sample or monitor, at reasonable times, any substances or parameters at any location for the purposes of assuring permit compliance or as otherwise authorized by Code of Alabama 1975, §§ 22-27-1 *et seq.*
9. Monitoring, Corrective Actions, and Records.
 - a. Samples and measurements taken for the purpose of monitoring or corrective action shall be representative of the monitored activity. The methods used to obtain representative samples to be analyzed must be the appropriate method from ADEM Admin. Code 335-13-4 or the methods as specified in the Application attached hereto and incorporated by reference. Laboratory methods must be those specified in Standard Methods for the Examination of Water and Wastewater (American Public Health Association, latest edition), Methods for Chemical Analysis of Water and Wastes (EPA-600/4-79-020), Test Methods for Evaluating Solid Waste, Physical/Chemical Methods (EPA Publication SW-846, latest edition), other appropriate EPA methods, or as specified in the Application. All field tests must be conducted using approved EPA test kits and procedures.
 - b. The Permittee shall retain records, at the location specified in Section I.I., of all monitoring, or corrective action information, including all calibration and maintenance records, copies of all reports and records required by this permit, and records of all data used to complete the application for this permit for a period of at least three years from the date of the sample, measurement, report or record or for periods elsewhere specified in this permit. These periods may be extended by the request of the Department at any time and are automatically extended during the course of any unresolved enforcement action regarding this facility.
 - c. Records of monitoring and corrective action information shall include.
 - i. The exact place, date, and time of sampling or measurement.
 - ii. The individual(s) and company who performed the sampling or measurements.
 - iii. The date(s) analyses were performed.

- iv. The individual(s) and company who performed the analyses.
 - v. The analytical techniques or methods used.
 - vi. The results of such analyses.
 - d. The Permittee shall submit all monitoring and corrective action results at the interval specified elsewhere in this permit.
10. Reporting Planned Changes. The Permittee shall notify the Department, in the form of a request for permit modification, at least 120 days prior to any change in the permitted service area, increase in the waste received, or change in the design or operating procedure as described in this permit, including any planned changes in the permitted facility or activity which may result in noncompliance with permit requirements.
 11. Transfer of Permit. This permit may be transferred to a new owner or operator. All requests for transfer of permits shall be in writing and shall be submitted on forms provided by the Department. Before transferring ownership or operation of the facility during its operating life, the Permittee shall notify the new owner or operator in writing of the requirements of this permit.
 12. Certification of Construction. Before the Permittee may commence disposal of waste in any new cell or phase:
 - a. The Permittee must submit a letter to the Department signed by both the Permittee and a professional engineer stating that the facility has been constructed in compliance with the permit.
 - b. The Department must inspect the new cells or phases unless the Permittee is notified that the Department will waive the inspection.
 - c. The Permittee may not commence disposal activities in any new cells or phases until approval of the new cells or phases is granted by the Department.
 13. Noncompliance. The Permittee shall report all instances of noncompliance with the permit at the time noncompliance is discovered.
 14. Other Information. If the Permittee becomes aware that information required by the Application was not submitted or was incorrect in the Application or in any report to the Department, the Permittee shall promptly submit such facts or information. In addition, upon request, the Permittee shall furnish to the Department, within a reasonable time, information related to compliance with the permit.
- F. Design and Operation of Facility. The Permittee shall maintain and operate the facility to minimize the possibility of a fire, explosion, or any unplanned sudden or nonsudden release of contaminants (including leachate and explosive gases) to air, soil, groundwater, or surface water, which could threaten human health or the environment.
- G. Inspection Requirements.
1. The Permittee shall comply with all requirements set forth under ADEM Admin. Code 335- 13-4-.21(1)(b).
 2. The Permittee shall conduct random inspections of incoming loads.
 3. Records of all inspections shall be included in the operating record.

H. Recordkeeping and Reporting.

1. The Permittee shall maintain a written operating record at the location specified in Section I.I. The operating record shall include:
 - a. Documentation of inspection and maintenance activities.
 - b. Daily Volume reports.
 - c. Personnel training documents and records.
 - d. Solid/Hazardous Waste Determination Forms for Industrial Wastes, and associated ADEM disposal approval correspondence for special wastes, industrial wastes, etc.
 - e. Groundwater monitoring records.
 - f. Explosive gas monitoring records.
 - g. Surface water and leachate monitoring records. Monitoring is subject to applicable conditions of Section VII. of the permit.
 - h. Copies of this Permit and the Application.
 - i. Copies of all variances granted by the Department, including copies of all approvals of special operating conditions (such as approvals for open burning,).
2. Quarterly Volume Report. Beginning with the effective date of this permit, the Permittee shall submit, within thirty (30) days after the end of each calendar quarter, a report summarizing the daily waste receipts for the previous (just ended) quarter. Copies of the quarterly reports shall be maintained in the operating record.
3. Monitoring and Corrective Action Reports. The Permittee shall submit reports on all monitoring and corrective activities conducted pursuant to the requirements of this permit, including, but not limited to, groundwater, surface water, explosive gas and leachate monitoring. The groundwater monitoring shall be conducted in March and September of each year and the reports shall be submitted at least semi-annually. The reports should contain all monitoring results and conclusions from samples and measurements conducted during the sampling period. Explosive gas monitoring must be submitted on a quarterly basis, and the reports should be submitted to the Department and placed in the operating record within 30 days of the monitoring event. Copies of the semi-annual groundwater and quarterly explosive gas monitoring reports shall be maintained in the operating record.
4. Availability, Retention, and Disposition of Records.
 - a. All records, including plans, required under this permit or ADEM Admin. Code 335-13 must be furnished upon request, and made available at reasonable times for inspection by any officer, employee, or representative of the Department.
 - b. All records, including plans, required under this permit or ADEM Admin. Code 335-13 shall be retained by the Permittee for a period of at least three years. The retention period for all records is extended automatically during the course of any unresolved enforcement action regarding the facility, or as requested by the Department.
 - c. A copy of records of waste disposal locations and quantities must be submitted to the Department and local land authority upon closure of the facility.

- I. Documents to be Maintained by the Permittee. The Permittee shall maintain, at the Arrowhead Landfill office, the following documents and amendments, revisions and modifications to these documents until an engineer certifies closure of the permitted landfill.
1. Operating record
 2. Closure Plan.
- J. Mailing Location. All reports, notifications, or other submissions which are required by this permit should be sent via signed mail (i.e. certified mail, express mail delivery service, etc.) or hand delivered to:
- Mailing Address.
Chief, Solid Waste Branch, Land Division
Alabama Department of Environmental Management
P.O. Box 301463
Montgomery, AL 36130-1463
- Physical Address.
Chief, Solid Waste Branch, Land Division
Alabama Department of Environmental Management
1400 Coliseum Blvd.
Montgomery, Alabama 36110-2400
- K. Signatory Requirement. All applications, reports or information required by this permit, or otherwise submitted to the Department, shall be signed and certified by the owner as follows:
1. If an individual, by the applicant.
 2. If a city, county, or other municipality or governmental entity, by the ranking elected official, or by a duly authorized representative of that person.
 3. If a corporation, organization, or other legal entity, by a principal executive officer, of at least the level of Vice President, or by a duly authorized representative of that person.
- L. Confidential Information. The Permittee may claim information submitted as confidential pursuant to ADEM Admin. Code 335-1-1-.06.
- M. State Laws and Regulations. Nothing in this permit shall be construed to preclude the initiation of any legal action or to relieve the Permittee from any responsibilities, liabilities, or penalties established pursuant to any applicable state law or regulation.

SECTION II. GENERAL OPERATING CONDITIONS

- A. Operation of Facility. The Permittee shall operate and maintain the disposal facility consistent with the Application, this permit, and ADEM Admin. Code 335-13.
- B. Open Burning. The Permittee shall not allow open burning without prior written approval from the Department and other appropriate agencies. A burn request should be submitted in writing to the Department outlining why that burn request should be granted. This request should include, but not be limited to, specifically what areas will be utilized, types of waste to be burned, the projected starting and completion dates for the project, and the projected days and hours of operation. The approval, if granted, shall be included in the operating record.

- C. Prevention of Unauthorized Disposal. The Permittee shall follow the approved procedures, as provided in the Application, for detecting and preventing the disposal of free liquids, regulated hazardous waste, PCB's, regulated medical waste, and other unauthorized waste streams at the facility.
- D. Unauthorized Discharge. The Permittee shall operate the disposal facility in such a manner that there will be no water pollution or unauthorized discharge. Any discharge from the disposal facility or practice thereof may require a National Pollutant Discharge Elimination System permit under the Alabama Water Pollution Control Act.
- E. Industrial and Medical Waste Disposal. The Permittee shall dispose of industrial process waste as required by ADEM Admin. Code 335-13, and as specified in the Application. The Permittee, prior to disposal of industrial waste and/or medical waste, shall obtain from each generator a written certification that the material to be disposed does not contain free liquids, regulated hazardous wastes, regulated medical waste, or regulated PCB wastes.
- F. Boundary Markers. The Permittee shall ensure that the facility is identified with a sufficient number of permanent boundary markers that are at least visible from one marker to the next.
- G. Certified Operator. The Permittee shall be required to have an operator certified by the Department on-site during hours of operation, in accordance with the requirements of ADEM Admin. Code 335-13-12.

SECTION III. SPECIFIC MSW LANDFILL REQUIREMENTS

- A. Waste Identification and Management.
 - 1. Subject to the terms of this permit, the Permittee may dispose of the nonhazardous solid wastes listed in Section III.B. Disposal of other waste streams is prohibited, except waste that is granted a temporary or one-time waiver by the Director.
 - 2. The total permitted area for the Arrowhead Landfill is 973.85 acres with 425.33 acres (Tract 1 is 117.63 acres, Tract 2 is 159.28 acres, and Tract 3 is 148.42 acres) permitted for disposal operations.
 - 3. The maximum average daily volume of waste disposed at the facility shall not exceed 15,000 tons/day. Should the average daily volume exceed this value by 20% or 100 tons/day, whichever is less, for two (2) consecutive quarters the permittee shall be required to modify the permit in accordance with ADEM Admin. Code 335-13-5-.06(2)(b)2. An increase in maximum average daily volume shall not be approved by ADEM unless the permittee has received local approval for the increased maximum average daily volume. The average daily volume shall be computed as specified by ADEM Admin. Code 335-13-4-.22(2)(g).
- B. Waste Streams. The Permittee may accept for disposal nonhazardous solid wastes, noninfectious putrescible and nonputrescible wastes including but not limited to household garbage, commercial waste, industrial waste, construction and demolition debris, tires, and other similar type materials. Special waste approved by ADEM may also be accepted.
- C. Service Area. The service area for the Arrowhead Landfill as contained in the permit application and approved by the Perry County Commission is the States of Alabama, Arkansas, Connecticut, Delaware, Florida, Georgia, Illinois, Indiana, Iowa, Kentucky, Louisiana, Maine, Maryland, Massachusetts, Michigan, Minnesota, Mississippi, Missouri, New Hampshire, New Jersey, New York, North Carolina, Ohio, Oklahoma, Pennsylvania, Rhode Island, South Carolina, Tennessee, Texas, Vermont, Virginia, West Virginia and Wisconsin.
- D. Special Waste. Disposal of special wastes is subject to a Hazardous/Solid Waste determination by ADEM.
 - 1. Asbestos Waste. The Permittee shall dispose of asbestos waste in accordance with ADEM Admin. Code 335-13-4-.26.

2. Foundry Sand. The Permittee shall dispose of foundry waste in accordance with ADEM Admin. Code 335-13-4-.26.
 3. Petroleum Contaminated Waste. The Permittee shall dispose of petroleum contaminated waste in accordance with ADEM Admin. Code 335-13-4-.26.
 4. Municipal Solid Waste Ash. The Permittee shall dispose of municipal solid waste ash in accordance with ADEM Admin. Code 335-13-4-.26.
- E. Liner Requirements. The Permittee shall install a composite liner system as described in the Application consisting of two feet of clay with a hydraulic conductivity of 1×10^{-7} cm/sec or less, overlain by a 60 mil High Density Polyethylene (HDPE) geomembrane, overlain by an 8 ounce per square yard non-woven geotextile fabric, and overlain by 12" of protective cover with a hydraulic conductivity greater than or equal to 1×10^{-2} cm/sec. The base of the composite liner system shall be a minimum of five (5) feet above the highest measured groundwater level as determined by ADEM Admin. Code 335-13-4-.11(2)(a).
- F. Septic Tank Pumpings and Sewage Sludge. The Permittee shall not dispose of septic tank pumpings and/or sewage sludge unless specifically approved in writing by the Department.
- G. Large Dead Animals and Highly Putrescible Wastes. The Permittee shall handle the disposal of large dead animals and/or highly putrescible waste as required by ADEM Admin. Code 335-13-4-.22(1)(j).
- H. Cover Requirements. The Permittee shall cover all wastes as required by ADEM Admin. Code 335-13. The Permittee has been approved to use synthetic tarps, petroleum contaminated soils, Posi-shell, and automotive shredder residue as alternate daily cover (See Section X.).
- I. Waste Compaction. All waste shall be thoroughly compacted with adequate landfill equipment before the daily cover is applied. A completed daily cell shall not exceed fifteen feet in vertical thickness measured perpendicular to the slope of the preceding cell (See Section X.G).
- J. Daily Cells. All waste shall be confined to an area as small as possible within a single working face (except as described in Section X.A) and spread to a depth not exceeding two feet prior to compaction, and such compaction shall be accomplished on a face slope not to exceed 3 to 1 (See Section X.E). Arrowhead Landfill is granted a variance to operate three working faces. Two working faces have been approved as follows: one working face in each of two separate tracts may be utilized for disposal operations simultaneously. Additionally, a temporary working face has been approved for newly constructed cells. This working face will consist of a fluff layer of selected waste that will protect the integrity of the liner and will only be applicable for newly constructed cells until a sufficiently thick initial fluff lift has been achieved. Each of the working faces should be confined to as small an area as possible.
- K. Security. The Permittee shall provide artificial and/or natural barriers, which prevent entry of unauthorized vehicular traffic to the facility.
- L. All Weather Access Roads. The Permittee shall provide an all-weather access road to the dumping face that is wide enough to allow passage of collection vehicles.
- M. Adverse Weather Disposal. The Permittee shall provide for disposal activities in adverse weather conditions.
- N. Personnel. The Permittee shall maintain adequate personnel to ensure continued and smooth operation of the facility.
- O. Equipment. The Permittee shall provide the landfill equipment as required by ADEM Admin. Code 335-13-4-.22(1)(f).
- P. Environmental Monitoring and Treatment Structures. The Permittee shall provide protection and proper maintenance of environmental monitoring and treatment structures.

- Q. Vector Control. The Permittee shall provide for vector control as required by ADEM Admin. Code 335-13.
- R. Bulk or Noncontainerized Liquid Waste. The Permittee shall not dispose of bulk or noncontainerized liquid waste, or containers capable of holding liquids, unless the conditions of ADEM Admin. Code 335-13-4-.22(1)(k) are met.
- S. Empty Containers. The Permittee shall render empty containers larger than normally found in household waste unsuitable for holding liquids prior to delivery to the landfill unit unless otherwise approved by the Department.
- T. Other Requirements. The Department may enhance or reduce any requirements for operating and maintaining the landfill as deemed necessary by the Land Division.
- U. Other Permits. The Permittee shall operate the landfill according to this and any other applicable permits. Additionally, the Department will verify that the Permittee has obtained a valid permit from the U. S. Army Corps of Engineers regarding an unnamed tributary located within Tract 3 before the construction of Tract 3 may commence.
- V. Scavenging and Salvaging Operations. The Permittee shall prevent scavenging and salvaging operations, except as part of a controlled recycling effort. Any recycling operation must be in accordance with plans submitted and approved by the Department.
- W. Signs. The Permittee shall provide a sign outlining instructions for use of the site. The sign shall be posted and have the information required by ADEM Admin. Code 335-13-4-.22(1)(i).
- X. Litter Control. The Permittee shall control litter.
- Y. Fire Control. The Permittee shall provide fire control measures.

SECTION IV. GROUNDWATER MONITORING REQUIREMENTS

- A. The Permittee shall install and/or maintain a groundwater monitoring system, as specified below.
1. The permittee shall construct and maintain the groundwater monitoring wells identified in Tables IV.1. and IV.4. at the locations and schedules specified in the Application, and any other groundwater monitoring wells which are added (Section IV.A.3.) during the active life and the post closure care period.
 2. The Permittee shall maintain groundwater monitoring wells GWM-1 and GWM-5 as the background groundwater monitoring wells for the entire facility.
 3. The Permittee shall install and maintain additional groundwater monitoring wells as necessary to assess changes in the rate and extent of any plume of contamination or as otherwise deemed necessary to maintain compliance with the ADEM Admin. Code 335-13.
 4. Prior to installing any additional groundwater monitoring wells, the Permittee shall submit a plan to the Department with a permit modification request specifying the design, location and installation of any additional monitoring wells. This plan shall be submitted at least 120 days prior to the installation which, at a minimum, shall include.
 - a. Well construction techniques including proposed casing depths, proposed total depth, and proposed screened interval of well(s);
 - b. Well development method(s);
 - c. A complete analysis of well construction materials;

- d. A schedule of implementation for construction; and
- e. Provisions for determining the lithologic characteristics, hydraulic conductivity and grain-size distribution for the applicable aquifer unit(s) at the location of the new well(s).

B. Groundwater Monitoring Requirements.

- 1. The Permittee shall determine the groundwater surface elevation at each monitoring well and piezometer identified in Table IV.1. each time the well or piezometer is sampled and at least semi-annually throughout the active life and post-closure care period.
- 2. The Permittee shall determine the groundwater flow rate and direction in the first zone of saturation at least annually or each time groundwater is sampled and submit as required by ADEM Admin. Code 335-13.
- 3. Prior to the initial receipt of waste at the facility, the Permittee shall sample, and analyze for the parameters listed in Appendix I of ADEM Admin. Code 335-13-4-.27, and/or any other parameters specified by the Department in Table IV. 2., all monitoring wells identified in Section IV.A.2. to establish background water quality and/or as directed by ADEM Admin. Code 335-13-4-.27(2)(j) and 335-13-4-.27(2)(a)(1).
- 4. The Permittee shall sample and analyze all monitoring wells identified in Table IV.1 for the parameters listed in Table IV.3, on a semi-annual basis throughout the active life of the facility and the post-closure care period in accordance with ADEM Admin. Code 335-13-4-.27(3). Sampling shall be conducted during March and September of each year, beginning with the effective date of this permit. The records and results of this sampling and analysis activity shall be submitted to ADEM, within ninety (90) days of the date of sampling.
- 5. In addition to the requirements of Sections IV., B.1., B.2., B.3. and B.4., the Permittee shall record water levels, mean sea level elevation measuring point, depth to water, and the results of field tests for pH and specific conductance at the time of sampling for each well.

C. Sampling and Analysis Procedures. The Permittee shall use the following techniques and procedures when obtaining and analyzing samples from the groundwater monitoring wells described in Section IV.A. to provide a reliable indication of the quality of the groundwater.

- 1. Samples shall be collected, preserved, and shipped (when shipped off-site for analysis) in accordance with the procedures specified in the Application.
- 2. Samples shall be analyzed according to the procedures specified of the Application, Standard Methods for the Examination of Water and Wastewater (American Public Health Association, latest edition), Methods for Chemical Analysis of Water and Wastes (EPA-600/4-79-020), Test Methods for Evaluating Solid Waste, Physical/Chemical Methods (EPA Publication SW-846, latest edition), or other appropriate methods approved by this Department. All field tests must be conducted using approved EPA test kits and procedures. The Permittee is approved for intrawell statistical analysis.
- 3. Samples shall be tracked and controlled using the chain-of-custody and QA/QC procedures specified in the Application.

D. Recordkeeping and Reporting Requirements.

- 1. Recording of Results. For each sample and/or measurement taken pursuant to the requirements of this permit, the Permittee shall record the information required by Section I.E.9.c.

2. Recordkeeping. Records and results of all groundwater monitoring, sampling, and analysis activities conducted pursuant to the requirements of this permit shall be included in the operating record required by Section I.I.1.
- E. Permit Modification. If at any time the Permittee or the Department determines that the groundwater monitoring system no longer satisfies the requirements of ADEM Admin. Code 335-13-4-.14 or Section IV.A. of this permit, the Permittee must, within 120 days, submit an application for a permit modification to make any necessary and/or appropriate changes to the system.

TABLE IV.1.
INSTALLED GROUNDWATER MONITORING WELLS

Well	Northing	Easting	Top Casing (feet msl)	Surface (feet msl)	Well Type
GWM-1	884667.24	1979482.39	203.37	200.1	Up Grad
GWM-2	876720.18	1978344.96	274.67	271.2	Dn. Grad
GWM-3	877237.63	1977604.4	272.67	269.5	Dn. Grad
GWM-4	877927.07	1976503.62	272.66	269.0	Dn. Grad
GWM-5	883499.74	1976238.62	215.84	212.7	Up Grad
GWM-6	878866.18	1979676.92	262.71	259.1	Dn. Grad
GWM-12	878746.96	1978684.14	276.43	272.9	Dn. Grad
GWM-13	879504.50	1978499.15	262.77	259.1	Dn. Grad
GWM-14	880438.28	1978283.93	238.42	235.1	Dn. Grad
GWM-15	876717.19	1978352.88	274.69	271.2	Dn. Grad
GWM-16	877234.71	1977611.58	272.72	269.5	Dn. Grad
GWM-17	877934.67	1976495.99	273.33	269.4	Dn. Grad
GWM-18	877891.57	1979006.68	286.05	282.6	Dn. Grad

TABLE IV.2.
BACKGROUND GROUNDWATER MONITORING

NOTE: The parameters in this Table are those listed in Appendix I of ADEM Admin. Code 335-13-4.

NOTE: The Permittee shall conduct a minimum of four independent sampling events as the initial sampling event, and analyze for the parameters listed above, in order to establish background water quality. Following the four independent events, the Permittee can submit a request, with justification, for the deletion of or change in these parameters

TABLE IV.3.
SEMI-ANNUAL GROUNDWATER MONITORING PARAMETERS

Boron, Calcium, Chloride, Fluoride, Sulfate, Total Dissolved Solids (TDS), and the parameters listed in Appendix I of ADEM Admin. Code 335-13-4-.27(3)

TABLE IV.4.
GROUNDWATER MONITORING WELLS TO BE INSTALLED

Monitoring Well Number	Top of Casing (feet msl)	Part Monitoring
GWM-7	To be installed	Tract 2
GWM-8	To be installed	Tract 2
GWM-9	To be installed	Tract 2
GWM-10	To be installed	Tract 2
GWM-11	To be installed	Tract 2
GWM-19	To be installed	Tract 2
GWM-20	To be installed	Tract 2
GWM-21	To be installed	Tract 2
GWM-22	To be installed	Tract 2
GWM-23	To be installed	Tract 2
GWM-24	To be installed	Tract 2
GWM-25	To be installed	Tract 2
GWM-26	To be installed	Tract 2
GWM-27	To be installed	Tract 3
GWM-28	To be installed	Tract 3
GWM-29	To be installed	Tract 3
GWM-30	To be installed	Tract 3
GWM-31	To be installed	Tract 3
GWM-32	To be installed	Tract 3
GWM-33	To be installed	Tract 3
GWM-34	To be installed	Tract 3
GWM-35	To be installed	Tract 3
GWM-36	To be installed	Tract 3
GWM-37	To be installed	Tract 3
GWM-38	To be installed	Tract 3
GWM-39	To be installed	Tract 3
GWM-40	To be installed	Tract 3
GWM-41	To be installed	Tract 1

SECTION V. GAS MONITORING REQUIREMENTS

The Permittee must install and maintain an explosive gas monitoring system in accordance with ADEM Admin. Code 335-13.

SECTION VI – MUNICIPAL SOLID WASTE LANDFILL AIR EMISSIONS

This landfill may be subject to ADEM Admin. Code 335-3 and the Federal Clean Air Act. Contact the ADEM Air Division for applicable requirements and permits.

SECTION VII. LEACHATE AND SURFACE WATER MANAGEMENT REQUIREMENTS

The Permittee must collect and dispose of the leachate that is generated at the facility. The Permittee shall install a leachate collection system designed to maintain less than 12 inches (30 cm) depth of leachate over the liner. Prior to disposal, the permittee shall provide the Department with a letter from the receiving publicly or privately owned treatment works, approving the acceptance of the leachate. Discharges to publicly or privately owned treatment works may be subject to the requirements of the ADEM Water Division's State Indirect Discharge (SID) Program. The permittee shall construct and maintain run-on and run-off control structures. Surface water discharges from

drainage control structures shall be permitted through the ADEM Water Division's National Pollutant Discharge Elimination System (NPDES) Program.

Arrowhead Landfill is granted permission for leachate recirculation. Leachate recirculation shall be accomplished through two (2) methods. The first method shall involve loading leachate at the leachate storage tank and hauling it by tanker to the working face where it will be distributed via a spray nozzle. The second method shall involve injecting leachate into the leachate recirculation lines that will be constructed 4' to 6' below the waste surface. Both methods shall distribute leachate at a rate and manner that does not cause runoff, odor, or operation difficulties. Leachate shall not be recirculated during or immediately after rainfall events. Records of leachate recirculation shall be made part of the facility operating record. The maximum daily leachate recirculation shall be 20,000 gpd and shall only be applied where there is a minimum of 20 feet of waste in place (See Section X.D.).

The Permittee is also granted permission to construct an Intermediate Drainage System (Capillary Break) to provide stability to the waste mass in the coal ash disposal area in the Tract 1 Area of the landfill and as depicted on the engineering plans dated July 30, 2010. This Intermediate Drainage System should be constructed with Double Bonded Geocomposite Drainage Media as its primary drainage path. The Geocomposite Drainage Media should be 250 mil thick HDPE geonet material with 6 ounce per square yard non-woven geotextile bonded to the geonet. The proposed system should require the Geocomposite Drainage Media to be placed over a large portion of the Tract 1 area at grades greater than 5% and less than 10% and should be installed approximately 90 vertical feet above the landfill base liner system to promote drainage within the waste mass at that elevation.

SECTION VIII. CLOSURE AND POST- CLOSURE REQUIREMENTS

The Permittee shall close the landfill and perform post-closure care of the landfill in accordance with ADEM Admin. Code 335-13.

- A. Final Cover. The Permittee shall grade final soil cover such that surface water does not pond over the permitted area as specified in the Application. The final cover system as specified in the Application shall consist of 12 inches of compacted soil with a permeability of 1×10^{-5} cm/sec, 40 mil flexible membrane liner, geocomposite drainage system, 18 inches of protective soil, 6 inches of topsoil capable of supporting vegetative cover. The Permittee is granted a variance from ADEM Admin. Code 335-13-4-.20(2)(c)2 requiring that the maximum final grade of the cover system shall not exceed 25 percent. (4:1). The Permittee is approved for 33 percent 3:1 final slopes (See Section X.F).
- B. Vegetative Cover. The Permittee shall establish a vegetative or other appropriate cover, as approved by the Department, within 90 days after completion of final grading requirements in the Application. Preparation of a vegetative cover shall include, but not be limited to, the placement of seed, fertilizer, mulch, and water.
- C. Notice of Intent. The Permittee shall place in the operating record and notify the Department of their intent to close the landfill prior to beginning closure.
- D. Completion of Closure Activities. The Permittee must complete closure activities of each landfill unit in accordance with the Closure Plan within 180 days of the last known receipt of waste.
- E. Certification of Closure. Following closure of each unit, the Permittee must submit to the Department a certification, signed by an independent registered professional engineer, verifying the closure has been completed according to the Closure Plan.
- F. Post-Closure Care Period. Post-closure care activities shall be conducted after closure of each unit throughout the life of this permit and continuing for a period of a minimum of thirty (30) years following closure of the facility. The Department may shorten or extend the post-closure care period applicable to the solid waste disposal facility.

- G. Post-Closure Maintenance. The Permittee shall provide post closure maintenance of the facility to include regularly scheduled inspections. This shall include maintenance of the cover, vegetation, monitoring devices and pollution control equipment and correction of other deficiencies that may be observed by ADEM. Monitoring requirements shall continue throughout the post closure period as determined by the Department unless all waste is removed and no unpermitted discharge to waters of the State have occurred.
- H. Post-Closure Use of Property. The Permittee shall ensure that post closure use of the property never be allowed to disturb the integrity of the final cover, liner, or any other component of the containment system. This shall preclude the growing of deep-rooted vegetation on the closed area.
- I. Certification of Post-Closure. Following post-closure of each unit, the Permittee must submit to the Department a certification, signed by an independent registered professional engineer, verifying the post-closure has been completed according to the Post-Closure Plan.
- J. Recording Instrument. The Permittee must provide documentation of compliance with the requirements of the Uniform Environmental Covenants Program in ADEM Admin. Code 335-5 and shall execute the following:
1. Record a notation onto the land deed within 90 days from the certification of closure. This notation shall state that the land has been used as a solid waste disposal facility, the name of the Permittee, type of disposal activity, location of the disposal facility, and beginning and closure dates of the disposal activity.
 2. File the covenant at the courthouse where the land deed is held within thirty (30) days of receipt of the covenant signed by ADEM's Land Division Chief.
 3. The Permittee shall submit a certified copy of the recording instrument to ADEM within 120 days after permit expiration, revocation, or as directed by ADEM as described in the Application.
- K. Removal of Waste. If the Permittee, or any other person(s), wishes to remove waste, waste residues, the liner, or any contaminated soils, the owner must request and receive prior approval from the Department.

SECTION IX. FINANCIAL ASSURANCE

- A. The Permittee shall maintain detailed written cost estimates, in current dollars, at the landfill office and on file with ADEM in accordance with ADEM Admin. Code 335-13-4-.28.
- B. All cost estimates must be updated annually as required by ADEM Admin Code 335-13-4-28.
- C. The Permittee must place a copy of the financial assurance mechanism along with other items required by ADEM Admin. Code 335-13-4-28. into the landfill operating record and submitted to ADEM before the initial receipt of waste in the case of closure, post-closure care, or no later than 120 days after corrective action remedy has been selected. A copy of this information shall be submitted to ADEM in accordance with ADEM Admin. Code 335-13-4-.28(5).
- D. The financial assurance mechanisms must ensure that funds will be available in a timely fashion when needed.
- E. The financial assurance mechanisms must be legally valid, binding, and enforceable under state and federal law.
- F. The Permittee shall demonstrate continuous compliance with ADEM Admin. Code 335-13-4-28. by providing documentation of financial assurance in at least the amount that equals or exceeds the cost estimate. Changes in the financial assurance mechanism must be approved by the Department.

- G. The Permittee shall increase the closure, post-closure or corrective action cost estimates and the amount of financial assurance if changes in the closure, post-closure or correction action plans or landfill conditions increase the maximum cost.
- H. The Permittee may reduce the amount of financial assurance by submitting justification and a revised estimate to ADEM for approval.

SECTION X. VARIANCES AND SPECIAL CONDITIONS

- A. A variance is granted for the Arrowhead Landfill from ADEM Admin. Code 335-13-4-.22.(1)(b) which states that all waste shall be confined to as small an area as possible. Under this variance, the Arrowhead Landfill is allowed to operate three working faces. Two working faces have been approved as follows: one working face in each of two separate tracts may be utilized for disposal operations simultaneously. Additionally, a temporary working face has been approved for newly constructed cells. This working face will consist of a fluff layer or selected waste that will protect the integrity of the liner and will only be applicable for newly constructed cells until a sufficiently thick initial fluff lift has been achieved. Each of the working faces should be confined to as small an area as possible. (See Section III.J.)
- B. A variance is granted from ADEM Admin. Code 335-13-4-.20(2)(c)3. requiring terraces every 20 feet rise in elevation. This variance requires terraces every 40 feet rise in elevation.
- C. The Permittee is allowed to solidify waste within the waste solidification mixing pit constructed as shown in the Application. Solidification shall follow the procedures specified in the Application. The solidification mixing pit shall be located within a lined cell area at all times.
- D. Arrowhead Landfill is granted permission for leachate recirculation. Leachate recirculation should be accomplished through two (2) methods. The first method should involve loading leachate at the leachate storage tank and hauling it by tanker to the working face where it will be distributed via a spray nozzle. The second method should involve injecting leachate into the leachate recirculation lines that will be constructed 4' to 6' below the waste surface. Both methods should distribute leachate at a rate and manner that does not cause runoff, odor, or operation difficulties. Leachate should not be recirculated during or immediately after rainfall events. Also, care should be taken to ensure that no more leachate is applied than the facility can manage. Records of leachate recirculation should be made part of the facility operating record. The maximum daily leachate recirculation should be 20,000 gallons per day and should only be applied where there is a minimum of 20 feet of waste in place (See Section VII).
- E. The Permittee is granted a variance from ADEM Admin. Code 335-13-4-.22(1)(b) requiring that the working face slope not exceed 4 to 1 (25%). The Permittee is approved to operate the working faces at a slope not to exceed 3 to 1 (33%) (See Section III., J.).
- F. The Permittee has been approved to use synthetic tarps as alternate daily cover. The Synthetic Tarps used should be at least 50' x 75' and shall be LandPac Tarps by Pactec or an equivalent. At the conclusion of each week's operation, the Permittee shall be required to cover all exposed waste with a minimum of six inches of compacted earth (See Section III. H.).
- G. The Permittee has been approved to use petroleum contaminated soil (PCS) as alternate daily cover. The maximum petroleum contaminant level of the soil that will be used as alternative daily cover material should be 100 parts per million (ppm) of Total Petroleum Hydrocarbons (TPH). The PCS should be used in the same manner as soil daily cover; covering the waste with a uniform compacted 6" thick layer. PCS should be stockpiled within the cell away from daily traffic and operations in such a manner that rainwater runoff will not leave the limits of the lined cell area. All run-off from PCS shall be contained within the lined cell (See Section III. H.).
- H. The Permittee has been approved to use Posi-shell as alternate daily cover. The Posi-shell will be spray-applied using a standard hydro seeding unit. The application thickness should be approximately 1/8" and

should not be applied during extremely wet weather. During these extremely wet times, daily soil should be used to cover the waste. At the conclusion of each week's operation, the Permittee shall be required to cover all exposed waste with a minimum of six inches of compacted earth (See Section III. H.).

- I. The Permittee has been approved to use automotive shredder residue (ASR) as alternate daily cover. ASR as it is commonly known is the non-metal waste generated after junked vehicles go through auto shredders. It is a mixture of crushed glass, ceramics, cloth, rubber, plastic, foam, wood, and air bags. About 25 percent of a shredded vehicle is ASR. Metal components, which are sold for reuse in new products, make up the remainder. ASR should be used in a 6" thick blanket in a manner similar to soil. ASR should not be used during rainfall events or on exterior slopes where run-off from the ASR could leave the cell. All run-off from ASR shall be contained within the lined cell. At the conclusion of each week's operation, the Permittee shall be required to cover all exposed waste with a minimum of six inches of compacted earth (See Section III. H.).
- J. The Permittee is granted a variance from ADEM Admin. Code 335-13-4-.20(2)(c)2. requiring that the maximum final grade of the cover system shall not exceed 25 percent. (4:1). The Permittee is approved for 33 percent (3:1) final slopes (See Section VIII.A).
- K. The Permittee has been granted a variance from ADEM Admin. Code 335-13-4-.22(1)(c) requiring that a completed daily cell shall not exceed eight feet in vertical thickness measured perpendicular to the slope of the preceding cell. A completed daily cell shall not exceed fifteen feet in vertical thickness measured perpendicular to the slope of the preceding cell (See Section III., I.).

Any variance granted by the Department may be terminated by the Department whenever the Department finds, after notice and opportunity for hearing, that the petitioner is in violation of any requirement, condition, schedule, limitation or any other provision of the variance, or that operation under the variance does not meet the minimum requirements established by state and federal laws.