



MAJOR SOURCE OPERATING PERMIT

PERMITTEE:

INTEGRITY CABINETS, LLC

FACILITY/PERMIT

NO.:

304-0011

LOCATION:

ASHLAND, ALABAMA

In accordance with and subject to the provisions of the Alabama Air Pollution Control Act of 1971, <u>Ala. Code</u> §§ 22-28-1 to 22-28-23, as amended, the Alabama Environmental Management Act, <u>Ala. Code</u> §§ 22-22A-1 to 22-22A-17, as amended, and rules and regulations adopted there under, and subject further to the conditions set forth in this permit, the Permittee is hereby authorized to construct, install and use the equipment, device or other article described above.

Pursuant to the **Clean Air Act of 1990**, all conditions of this permit are federally enforceable by EPA, the Alabama Department of Environmental Management, and citizens in general. Those provisions which are not required under the **Clean Air Act of 1990** are considered to be state permit provisions and are not federally enforceable by EPA and citizens in general. Those provisions are contained in separate sections of this permit.

Issuance Date:

March 7, 2026

Effective Date:

March 7, 2026

Expiration Date:

March 6, 2031

TABLE OF CONTENTS

General Permit Provisos	-
Provisos	03
Operating Permit Summary No. 1	13
SURFACE COATING OPERATION	
Operating Permit Summary No. 2 OFF-LINE BOOTH(S)	16
Operating Permit Summary No. 4 WOODWORKING OPERATIONS WITH CYCLON	

Fede	rally Enforceable Provisos	Regulations
1.	Transfer	
	This permit is not transferable, whether by operation of law or otherwise, either from one location to another, from one piece of equipment to another, or from one person to another, except as provided in Rule 335-3-1613(1)(a)5.	Rule 335-3-1602(6)
2.	Renewals	
	An application for permit renewal shall be submitted at least six (6) months, but not more than eighteen (18) months, before the date of expiration of this permit.	Rule 335-3-1612(2)
	The source for which this permit is issued shall lose its right to operate upon the expiration of this permit unless a timely and complete renewal application has been submitted within the time constraints listed in the previous paragraph.	
3.	Severability Clause	
	The provisions of this permit are declared to be severable and if any section, paragraph, subparagraph, subdivision, clause, or phrase of this permit shall be adjudged to be invalid or unconstitutional by any court of competent jurisdiction, the judgment shall not affect, impair, or invalidate the remainder of this permit, but shall be confined in its operation to the section, paragraph, subparagraph, subdivisions, clause, or phrase of this permit that shall be directly involved in the controversy in which such judgment shall have been rendered.	Rule 335-3-1605(5)
4.	Compliance	
	(a) The permittee shall comply with all conditions of ADEM Admin. Code 335-3. Noncompliance with this permit will constitute a violation of the Clean Air Act of 1990 and ADEM Admin. Code 335-3 and may result in an enforcement action; including but not limited to, permit termination, revocation and reissuance, or modification; or denial of a permit renewal application by the permittee.	Rule 335-3-1605(6)
	(b) The permittee shall not use as a defense in an enforcement action that maintaining compliance with conditions of this permit would have required halting or reducing the permitted activity.	Rule 335-3-1605(7)

Fede	erally Enforceable Provisos	Regulations
5.	Termination for Cause	
	This permit may be modified, revoked, reopened, and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or of a notification of planned changes or anticipated noncompliance will not stay any permit condition.	, Rule 335-3-1605(8)
6.	Property Rights	
	The issuance of this permit does not convey any property rights of any sort, or any exclusive privilege.	Rule 335-3-1605(9)
7.	Submission of Information	
	The permittee must submit to the Department, within 30 days or for such other reasonable time as the Department may set, any information that the Department may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit or to determine compliance with this permit. Upon receiving a specific request, the permittee shall also furnish to the Department copies of records required to be kept by this permit.	Rule 335-3-1605(10)
8.	Economic Incentives, Marketable Permits, and Emissions Trading	
	No permit revision shall be required, under any approved economic incentives, marketable permits, emissions trading and other similar programs or processes for changes that are provided for in this permit.	Rule 335-3-1605(11)
9.	Certification of Truth, Accuracy, and Completeness:	
	Any application form, report, test data, monitoring data, or compliance certification submitted pursuant to this permit shall contain certification by a responsible official of truth, accuracy, and completeness except as provided in Rule 335-3-1604(9)(b). This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate and complete.	Rule 335-3-1607(1)

Fede	rally E	nforceable Provisos	Regulations
10.	Inspe	ection and Entry	
	may l	presentation of credentials and other documents as be required by law, the permittee shall allow authorized sentatives of the Alabama Department of conmental Management and EPA to conduct the ring:	Rule 335-3-1607(2)
	(a)	Enter upon the permittee's premises where a source is located or emissions-related activity is conducted, or where records must be kept pursuant to the conditions of this permit;	
	(b)	Review and/or copy, at reasonable times, any records that must be kept pursuant to the conditions of this permit;	
	(c)	Inspect, at reasonable times, this facility's equipment (including monitoring equipment and air pollution control equipment), practices, or operations regulated or required pursuant to this permit;	
	(d)	Sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with this permit or other applicable requirements.	
11.	Com	pliance Provisions	
	(a)	The permittee shall continue to comply with the applicable requirements with which the company has certified that it is already in compliance.	Rule 335-3-1607(3)
	(b)	The permittee shall comply in a timely manner with applicable requirements that become effective during the term of this permit.	
12.	Com	pliance Certification	
	A compliance certification shall be submitted annually within 60 days of the date of issuance of this permit.		Rule 335-3-1607(5)
•	(a)	The compliance certification shall include the following:	
		(1) The identification of each term or condition of this permit that is the basis of the certification;	
		(2) The compliance status;	

Fede	rally E	iforceable Provisos	Regulations
		(3) The method(s) used for determining the compliance status of the source, currently and over the reporting period consistent with Rule 335-3-1605(3) (Monitoring and Record Keeping Requirements);	
		(4) Whether the method(s) or other means used to assure compliance provided continuous or intermittent data;	<u></u>
		(5) Such other facts as the Department may require to determine the compliance status of the source;	
	(b)	The compliance certification shall be submitted to :	
	Alaba	ima Department of Environmental Management Air Division P.O. Box 301463 Montgomery, AL 36130-1463 and to:	
13.	Reope	Air Enforcement and TOXICS Branch EPA Region 4 61 Forsyth Street, SW Atlanta, GA 30303 ening for Cause	
		any of the following circumstances, this permit will be ned prior to the expiration of the permit:	Rule 335-3-1613(5)
	(a)	Additional applicable requirements under the Clean Air Act of 1990 become applicable to the permittee with a remaining permit term of three (3) or more years. Such a reopening shall be completed not later than eighteen (18) months after promulgation of the applicable requirement. No such reopening is required if the effective date of the requirement is later than the date on which this permit is due to expire.	
	(b)	Additional requirements (including excess emissions requirements) become applicable to an affected source under the acid rain program. Upon approval by the Administrator, excess emissions offset plans shall be deemed to be incorporated into this permit.	

Regulations Federally Enforceable Provisos The Department or EPA determines that this permit (c) contains a material mistake or that inaccurate statements were made in establishing the emissions standards or other terms or conditions of this permit. The Administrator or the Department determines that (d) this permit must be revised or revoked to assure compliance with the applicable requirements. Additional Rules and Regulations 14. §22-28-16(d), Code of This permit is issued on the basis of Rules and Regulations existing on the date of issuance. In the event additional Alabama 1975, as Rules and Regulations are adopted, it shall be the permit amended holder's responsibility to comply with such rules. **15**. Equipment Maintenance or Breakdown In case of shutdown of air pollution control Rule 335-3-1-.07(1),(2) (a) equipment for scheduled maintenance, the intent to shut down shall be reported to the Department at least 24 hours prior to the planned shutdown, unless such shutdown is accompanied by the shutdown of the source which such equipment is intended to The Department shall be notified when control. maintenance on the air pollution control equipment is complete and the equipment is operating. In the event that there is a breakdown of equipment (b) or upset of process in such a manner as to cause, or is expected to cause, increased emissions of air contaminants which are above an applicable standard, the person responsible for such equipment shall notify the Director within 24 hours or the next working day and provide a statement giving all pertinent facts, including the estimated duration of the breakdown. The Director will be notified when the breakdown has been corrected. Operation of Capture and Control Devices 16. All air pollution control devices and capture systems for §22-28-16(d), Code of which this permit is issued shall be maintained and Alabama 1975, as operated at all times in a manner so as to minimize the amended emissions of air contaminants. Procedures for ensuring that the above equipment is properly operated and maintained so as to minimize the emission of air contaminants shall be

established.

Fede	rally E	nforc	ceable Provisos	Regulations
17.	Obno	xious	s Odors	
	obno verifi odoro the	xious ed by ous er Alabar these	nit is issued with the condition that, should odors arising from the plant operations be Air Division inspectors, measures to abate the missions shall be taken upon a determination by ma Department of Environmental Management e measures are technically and economically	Rule 335-3-108
18.	Fugitive Dust		<u>Oust</u>	
	(a)	ema	cautions shall be taken to prevent fugitive dust mating from plant roads, grounds, stockpiles, eens, dryers, hoppers, ductwork, etc.	Rule 335-3-402
	(b)	in t	nt or haul roads and grounds will be maintained he following manner so that dust will not become forne:	
		(1)	By the application of water any time the surface of the road is sufficiently dry to allow the creation of dust emissions by the act of wind or vehicular traffic;	
		(2)	By reducing the speed of vehicular traffic to a point below that at which dust emissions are created;	
		(3)	By paving;	
		(4)	By the application of binders to the road surface at any time the road surface is found to allow the creation of dust emissions; or	
		(5)	By any combination of the above methods which results in the prevention of dust becoming airborne from the road surface.	
19.	<u>Adđi</u>	<u>tions</u>	and Revisions	
	-		fications to this source shall comply with the on procedures in Rules 335-3-1613 or 335-3-16-	
20.	Reco	rdkee	eping Requirements	
	(a)		ords of required monitoring information of the rce shall include the following:	Rule 335-3-1605(3)(b)

The date, place, and time of all sampling or measurements; The date analyses were performed; The company or entity that performed the analyses; The analytical techniques or methods used; The results of all analyses; and The operating conditions that existed at the time of sampling or measurement. Itention of records of all required monitoring data d support information of the source for a period of least 5 years from the date of the monitoring mple, measurement, report, or application. Inport information includes all calibration and aintenance records and all original strip-chart	
The company or entity that performed the analyses; The analytical techniques or methods used; The results of all analyses; and The operating conditions that existed at the time of sampling or measurement. Itention of records of all required monitoring data d support information of the source for a period of least 5 years from the date of the monitoring mple, measurement, report, or application. Import information includes all calibration and anintenance records and all original strip-chart	
analyses; The analytical techniques or methods used; The results of all analyses; and The operating conditions that existed at the time of sampling or measurement. Itention of records of all required monitoring data d support information of the source for a period of least 5 years from the date of the monitoring mple, measurement, report, or application. Import information includes all calibration and anintenance records and all original strip-chart	
The results of all analyses; and The operating conditions that existed at the time of sampling or measurement. Itention of records of all required monitoring data d support information of the source for a period of least 5 years from the date of the monitoring mple, measurement, report, or application. Import information includes all calibration and anintenance records and all original strip-chart	
The operating conditions that existed at the time of sampling or measurement. Itention of records of all required monitoring data d support information of the source for a period of least 5 years from the date of the monitoring mple, measurement, report, or application apport information includes all calibration and aintenance records and all original strip-chart	
time of sampling or measurement. tention of records of all required monitoring data d support information of the source for a period of least 5 years from the date of the monitoring mple, measurement, report, or application apport information includes all calibration and aintenance records and all original strip-chart	
d support information of the source for a period of least 5 years from the date of the monitoring mple, measurement, report, or application apport information includes all calibration and aintenance records and all original strip-chart	
cordings for continuous monitoring strumentation and copies of all reports required by e permit	
ng Requirements	
eports to the Department of any required monitoring all be submitted at least every 6 months. All stances of deviations from permit requirements ust be clearly identified in said reports. All required ports must be certified by a responsible official nsistent with Rule 335-3-1604(9).	
ported within 48 hours or 2 working days of such eviations, including those attributable to upset anditions as defined in the permit. The report will clude the probable cause of said deviations, and	
p n ev p v n c	orts must be certified by a responsible official asistent with Rule 335-3-1604(9). viations from permit requirements shall be corted within 48 hours or 2 working days of such viations, including those attributable to upset additions as defined in the permit. The report will

22. Emission Testing Requirements

Feder	ally Enforceable Provisos	Regulations
	Each point of emission which requires testing will be provided with sampling ports, ladders, platforms, and other safety equipment to facilitate testing performed in accordance with procedures established by Part 60 of Title 40 of the Code of Federal Regulations, as the same may be amended or revised.	Rule 335-3-105(3) and Rule 335-3-1- .04(1)
	The Air Division must be notified in writing at least 10 days in advance of all emission tests to be conducted and submitted as proof of compliance with the Department's air pollution control rules and regulations.	
	To avoid problems concerning testing methods and procedures, the following shall be included with the notification letter:	
	1. The date the test crew is expected to arrive, the date and time anticipated of the start of the first run, how many and which sources are to be tested, and the names of the persons and/or testing company that will conduct the tests.	Rule 335-3-104
	2. A complete description of each sampling train to be used, including type of media used in determining gas stream components, type of probe lining, type of filter media, and probe cleaning method and solvent to be used (if test procedures requires probe cleaning).	
	3. A description of the process(es) to be tested including the feed rate, any operating parameters used to control or influence the operations, and the rated capacity.	
	4. A sketch or sketches showing sampling point locations and their relative positions to the nearest upstream and downstream gas flow disturbances.	
	A pretest meeting may be held at the request of the source owner or the Air Division. The necessity for such a meeting and the required attendees will be determined on a case-by- case basis.	Rule 335-3-104
	All test reports must be submitted to the Air Division within 30 days of the actual completion of the test unless an extension of time is specifically approved by the Air Division.	
23.	Payment of Emission Fees	
	Annual emission fees shall be remitted each year according to the fee schedule in ADEM Admin. Code R. 335-1-704.	Rule 335-1-704
24.	Other Reporting and Testing Requirements	

Fede	rally E	nforceable Provisos	Regulations
<u> </u>	fuel a may pollut may r	ission of other reports regarding monitoring records, malyses, operating rates, and equipment malfunctions be required as authorized in the Department's airtion control rules and regulations. The Department require emission testing at any time. VI Requirements (Refrigerants)	Rule 335-3-104(1)
40.			005 0 16 05/1)
	include Class 82, S and pract certifi	facility having appliances or refrigeration equipment, ding air conditioning equipment, which use Class I or II ozone-depleting substances as listed in 40 CFR Part Subpart A, Appendices A and B, shall service, repair, maintain such equipment according to the work ices, personnel certification requirements, and ied recycling and recovery equipment specified in 40 Part 82, Subpart F.	335-3-1605(1)
	Class the re	erson shall knowingly vent or otherwise release any I or Class II substance into the environment during epair, servicing, maintenance, or disposal of any device of as provided in 40 CFR Part 82, Subpart E.	
	recor	responsible official shall comply with all reporting and dkeeping requirements of 40 CFR 82.166. Reports be submitted to the US EPA and the Department as red.	
26.	Chen	nical Accidental Prevention Provisions	
	prese	chemical listed in Table 1 of 40 CFR Part 68.130 is ent in a process in quantities greater than the threshold tity listed in Table 1, then:	40 CFR Part 68
	(a)	The owner or operator shall comply with the provisions in 40 CFR Part 68.	,
	(b)	The owner or operator shall submit one of the following:	
		(1) A compliance schedule for meeting the requirements of 40 CFR Part 68 by the date provided in 40 CFR Part 68 § 68.10(a) or,	
		(2) A certification statement that the source is in compliance with all requirements of 40 CFR Part 68, including the registration and submission of the Risk Management Plan.	

Fede	rally Enforceable Provisos	Regulations
27.	Display of Permit	
	This permit shall be kept under file or on display at all times at the site where the facility for which the permit is issued is located and will make the permit readily available for inspection by any or all persons who may request to see it.	Rule 335-3-1401(1)(d)
28.	Circumvention	Ĺ
	No person shall cause or permit the installation or use of any device or any means which, without resulting in the reduction in the total amount of air contaminant emitted, conceals or dilutes any emission of air contaminant which would otherwise violate the Division 3 rules and regulations.	Rule 335-3-110
29.	<u>Visible Emissions</u>	
	Unless otherwise specified in the Unit Specific provisos of this permit, any source of particulate emissions shall not discharge more than one 6-minute average opacity greater than 20% in any 60-minute period. At no time shall any source discharge a 6-minute average opacity of particulate emissions greater than 40%. Opacity will be determined by 40 CFR Part 60, Appendix A, Method 9, unless otherwise specified in the Unit Specific provisos of this permit.	Rule 335-3-401(1)
30.	Fuel-Burning Equipment	
	Unless otherwise specified in the Unit Specific provisos of this permit, no fuel-burning equipment may discharge particulate emissions in excess of the emissions specified in Part 335-3-403.	Rule 335-3-403
	Unless otherwise specified in the Unit Specific provisos of this permit, no fuel-burning equipment may discharge sulfur dioxide emissions in excess of the emissions specified in Part 335-3-501.	Rule 335-3-501
31.	Process Industries - General	
	Unless otherwise specified in the Unit Specific provisos of this permit, no process may discharge particulate emissions in excess of the emissions specified in Part 335-3-404.	Rule 335-3-404
32.	Averaging Time for Emission Limits	
	Unless otherwise specified in the permit, the averaging time for the emission limits listed in this permit shall be the normal time required by the specific test method.	Rule 335-3-105

Emission Unit(s):

Surface Coating Operation ton: 001

Designation No(s). in Application:

Description:

Hand rolled floor and automated overhead conveyor that feeds a stain booth, a small heat tunnel, followed by a sealer booth, a small heat tunnel, another sealer booth, a topcoat booth,

and finishing with a small heat tunnel.

Type and quantity of fuel used:

Primary:

None

Secondary:

None

Z O Z Z CON 1 1 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	The state of the s	
Pollutant	Regulatory Emission Limit	Applicable Standard
VOCs	245 TONS OF VOCS PER	SYNTHETIC MINOR PSD
	ROLLING 12 MONTH PERIOD	<u>·</u>
HAPs	0.8 LB VHAPs/POUND	MACT
	SOLIDS AT THE APPLICATOR	
	FOR ALL COATINGS	

Unit Specific Provisos

Fede	rally Enforceable Provisos	Regulations
Secti	on 1Applicability	
1.	This source is subject to the applicable requirements of ADEM Admin. Code R. 335-3-1603, "Major Source Operating Permits."	ADEM Admin. Code R. 335-3-16.03
2.	This source is subject to the National Emission Standards for Hazardous Air Pollutants (NESHAPs) for Hazardous Air Pollutant (HAP) Emissions from Wood Furniture Manufacturing Operations as an "New Source" as listed in 40 CFR Part §63 Subpart JJ, to include 40 CFR Part §63.800(a) among other requirements.	
3.	This source is subject to a PSD synthetic minor emission limitation.	ADEM Admin. Code R. 335-3-1404
Secti	on 2Emission Standards	
1.	This facility shall not emit a weighted average of greater than 0.8 pound of VHAPs per pound of solids as delivered to the applicator for all coatings as determined by a monthly average as listed in Table 3 of 40 CFR Part §63 Subpart JJ, among other requirements. The facility is currently complying with this requirement with compliant coatings.	ADEM Admin. Code R. 335-3-1106(35)
2.	Emission of Volatile Organic Compounds (VOCs) from all surface coating operations from this facility, including, but not limited to coating, storage, cleanup, etc., shall not exceed 245 tons per year (TPY) in any consecutive rolling 12-month period based on the premise that all VOCs applied are emitted.	ADEM Admin. Code R. 335-3-1404(8)
3.	This facility is subject to the applicable work practice standards of 40 CFR Part 63 Subpart JJ §63.803 "National Emission Standards for Wood Furniture Manufacturing Operations" to include §63.803 (a) through (l).	

Fede	erally E	Regulations	
Section 3Compliance and Performance Test Methods and			
Proc	edures		
1.	mater Metho Vendo	OC content by weight of each VOC containing rial used shall be determined using EPA Test od 24, as defined in 40 CFR 60, Appendix A. or data based on this method is an appropriate situte.	ADEM Admin. Code R. 335-3-104
2.	of 40 Emis	source is subject to the applicable testing methods CFR Part 63 Subpart JJ §63.805, "National sion Standards for Wood Furniture Manufacturing ations" to include §63.805 (a).	ADEM Admin. Code R. 335-3-1106(35)
3.	proce "Nation" Manu	source is subject to the applicable compliance dures of 40 CFR Part 63 Subpart JJ §63.804, onal Emission Standards for Wood Furniture afacturing Operations" to include §63.804 (a) agh (c), (f), and (g).	ADEM Admin. Code R. 335-3-1106(35)
Sec	tion 4E	Emission Monitoring	
1.	requi	nonitoring requirements in this permit shall be as red in Section 5Recordkeeping and Reporting irements.	
Sec	tion 5F	Recordkeeping and Reporting Requirements	
1.	cons of da suita upon recor requ	rate and understandable monthly records of umption, which record at least the last five years ta, will be maintained in a permanent form ble for inspection and be available immediately request. This facility shall provide a copy of ds and supporting background documents upon est that pertain to this air permit. These records contain the following information:	ADEM Admin. Code R. 335-3-104
	(a)	The type, quantity in gallons, and weight in pounds of each VOC or HAP containing material used during each calendar month.	
	(b)	The percent by weight of VOCs, water, solids, VHAPs, and exempt VOC compounds content of each VOC containing material used each calendar month.	
	(c)	The percent by volume of VOCs, water, solids, VHAPs,	

Fede	rally l	Enforceable Provisos	Regulations
		and exempt VOC compounds content of each VOC containing material used each calendar month.	
	(d)	Compliance with VOC and VHAP limits shall be based upon monthly material use inventories. Emissions may be adjusted for VOC and VHAP content of material removed from the plant as waste or returns if the record keeping and details surrounding the materials are approved in advance.	
	(e)	Complete inventories of the VOC and HAP containing materials (their usage, VOC content and VHAP content) shall be made at the end of each calendar month.	
	(f)	The amount of VOCs emitted per calendar month from the coating and cleaning operations in units of pounds and tons	
	(g)	The rolling 12-month total of VOCs emitted from the coating and cleaning operations in units of pounds and tons.	
2.	provi by th	nonthly report summarizing the information in iso 5.1 shall be submitted each calendar quarter he 15th day of the month following the end of the ter, in a format approved by the Department in nce.	ADEM Admin. Code R. 335-3-104
3.	facili inclu acco	accordance with 40 CFR Part 63, Subppart JJ, the ty shall maintain the records required by §63.804, ading the recordkeeping required by §63.10 rding to the applicability criteria in §63.800(d), and other requirements.	R. 335-3-1106(35)
4.	requ "Nat: Man	source is subject to the applicable recordkeeping irements of 40 CFR Part 63 Subpart JJ §63.806, ional Emission Standards for Wood Furniture ufacturing Operations" to include §63.806 (a) ugh (e), and (h) through (j).	
5.	requ "Nat Man	source is subject to the applicable reporting irements of 40 CFR Part 63 Subpart JJ §63.807, ional Emission Standards for Wood Furniture ufacturing Operations" to include §63.807 (a) ugh (c), and (e). This requirement requires a semi-	R. 335-3-1106(35)

Federally Enforceable Provisos	Regulations
annual statement of compliance.	

1

005

Emission Unit(s):

Off-Line Booth(s)

Designation No(s). in Application:

Description:

Off-Line Booth(s)

Type and quantity of fuel used:

Primary:

None

Secondary:

None

Pollutant	Regulatory Emission Limit	Applicable Standard
VOCs	245 TONS OF VOCS PER	SYNTHETIC MINOR PSD
	ROLLING 12 MONTH PERIOD	
HAPs	0.8 LB VHAPs/POUND	MACT
	SOLIDS AT THE APPLICATOR	
	FOR ALL COATINGS	

Unit Specific Provisos

Fede	rally Enforceable Provisos	Regulations
Secti	on 1Applicability	
1.	This source is subject to the applicable requirements of ADEM Admin. Code R. 335-3-1603, "Major Source Operating Permits."	ADEM Admin. Code R. 335-3-16.03
2.	This source is subject to the National Emission Standards for Hazardous Air Pollutants (NESHAPs) for Hazardous Air Pollutant (HAP) Emissions from Wood Furniture Manufacturing Operations as an "New Source" as listed in 40 CFR Part §63 Subpart JJ, to include 40 CFR Part §63.800(a) among other requirements.	ADEM Admin. Code R. 335-3-1106(35)
3.	This source is subject to a PSD synthetic minor emission limitation.	ADEM Admin. Code R. 335-3-1404
Secti	on 2Emission Standards	
1.	This facility shall not emit a weighted average of greater than 0.8 pound of VHAPs per pound of solids as delivered to the applicator for all coatings as determined by a monthly average as listed in Table 3 of 40 CFR Part §63 Subpart JJ, among other requirements. The facility is currently complying with this requirement with compliant coatings.	ADEM Admin. Code R. 335-3-1106(35)
2.	Emission of Volatile Organic Compounds (VOCs) from all surface coating operations from this facility, including, but not limited to coating, storage, cleanup, etc., shall not exceed 245 tons per year (TPY) in any consecutive rolling 12-month period based on the premise that all VOCs applied are emitted.	ADEM Admin. Code R. 335-3-1404(8)
3.	This facility is subject to the applicable work practice standards of 40 CFR Part 63 Subpart JJ §63.803 "National Emission Standards for Wood Furniture Manufacturing Operations" to include §63.803 (a) through (l).	

Fede	Federally Enforceable Provisos Regulations				
Sect	ion 3(Compliance and Performance Test Methods and			
Proc	edures				
1.	mate Meth Vend	OC content by weight of each VOC containing rial used shall be determined using EPA Test od 24, as defined in 40 CFR 60, Appendix A. for data based on this method is an appropriate titute.	ADEM Admin. Code R. 335-3-104		
2.	of 40 Emis	source is subject to the applicable testing methods O CFR Part 63 Subpart JJ §63.805, "National sion Standards for Wood Furniture Manufacturing ations" to include §63.805 (a).	ADEM Admin. Code R. 335-3-1106(35)		
3.	proce "Nati Manı	source is subject to the applicable compliance edures of 40 CFR Part 63 Subpart JJ §63.804, onal Emission Standards for Wood Furniture afacturing Operations" to include §63.804 (a) agh (c), (f), and (g).	ADEM Admin. Code R. 335-3-1106(35)		
Sect	ion 4 !	Emission Monitoring			
1.	requi	nonitoring requirements in this permit shall be as ired in Section 5Recordkeeping and Reporting irements.			
Sect	ion 5I	Recordkeeping and Reporting Requirements			
1.	cons of da suita upon recor requ	rate and understandable monthly records of umption, which record at least the last five years ta, will be maintained in a permanent form ble for inspection and be available immediately request. This facility shall provide a copy of eds and supporting background documents upon est that pertain to this air permit. These records contain the following information:	ADEM Admin. Code R. 335-3-104		
	(a)	The type, quantity in gallons, and weight in pounds of each VOC or HAP containing material used during each calendar month.			
	(b)	The percent by weight of VOCs, water, solids, VHAPs, and exempt VOC compounds content of each VOC containing material used each calendar month.			
	(c)	The percent by volume of VOCs, water, solids, VHAPs,			

Fede	rally l	Enforceable Provisos	Regulations
		and exempt VOC compounds content of each VOC containing material used each calendar month.	
	(d)	Compliance with VOC and VHAP limits shall be based upon monthly material use inventories. Emissions may be adjusted for VOC and VHAP content of material removed from the plant as waste or returns if the record keeping and details surrounding the materials are approved in advance.	
	(e)	Complete inventories of the VOC and HAP containing materials (their usage, VOC content and VHAP content) shall be made at the end of each calendar month.	
	(f)	The amount of VOCs emitted per calendar month from the coating and cleaning operations in units of pounds and tons	
	(g)	The rolling 12-month total of VOCs emitted from the coating and cleaning operations in units of pounds and tons.	
2.	provi by th	nonthly report summarizing the information in iso 5.1 shall be submitted each calendar quarter ne 15th day of the month following the end of the ter, in a format approved by the Department in nce.	ADEM Admin. Code R. 335-3-104
3.	facili inclu acco	accordance with 40 CFR Part 63, Subppart JJ, the ty shall maintain the records required by §63.804, adding the recordkeeping required by §63.10 rding to the applicability criteria in §63.800(d), and other requirements.	ADEM Admin. Code R. 335-3-1106(35)
4.	requ "Nati Man	source is subject to the applicable recordkeeping irements of 40 CFR Part 63 Subpart JJ §63.806, ional Emission Standards for Wood Furniture ufacturing Operations" to include §63.806 (a) ugh (e), and (h) through (j).	
5.	requ "Nati Man	source is subject to the applicable reporting irements of 40 CFR Part 63 Subpart JJ §63.807, ional Emission Standards for Wood Furniture ufacturing Operations" to include §63.807 (a) ugh (c), and (e). This requirement requires a semi-	R. 335-3-1106(35)

Federally Enforceable Provisos	Regulations
annual statement of compliance.	
	1

Emission Unit(s):

Woodworking Operations with

Cyclone/Baghouse

Designation No(s). in

003

Application:

Description:

Woodworking Operations with Cyclone

Type and quantity of fuel used:

Primary:

None

Secondary:

None

Pollutant	Regulatory Emission Limit	Applicable Standard
Opacity	Only one 6-minute average opacity greater than 20% in a 60-minute period; No 6-minute average opacity greater than 40%	SIP
Particulates	$E = 3.59(P^{0.62})$	SIP

Unit	Specific	Provisos
os		

Fede	erally Enforceable Provisos	Regulations
Sect	ion 1Applicability	
1.	This unit is subject to the opacity emission rate limits.	ADEM Admin. Code R. 335-3-401
2.	This unit is subject to the particulate emission rate limits for Process Industries - General sources.	ADEM Admin. Code R. 335-3-404
Sect	ion 2Emission Standards	
1.	This unit shall not discharge into the atmosphere opacity greater than twenty percent (20%), as determined by a six (6) minute average. During one six (6) minute period during any sixty (60) minute period, this unit may discharge opacity not exceeding forty (40%) percent.	ADEM Admin. Code R. 335-3-401
2.	This unit shall not discharge into the atmosphere particulate matter in any one hour in excess of $E = 3.59(P^{0.62})$ where P is the process weight in tons/hr.	ADEM Admin. Code R. 335-3-404
	ion 3–Compliance and Performance Test Methods and edures	
1.	Method 9 as defined in 40 CFR 60, Appendix A shall be used in the determination of the opacity of the stack emissions.	ADEM Admin. Code R. 335-3-105
2.	Method 5 as defined in 40 CFR 60, Appendix A shall be used in the determination of particulate emissions from the stack.	ADEM Admin. Code R. 335-3-105
Sect	ion 4Emission Monitoring	
1.	When the process is operating, someone familiar with the process shall perform a visible emissions check during daylight hours on the baghouse at a minimum of once weekly for excess visible emissions as determined by previous observations.	ADEM Admin. Code R.335-3-1605(c)(1)ii
2.	Whenever excess visible emissions are observed, corrective action to minimize emissions shall be taken as soon as practicable, but at least within 24 hours, followed by an additional visible emissions check to confirm that emissions are reduced to normal.	ADEM Admin. Code R.335-3-1605(c)(1)ii

Fede	erally Enforceable Provisos	Regulations
3.	The cyclone shall be inspected for proper operation and cleaned at least annually and whenever observed emissions are greater than normal.	ADEM Admin. Code R.335-3-1605(c)(1)ii
Sect	ion 5Recordkeeping and Reporting Requirements	
1.	A logbook of the weekly visible observations required in the Emission Monitoring Section shall be retained for at least five years and be available for inspection upon request. Each entry shall include the date, time, result, and identification of the observer. This logbook should also include the nature and date of any maintenance actions including those taken to correct excess opacity episodes.	ADEM Admin. Code R. 335-3-104

f

Emission Unit(s):

Woodworking Operations with

Cyclone/Baghouse

Designation No(s). in

004

Application:

Description:

Woodworking Operations with Baghouse

Type and quantity of fuel used:

Primary:

None

Secondary:

None

Foliutants Emitted.		
Pollutant	Regulatory Emission Limit	Applicable Standard
Opacity	Only one 6-minute average opacity greater than 20% in a 60-minute period; No 6-minute average opacity greater than 40%	SIP
Particulates	$E = 3.59(P^{0.62})$	SIP

Unit Specific Provisos			
Feder	rally Enforceable Provisos	Regulations	
	on 1Applicability This unit is subject to the opacity emission rate limits.	ADEM Admin. Code R. 335-3-401	
2.	This unit is subject to the particulate emission rate limits for Process Industries - General sources.	ADEM Admin. Code R. 335-3-404	
Section 2Emission Standards			
1.	This unit shall not discharge into the atmosphere opacity greater than twenty percent (20%), as determined by a six (6) minute average. During one six (6) minute period during any sixty (60) minute period, this unit may discharge opacity not exceeding forty (40%) percent.	ADEM Admin. Code R. 335-3-401	
2.	This unit shall not discharge into the atmosphere particulate matter in any one hour in excess of $E = 3.59(P^{0.62})$ where P is the process weight in tons/hr.	ADEM Admin. Code R. 335-3-404	
Section 3Compliance and Performance Test Methods and Procedures			
1.	Method 9 as defined in 40 CFR 60, Appendix A shall be used in the determination of the opacity of the stack emissions.	ADEM Admin. Code R. 335-3-105	
2.	Method 5 as defined in 40 CFR 60, Appendix A shall be used in the determination of particulate emissions from the stack.	ADEM Admin. Code R. 335-3-105	
Section 4Emission Monitoring			
1.	When the process is operating, someone familiar with the process shall perform a visible emissions check during daylight hours on the baghouse at a minimum of once weekly for excess visible emissions as determined by previous observations.	ADEM Admin. Code R.335-3-1605(c)(1)ii	
2.	Whenever excess visible emissions are observed, corrective action to minimize emissions shall be taken as soon as practicable, but at least within 24 hours, followed by an additional visible emissions check to confirm that emissions are reduced to normal.	ADEM Admin. Code R.335-3-1605(c)(1)ii	

	a di Burriana	Regulations
Fede:	The cyclone shall be inspected for proper operation and cleaned at least annually and whenever observed emissions are greater than normal.	ADEM Admin. Code R.335-3-1605(c)(1)ii
Secti	on 5Recordkeeping and Reporting Requirements	
1.	A logbook of the weekly visible observations required in the Emission Monitoring Section shall be retained for at least five years and be available for inspection upon request. Each entry shall include the date, time, result, and identification of the observer. This logbook should also include the nature and date of any maintenance actions including those taken to correct excess opacity episodes.	ADEM Admin. Code R. 335-3-104