

SYNTHETIC MINOR OPERATING PERMIT

PERMITTEE: VESTIS SERVICES, LLC
FACILITY NAME: DECATUR FACILITY
LOCATION: DECATUR, MORGAN COUNTY, ALABAMA

PERMIT NUMBER	DESCRIPTION OF EQUIPMENT, ARTICLE OR DEVICE
712-0114-X001	Industrial Laundering Process consisting of: – 10.46 MMBtu/hr Cleaver Brooks Natural Gas-fired Boiler (40 CFR Part 60, Subpart Dc) – 0.8 MMBtu/hr Natural Gas-fired Steam Tunnel – Two (2) 400 lb G.A. Braun Industrial Washers – One (1) 600 lb G.A. Braun Industrial Washer – Four (4) 675 lb Ellis Industrial Washers – One (1) 900 lb Ellis Industrial Washer – Two (2) 200 lb Milnor Industrial Washers – One (1) 90 lb G.A. Braun Industrial Washer – Two (2) 2.90 MMBtu/hr Challenge Natural Gas-fired Dryers – Two (2) 2.70 MMBtu/hr Challenge Natural Gas-fired Dryers – One (1) 0.395 MMBtu/hr Unimac Natural Gas-fired Dryer

In accordance with and subject to the provisions of the Alabama Air Pollution Control Act of 1971, Ala. Code §§ 22-28-1 to 22-28-23, as amended, the Alabama Environmental Management Act, Ala. Code §§ 22-22A-1 to 22-22A-17, as amended, and rules and regulations adopted there under, and subject further to the conditions set forth in this permit, the Permittee is hereby authorized to construct, install and use the equipment, device or other article described above.

ISSUANCE DATE: DRAFT

Alabama Department of Environmental Management

1. This permit is issued on the basis of Rules and Regulations existing on the date of issuance. In the event additional Rules and Regulations are adopted, it shall be the permit holder's responsibility to comply with such rules.
2. This permit is not transferable. Upon sale or legal transfer, the new owner or operator must apply for a permit within 30 days.
3. A new permit application must be made for new sources, replacements, alterations or design changes which may result in the issuance of, or an increase in the issuance of, air contaminants, or the use of which may eliminate or reduce or control the issuance of air contaminants.
4. The permittee shall keep this permit under file or on display at all times at the site where the facility for which the permit is issued is located and shall make the permit readily available for inspection by any or all persons who may request to see it.
5. Each point of emission, which requires testing, will be provided with sampling ports, ladders, platforms, and other safety equipment to facilitate testing performed in accordance with procedures established by Part 60 of Title 40 of the Code of Federal Regulations, as the same may be amended or revised.
6. All air pollution control equipment shall be operated at all times while this process is operational. In the event of scheduled maintenance, unscheduled maintenance, or a breakdown of the pollution control equipment, the process shall be shut down as expeditiously as possible (unless this act and subsequent re-start would clearly cause greater emissions than continuing operations of the process for a short period). The Department shall be notified of all such events **that exceed 1 hour** within 24 hours. The notification shall include all pertinent facts, including the duration of the process operating without the control device and the level of excess emissions which have occurred. Records of all such events, regardless of reporting requirements, shall be made and maintained for a period of five years. These records shall be available for inspection.
7. This process, including all air pollution control devices and capture systems for which this permit is issued, shall be maintained and operated at all times in a manner so as to minimize the emissions of air contaminants. Procedures for ensuring that the above equipment is properly operated and maintained so as to minimize the emission of air contaminants shall be established.
8. Submittal of other reports regarding monitoring records, fuel analyses, operating rates, and equipment malfunctions may be required as authorized in the Department's air pollution control rules and regulations. The Department may require stack emission testing at any time.
9. Additions and revisions to the conditions of this Permit will be made, if necessary, to ensure that the Department's air pollution control rules and regulations are not violated.

10. Nothing in this permit or conditions thereto shall negate any authority granted to the Air Division pursuant to the Alabama Environmental Management Act or regulations issued thereunder.
11. Unless otherwise stated in this permit or an applicable regulation, the Air Division must be notified in writing at least 10 working days in advance of all emission tests to be conducted and submitted as proof of compliance with the Department's air pollution control rules and regulations.

To avoid problems concerning testing methods and procedures, the following shall be included with the notification letter:

- (a) The date the test crew is expected to arrive, the date and time anticipated of the start of the first run, how many and which sources are to be tested, and the names of the persons and/or testing company that will conduct the tests.
- (b) A complete description of each sampling train to be used, including type of media used in determining gas stream components, type of probe lining, type of filter media, and probe cleaning method and solvent to be used (if test procedure requires probe cleaning).
- (c) A description of the process(es) to be tested, including the feed rate, any operating parameter used to control or influence the operations, and the rated capacity.
- (d) A sketch or sketches showing sampling point locations and their relative positions to the nearest upstream and downstream gas flow disturbances.

A pretest meeting may be held at the request of the source owner or the Department. The necessity for such a meeting and the required attendees will be determined on a case-by-case basis.

All test reports must be submitted to the Air Division within 30 days of the actual completion of the test, unless an extension of time is specifically approved by the Air Division.

12. Any performance tests required shall be conducted and data reduced in accordance with the test methods and procedures contained in each specific permit condition unless the Director (1) specifies or approves, in specific cases, the use of a reference method with minor changes in methodology, (2) approves the use of an equivalent method, or (3) approves the use of an alternative method, the results of which he has determined to be adequate for indicating whether a specific source is in compliance.
13. This permit is issued with the condition that, should obnoxious odors arising from the plant operations be verified by Air Division inspectors, measures to abate the odorous emissions shall be taken upon a determination by the Alabama Department of Environmental Management that these measures are technically and economically feasible.

14. Precautions shall be taken to prevent fugitive dust emanating from plant roads, grounds, stockpiles, screens, dryers, hoppers, ductwork, etc.

Plant or haul roads and grounds will be maintained in the following manner so that dust will not become airborne. A minimum of one, or a combination, of the following methods shall be utilized to minimize airborne dust from plant or haul roads and grounds:

- (a) by the application of water any time the surface of the road is sufficiently dry to allow the creation of dust emissions by the act of wind or vehicular traffic;
- (b) by reducing the speed of vehicular traffic to a point below that at which dust emissions are created;
- (c) by paving;
- (d) by the application of binders to the road surface at any time the road surface is found to allow the creation of dust emissions;

Should one, or a combination, of the above methods fail to adequately reduce airborne dust from plant or haul roads and grounds, alternative methods shall be employed, either exclusively or in combination with one or all of the above control techniques, so that dust will not become airborne. Alternative methods shall be approved by the Department prior to utilization.

15. Precautions shall be taken by the permittee and its personnel to ensure that no person shall ignite, cause to be ignited, permit to be ignited, or maintain any open fire in such a manner as to cause the Department's rules and regulations applicable to open burning to be violated.
16. In accordance with ADEM Admin. Code. r. 335-3-4-.01(1), any source of particulate emissions shall not discharge more than one 6-minute average opacity greater than 20% in any 60-minute period. At no time shall any source discharge a 6-minute average opacity of particulate emissions greater than 40%. Opacity shall be determined by 40 CFR Part 60, Appendix A, Method 9.
17. The permittee shall not use as a defense in an enforcement action that maintaining compliance with conditions of this permit would have required halting or reducing the permitted activity.
18. The issuance of this permit does not convey any property rights of any sort, or any exclusive privilege.

19. In accordance with ADEM Admin. Code r. 335-3-4-.03, the permittee shall not cause or allow emissions of particulate matter (PM) from the natural gas-fired boiler, dryers, and steam tunnel in excess of the allowable emission rate calculated using the following equation:

$$E = 1.38H^{-0.44}$$

Where
E = Emissions in lb/million BTU
H = Heat input in millions of BTU/hr

20. The permittee shall not cause or allow emissions of sulfur dioxide (SO₂) from the natural gas-fired boiler, dryers, and steam tunnel in excess of 4.0 pounds per million Btu (lb/MMBtu) heat input, in accordance with ADEM Admin. Code r. 335-3-5-.01(b).

New Source Performance Standards (NSPS) Requirements

21. The 10.46 MMBtu/hr natural gas-fired boiler is subject to the applicable requirements of 40 CFR Part 60, Subpart Dc, Standards of Performance for New Stationary Sources; Small Industrial-Commercial-Institutional Steam Generating Units, which include, but may not be limited to the following:
- (a) Records of daily or monthly fuel usage shall be recorded and maintained in a permanent form suitable for inspection [40 CFR §60.48c(g)];
 - (b) All records required under Subpart Dc shall be maintained for a period of two years from the date of generation and be made available upon request [40 CFR §60.48c(i)]

Synthetic Minor Source Requirements

22. The permittee shall not cause or allow shop towel processing to exceed 20,000,000 pounds during any consecutive 12-month period from this process.
23. By the 10th day of each month, the permittee shall calculate and record the actual amount of shop towels processed, in pounds, on a monthly and 12-month rolling total basis for the previous calendar month and previous consecutive 12-month period.
24. The permittee shall maintain records of the monthly and 12-month rolling totals of the actual amount of shop towels processed, in pounds, as well as all supporting data utilized to calculate the actual amount of shop towels processed.
25. The permittee shall submit an annual report by **January 30th** of each year that provides each monthly and 12-month rolling total of the actual amount of shop towels processed, in pounds, during the previous calendar year.
26. Should the permittee, at any time, exceed the 20,000,000 pounds shop towel processing throughput limit, the permittee shall notify the Air Division in writing, within two (2) working days of determining that the exceedance occurred.

27. The permittee shall maintain a copy of all records and reports required by this permit for a period of five years from the date of generation of each record. Each record shall be in a permanent form suitable for inspection and shall be readily available for inspection upon request. For the first two years, the permittee shall maintain the records onsite. For the remaining three years, the permittee may maintain the records off-site as long as the permittee can readily access the records if requested by the Air Division.