

SYNTHETIC MINOR OPERATING PERMIT

PERMITTEE: COOPER STEEL SOUTH

FACILITY NAME:

LOCATION: CHILDERSBURG, TALLADEGA COUNTY, ALABAMA

PERMIT NUMBER	DESCRIPTION OF EQUIPMENT, ARTICLE OR DEVICE
309-0079-X001	Metal Surface Coating (EU01) and Steel Fabrication: Plasma Cutting Tables (EU03, EU08) Welding (EU04, EU13) Machining (EU05, EU06, EU07, EU10, EU12) Laser Cutting Table (EU11) OxyFuel Torches (EU14)

In accordance with and subject to the provisions of the Alabama Air Pollution Control Act of 1971, Ala. Code §§ 22-28-1 to 22-28-23, as amended, the Alabama Environmental Management Act, Ala. Code §§ 22-22A-1 to 22-22A-17, as amended, and rules and regulations adopted there under, and subject further to the conditions set forth in this permit, the Permittee is hereby authorized to construct, install and use the equipment, device or other article described above.

ISSUANCE DATE: DRAFT

Alabama Department of Environmental Management

1. This permit is issued on the basis of Rules and Regulations existing on the date of issuance. In the event additional Rules and Regulations are adopted, it shall be the permit holder's responsibility to comply with such rules.
2. This permit is not transferable. Upon sale or legal transfer, the new owner or operator must apply for a permit within 30 days.
3. A new permit application must be made for new sources, replacements, alterations or design changes which may result in the issuance of, or an increase in the issuance of, air contaminants, or the use of which may eliminate or reduce or control the issuance of air contaminants.
4. The permittee shall keep this permit under file or on display at all times at the site where the facility for which the permit is issued is located and shall make the permit readily available for inspection by any or all persons who may request to see it.
5. Each point of emission, which requires testing, will be provided with sampling ports, ladders, platforms, and other safety equipment to facilitate testing performed in accordance with procedures established by Part 60 of Title 40 of the Code of Federal Regulations, as the same may be amended or revised.
6. All air pollution control equipment shall be operated at all times while this process is operational. In the event of scheduled maintenance, unscheduled maintenance, or a breakdown of the pollution control equipment, the process shall be shutdown as expeditiously as possible (unless this act and subsequent re-start would clearly cause greater emissions than continuing operations of the process for a short period). The Department shall be notified of all such events **that exceed 2 hours** within 24 hours. The notification shall include all pertinent facts, including the duration of the process operating without the control device and the level of excess emissions which have occurred. Records of all such events, regardless of reporting requirements, shall be made and maintained for a period of five years. These records shall be available for inspection.
7. This process, including all air pollution control devices and capture systems for which this permit is issued, shall be maintained and operated at all times in a manner so as to minimize the emissions of air contaminants. Procedures for ensuring that the above equipment is properly operated and maintained so as to minimize the emission of air contaminants shall be established.
8. On completion of construction of the device(s) for which this permit is issued, written notification of the fact is to be submitted to the Chief of the Air Division. The notification shall indicate whether the device(s) was constructed as proposed in the application. The device(s) shall not be operated until authorization to operate is granted by the Chief of the Air Division. Failure to notify the Chief of the Air Division of completion of construction and/or operation without authorization could result in revocation of this permit.

9. Submittal of other reports regarding monitoring records, fuel analyses, operating rates, and equipment malfunctions may be required as authorized in the Department's air pollution control rules and regulations. The Department may require stack emission testing at any time.
10. Additions and revisions to the conditions of this Permit will be made, if necessary, to ensure that the Department's air pollution control rules and regulations are not violated.
11. Nothing in this permit or conditions thereto shall negate any authority granted to the Air Division pursuant to the Alabama Environmental Management Act or regulations issued thereunder.
12. Unless otherwise stated in this permit or an applicable regulation, the Air Division must be notified in writing at least 10 working days in advance of all emission tests to be conducted and submitted as proof of compliance with the Department's air pollution control rules and regulations.

To avoid problems concerning testing methods and procedures, the following shall be included with the notification letter:

- (a) The date the test crew is expected to arrive, the date and time anticipated of the start of the first run, how many and which sources are to be tested, and the names of the persons and/or testing company that will conduct the tests.
- (b) A complete description of each sampling train to be used, including type of media used in determining gas stream components, type of probe lining, type of filter media, and probe cleaning method and solvent to be used (if test procedure requires probe cleaning).
- (c) A description of the process(es) to be tested, including the feed rate, any operating parameter used to control or influence the operations, and the rated capacity.
- (d) A sketch or sketches showing sampling point locations and their relative positions to the nearest upstream and downstream gas flow disturbances.

A pretest meeting may be held at the request of the source owner or the Department. The necessity for such a meeting and the required attendees will be determined on a case-by-case basis.

All test reports must be submitted to the Air Division within 30 days of the actual completion of the test, unless an extension of time is specifically approved by the Air Division.

13. Any performance tests required shall be conducted and data reduced in accordance with the test methods and procedures contained in each specific permit condition unless the Director (1) specifies or approves, in specific cases, the use of a reference method with minor changes in methodology, (2) approves the use of an equivalent method, or (3)

approves the use of an alternative method, the results of which he has determined to be adequate for indicating whether a specific source is in compliance.

14. This permit is issued with the condition that, should obnoxious odors arising from the plant operations be verified by Air Division inspectors, measures to abate the odorous emissions shall be taken upon a determination by the Alabama Department of Environmental Management that these measures are technically and economically feasible.
15. Precautions shall be taken to prevent fugitive dust emanating from plant roads, grounds, stockpiles, screens, dryers, hoppers, ductwork, etc.

Plant or haul roads and grounds will be maintained in the following manner so that dust will not become airborne. A minimum of one, or a combination, of the following methods shall be utilized to minimize airborne dust from plant or haul roads and grounds:

- (a) by the application of water any time the surface of the road is sufficiently dry to allow the creation of dust emissions by the act of wind or vehicular traffic;
- (b) by reducing the speed of vehicular traffic to a point below that at which dust emissions are created;
- (c) by paving;
- (d) by the application of binders to the road surface at any time the road surface is found to allow the creation of dust emissions;

Should one, or a combination, of the above methods fail to adequately reduce airborne dust from plant or haul roads and grounds, alternative methods shall be employed, either exclusively or in combination with one or all of the above control techniques, so that dust will not become airborne. Alternative methods shall be approved by the Department prior to utilization.

16. Precautions shall be taken by the permittee and its personnel to ensure that no person shall ignite, cause to be ignited, permit to be ignited, or maintain any open fire in such a manner as to cause the Department's rules and regulations applicable to open burning to be violated.
17. In accordance with ADEM Admin. Code. r. 335-3-4-.01(1), any source of particulate emissions shall not discharge more than one 6-minute average opacity greater than 20% in any 60-minute period. At no time shall any source discharge a 6-minute average opacity of particulate emissions greater than 40%. Opacity shall be determined by 40 CFR Part 60, Appendix A, Method 9.
18. Should this facility, at any time, exceeds the limits for VOC, HAP, or propane usage, the permittee shall notify the Air Division within two (2) working days of determining that the exceedance occurred.

19. The permittee shall not use as a defense in an enforcement action that maintaining compliance with conditions of this permit would have required halting or reducing the permitted activity.
20. The issuance of this permit does not convey any property rights of any sort, or any exclusive privilege.
21. Emissions of Volatile Organic Compounds from this facility shall not exceed 95.0 tons per year in any consecutive rolling 12-month period, based on the premise that all Volatile Organic Compounds applied are emitted. If the emission of Volatile Organic Compounds exceeds this limit, then ADEM shall be notified in writing within 10 days of the exceedance. Accurate and understandable records of Volatile Organic Compound consumption which records at least the last two years of data will be maintained in a permanent form suitable for inspection and be available immediately upon request. These records shall contain the following information:
 - A. The type and quantity of each Volatile Organic Compound containing material used during each calendar month.
 - B. The Volatile Organic Compound content by weight of each coating used shall be determined using EPA Method 24, as defined in 40 CFR 60, Appendix A, or equivalent vendor data approved by the Department in advance.
 - C. Compliance with Volatile Organic Compound limits shall be based upon monthly material use inventories. Emissions may be adjusted for the Volatile Organic Compound content of materials removed from the plant as waste or returns if the record keeping and details surrounding the materials are approved in advance.
 - D. Complete inventories of Volatile Organic Compound containing materials (their usage and Volatile Organic Compound content) shall be made at the end of each month.
 - E. The amount of each Volatile Organic Compound emitted each calendar month expressed in units of pounds and tons.
 - F. The rolling 12-month total of each Volatile Organic Compound emitted expressed in units of pounds and tons.

A report summarizing the above information shall be submitted by January 15, April 15, July 15, and October 15 each year, in a format approved by the Department in advance.
22. Emissions of Hazardous Air Pollutants from this facility will not exceed 24.0 tons per year in any consecutive rolling 12-month period, based on the premise that all Hazardous Air Pollutants applied are emitted. Emissions of Hazardous Air Pollutants from this facility will not exceed 9.0 tons per year per pollutant in any consecutive rolling 12-month period, based on the premise that all Hazardous Air Pollutants applied are emitted. If the emission of Hazardous Air Pollutants exceeds either of these limits, then ADEM shall be notified in writing within 10 days of the exceedance. Accurate and understandable records of

Hazardous Air Pollutant consumption which records at least the last two years of data will be maintained in a permanent form suitable for inspection and be available immediately upon request. These records shall contain the following information:

- A. The type and quantity of each Hazardous Air Pollutant containing material used during each calendar month.
- B. The Hazardous Air Pollutant content by weight of each coating used shall be determined using EPA Method 311, as defined in 40 CFR 63, Appendix A, or equivalent vendor data approved by the Department in advance.
- C. Compliance with Hazardous Air Pollutant limits shall be based upon monthly material use inventories. Emissions may be adjusted for the Hazardous Air Pollutant content of materials removed from the plant as waste or returns if the record keeping and details surrounding the materials are approved in advance.
- D. Complete inventories of Hazardous Air Pollutant containing materials (their usage and Hazardous Air Pollutant content) shall be made at the end of each month.
- E. The amount of each Hazardous Air Pollutant emitted each calendar month expressed in units of pounds and tons.
- F. The rolling 12-month total of each Hazardous Air Pollutant emitted expressed in units of pounds and tons.

A report summarizing the above information shall be submitted by January 15, April 15, July 15, and October 15 each year, in a format approved by the Department in advance.

- 23. The Oxyfuel Torches (EU14) shall not be operated more than 700 hours each in any rolling 12-month period. Compliance with the hours of operation limit shall be demonstrated by utilizing no more than 420,000 standard cubic feet (scf) of propane fuel for this unit in any rolling 12-month period. Records of the propane fuel usage for this unit shall be maintained and readily available for inspection for a period of at least five (5) years.
- 24. This facility shall follow the applicable standards and management practices stated in §63.11516 of 40 CFR Part 63 Subpart XXXXXX, the National Emission Standards for Hazardous Air Pollutants Area Source Standards for Nine Metal Fabrication and Finishing Source Categories.
 - (a) The monitoring requirements stated in §63.11517 of Subpart XXXXXX shall be followed, as applicable.
 - (b) The recordkeeping and reporting requirements stated in §63.11519 of Subpart XXXXXX shall be followed, as applicable.
 - (c) An annual compliance and certification report covering the reporting period of January 1 through December 31 of the previous year shall be submitted to the Department no later than January 31 of the following year as required by §63.11519(b) of Subpart XXXXXX.

SYNTHETIC MINOR OPERATING PERMIT

PERMITTEE: COOPER STEEL SOUTH

FACILITY NAME:

LOCATION: CHILDERSBURG, TALLADEGA COUNTY, ALABAMA

PERMIT NUMBER	DESCRIPTION OF EQUIPMENT, ARTICLE OR DEVICE
309-0079-X002	Two Enclosed Shot Blasting Machines each with Particulate Filters (EU02, EU09)

In accordance with and subject to the provisions of the Alabama Air Pollution Control Act of 1971, Ala. Code §§ 22-28-1 to 22-28-23, as amended, the Alabama Environmental Management Act, Ala. Code §§ 22-22A-1 to 22-22A-17, as amended, and rules and regulations adopted there under, and subject further to the conditions set forth in this permit, the Permittee is hereby authorized to construct, install and use the equipment, device or other article described above.

ISSUANCE DATE: DRAFT

Alabama Department of Environmental Management

1. This permit is issued on the basis of Rules and Regulations existing on the date of issuance. In the event additional Rules and Regulations are adopted, it shall be the permit holder's responsibility to comply with such rules.
2. This permit is not transferable. Upon sale or legal transfer, the new owner or operator must apply for a permit within 30 days.
3. A new permit application must be made for new sources, replacements, alterations or design changes which may result in the issuance of, or an increase in the issuance of, air contaminants, or the use of which may eliminate or reduce or control the issuance of air contaminants.
4. The permittee shall keep this permit under file or on display at all times at the site where the facility for which the permit is issued is located and shall make the permit readily available for inspection by any or all persons who may request to see it.
5. Each point of emission, which requires testing, will be provided with sampling ports, ladders, platforms, and other safety equipment to facilitate testing performed in accordance with procedures established by Part 60 of Title 40 of the Code of Federal Regulations, as the same may be amended or revised.
6. All air pollution control equipment shall be operated at all times while this process is operational. In the event of scheduled maintenance, unscheduled maintenance, or a breakdown of the pollution control equipment, the process shall be shutdown as expeditiously as possible (unless this act and subsequent re-start would clearly cause greater emissions than continuing operations of the process for a short period). The Department shall be notified of all such events that exceed 2 hours within 24 hours. The notification shall include all pertinent facts, including the duration of the process operating without the control device and the level of excess emissions which have occurred. Records of all such events, regardless of reporting requirements, shall be made and maintained for a period of five years. These records shall be available for inspection.
7. This process, including all air pollution control devices and capture systems for which this permit is issued, shall be maintained and operated at all times in a manner so as to minimize the emissions of air contaminants. Procedures for ensuring that the above equipment is properly operated and maintained so as to minimize the emission of air contaminants shall be established.
8. This permit expires and the application is cancelled if construction has not begun within 24 months of the date of issuance of the permit.
9. On completion of construction of the device(s) for which this permit is issued, written notification of the fact is to be submitted to the Chief of the Air Division. The notification shall indicate whether the device(s) was constructed as proposed in the application. The device(s) shall not be operated until authorization to operate is granted by the Chief of the Air Division. Failure to notify the Chief of the Air Division of completion of construction and/or operation without authorization could result in revocation of this permit.

10. Additions and revisions to the conditions of this Permit will be made, if necessary, to ensure that the Department's air pollution control rules and regulations are not violated.
11. Nothing in this permit or conditions thereto shall negate any authority granted to the Air Division pursuant to the Alabama Environmental Management Act or regulations issued thereunder.
12. Unless otherwise stated in this permit or an applicable regulation, the Air Division must be notified in writing at least 10 working days in advance of all emission tests to be conducted and submitted as proof of compliance with the Department's air pollution control rules and regulations.

To avoid problems concerning testing methods and procedures, the following shall be included with the notification letter:

- (a) The date the test crew is expected to arrive, the date and time anticipated of the start of the first run, how many and which sources are to be tested, and the names of the persons and/or testing company that will conduct the tests.
- (b) A complete description of each sampling train to be used, including type of media used in determining gas stream components, type of probe lining, type of filter media, and probe cleaning method and solvent to be used (if test procedure requires probe cleaning).
- (c) A description of the process(es) to be tested, including the feed rate, any operating parameter used to control or influence the operations, and the rated capacity.
- (d) A sketch or sketches showing sampling point locations and their relative positions to the nearest upstream and downstream gas flow disturbances.

A pretest meeting may be held at the request of the source owner or the Department. The necessity for such a meeting and the required attendees will be determined on a case-by-case basis.

All test reports must be submitted to the Air Division within 30 days of the actual completion of the test, unless an extension of time is specifically approved by the Air Division.

13. Any performance tests required shall be conducted and data reduced in accordance with the test methods and procedures contained in each specific permit condition unless the Director (1) specifies or approves, in specific cases, the use of a reference method with minor changes in methodology, (2) approves the use of an equivalent method, or (3) approves the use of an alternative method, the results of which he has determined to be adequate for indicating whether a specific source is in compliance.
14. This permit is issued with the condition that, should obnoxious odors arising from the plant operations be verified by Air Division inspectors, measures to abate the odorous emissions

shall be taken upon a determination by the Alabama Department of Environmental Management that these measures are technically and economically feasible.

15. Precautions shall be taken to prevent fugitive dust emanating from plant roads, grounds, stockpiles, screens, dryers, hoppers, ductwork, etc.

Plant or haul roads and grounds will be maintained in the following manner so that dust will not become airborne. A minimum of one, or a combination, of the following methods shall be utilized to minimize airborne dust from plant or haul roads and grounds:

- (a) by the application of water any time the surface of the road is sufficiently dry to allow the creation of dust emissions by the act of wind or vehicular traffic;
- (b) by reducing the speed of vehicular traffic to a point below that at which dust emissions are created;
- (c) by paving;
- (d) by the application of binders to the road surface at any time the road surface is found to allow the creation of dust emissions;

Should one, or a combination, of the above methods fail to adequately reduce airborne dust from plant or haul roads and grounds, alternative methods shall be employed, either exclusively or in combination with one or all of the above control techniques, so that dust will not become airborne. Alternative methods shall be approved by the Department prior to utilization.

16. Precautions shall be taken by the permittee and its personnel to ensure that no person shall ignite, cause to be ignited, permit to be ignited, or maintain any open fire in such a manner as to cause the Department's rules and regulations applicable to open burning to be violated.
17. In accordance with ADEM Admin. Code. r. 335-3-4-.01(1), any source of particulate emissions shall not discharge more than one 6-minute average opacity greater than 20% in any 60-minute period. At no time shall any source discharge a 6-minute average opacity of particulate emissions greater than 40%. Opacity shall be determined by 40 CFR Part 60, Appendix A, Method 9.
18. Particulate emissions from the dust collectors shall not exceed the limits of ADEM Code R. 335-3-4-.04(1).
19. The permittee shall not use as a defense in an enforcement action that maintaining compliance with conditions of this permit would have required halting or reducing the permitted activity.
20. The issuance of this permit does not convey any property rights of any sort, or any exclusive privilege.

21. The combined total shot media usage for both shot blasters (EU02, EU09) shall not exceed 100 tons (200,000 lbs) in any rolling 12-month period. Records of blast media usage shall be kept shall be maintained and readily available for inspection for a period of at least five (5) years. These records shall include the following:
- A. The quantity of shot media used during each calendar month expressed in units of pounds and tons.
 - B. The rolling 12-month total of shot media used expressed in units of pounds and tons.
- A report summarizing the above information shall be submitted by January 15, April 15, July 15, and October 15 each year, in a format approved by the Department in advance.
22. This facility shall follow the applicable standards and management practices stated in §63.11516 of 40 CFR Part 63 Subpart XXXXXX, the National Emission Standards for Hazardous Air Pollutants Area Source Standards for Nine Metal Fabrication and Finishing Source Categories.
- (a) The monitoring requirements stated in §63.11517 of Subpart XXXXXX shall be followed, as applicable.
 - (b) The recordkeeping and reporting requirements stated in §63.11519 of Subpart XXXXXX shall be followed, as applicable.
 - (c) An annual compliance and certification report covering the reporting period of January 1 through December 31 of the previous year shall be submitted to the Department no later than January 31 of the following year as required by §63.11519(b) of Subpart XXXXXX.